

FITTINGS

MF2000®



Fluid connectors, solid solutions

manuli®
HYDRAULICS

INTRODUCTION

GB

The range of hydraulic fittings applies to English BS (British Standard), American SAE and German DIN (Deutsches Institut für Normung) norms. Additional items conforming to Japanese norms JIS (Japanese Industrial Standard), French NF and some flanged head fittings for OEM applications are also included in the range.

For braid hose, MF2000® range is available with a no-skive or skive assembling technology.

For wire spiral hose MF2000® range is used with external skive.

For the highest pressure levels, the Interlock Plus range is recommended with internal and external skiving operations.

CN

液压接头系列符合英国BS (英国标准), 美国SAE和德国DIN (德国标准) 规范。

本系列还包括符合日本JIS规范 (日本工业标准) 和法国NF规范 (法国国家标准) 的部分产品以及某些OEM应用的法兰接头

对于编织胶管, 可使用采取不剥胶和剥胶总成技术的MF2000®系列。

对于缠绕胶管, 可使用采取外部剥胶技术的MF2000®系列。

对于高压胶管, 推荐使用采取内部和外部剥胶操作的内锁增强式系列。

D

SAE und DIN (Deutsches Institut für Normung). Ergänzende Produkte nach der japanischen Norm JIS (Japanese Industrial Standard), Französische NF Spezifikationen und einige Flanscharmaturen nach OEM-Vorschriften sind ebenfalls verfügbar.

Für Drahtgeflechschläuche steht das MF2000® Programm mit Schäl- oder Nicht-Schäl-Technologie zur Verfügung, während für die Superhochdruckanwendungen das MF2000® InterlockPlusprogramm mit Innen und Außenschälung die optimale Lösung darstellt.

IT

La gamma raccordi MRI comprende prodotti rispondenti alle norme inglesi BSP (British Standard Pipe), americane JIC (Joint Industrial Council) e tedesche DIN (Deutsches Institut für Normung). Sono inoltre disponibili ulteriori referenze conformi alle norme giapponesi JIS (Japanese Industrial Standard), francesi NF ed una gamma di flange speciali per specifiche applicazioni OEM. Per tubi con rinforzo trecciato è disponibile la gamma MF2000® con entrambe le soluzioni con e senza pelatura esterna del tubo. Per tubi con rinforzo in acciaio spiralato è utilizzata la gamma MF2000® con pelatura esterna, mentre, per le altissime pressioni, può essere utilizzata la gamma Interlock Plus che prevede la pelatura interna ed esterna del tubo.

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

MF2000® MULTIFIT TYPE FERRULE

M00110/M00120	SKIVE FERRULE FOR WIRE BRAID HOSES 钢丝编织管剥胶套筒 SCHÄLFASSUNG FÜR STAHLGEFLECHTSCHLÄUCHE GHIERA PER TUBI TRECCIATI CON PELATURA	157
M00910/M00920	SKIVE FERRULE FOR WIRE BRAID AND SPIRAL HOSES 钢丝编织/缠绕管剥胶套筒 SCHÄLFASSUNG FÜR STAHLGEFLECHT- UND SPIRALSCHLÄUCHE GHIERA PER TUBI TRECCIATI E SPIRALATI CON PELATURA	157
M03400	NO-SKIVE FERRULE FOR WIRE BRAID HOSES 钢丝编织管不剥胶套筒 NICHT-SCHÄLFASSUNG FÜR STAHLGEFLECHTSCHLÄUCHE GHIERA PER TUBI TRECCIATI SENZA PELATURA	158
M00310	NO-SKIVE FERRULE FOR TEXTILE BRAID HOSES 棉线编织管不剥胶套筒 NICHT-SCHÄLFASSUNG FÜR TEXTILGEFLECHTSCHLÄUCHE GHIERA PER TUBI TESSILI SENZA PELATURA	159
M00820/M00830	NO-SKIVE FERRULE FOR COMPACT HOSES 紧凑型胶管不剥胶套筒 NICHT-SCHÄLFASSUNG FÜR KOMPAKT-SCHLÄUCHE GHIERA PER TUBI COMPATTI SENZA PELATURA	159

MF2000® MULTIFIT TYPE INSERT BS STANDARD CONNECTIONS

M10710	BSP MALE TAPERED - ISO 7 BSP 锥形外螺纹 - ISO 7 AGR KONISCH (BSPT GEWINDE NACH) - ISO 7 MASCHIO CONICO GAS - ISO 7	160
M10510	BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6 BSP 平行外螺纹 (60° 锥形底座) - BS5200 / ISO 8434-6 AGR 60° INNENKONUS (BSP-GEWINDE NACH BS5200 / ISO 8434-6) MASCHIO GAS CILINDRICO 60° - BS5200 / ISO 8434-6	161
M20512	BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT) BSP 内螺纹 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER) FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)	162
M20513	BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT) BSP 内螺纹 (60° 锥) BS5200 / ISO 12151-6 (带滑套螺母) DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER) FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)	162
M20592	90° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 90° BSP 内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKR 90° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER) FEMMINA GAS 90° CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)	163
M20593	90° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT) 90° BSP 内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带滑套螺母) DKR 90° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER) FEMMINA GAS 90° CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)	163

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
M20542	45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 45° BSP 内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKR 45° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER) FEMMINA GAS 45° CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)	164
M20543	45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT) 45° BSP 内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带滑套螺母) DKR 45° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER) FEMMINA GAS 45° CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)	164
M20812	BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT) BSP O型圈内螺纹 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 60° KONUS MIT O-RING - (BSP-GEWINDE NACH BS5200 / ISO 12151-6 GESTIFTETE MUTTER) FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)	165
M20813	BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT) BSP O型圈内螺纹 (60° 锥) BS5200 / ISO 12151-6 (带滑套螺母) DKOR 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6 HINTERLEGTE MUTTER) FEMMINA GAS CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)	165
M20892	90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 90° BSP O型圈内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 90° BOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER) FEMMINA GAS 90° CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)	166
M20893	A90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT) 90° BSP O型圈内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带滑套螺母) DKOR 90° BOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6 HINTERLEGTE MUTTER) FEMMINA GAS 90° CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)	166
M20842	45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 45° BSP O型圈内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 45° BOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER) FEMMINA GAS 45° CONO 60° O-RING BS5200 / ISO 12151-6 (DADO SPINATO)	167
M20843	45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (SLIP-ON NUT) 45° BSP O型圈内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带滑套螺母) DKOR 45° BOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER) FEMMINA GAS 45° CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)	167
M20882F	90° BSP O-RING FEMALE COMPACT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 90° BSP O型圈内螺纹紧凑型弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 90° KOMPAKTBOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER) FEMMINA GAS 90° CONO 60° O-RING TIPO COMPATTO BS5200 / ISO 12151-6 (DADO SPINATO)	168
M10610	BSP MALE FLAT SEAT BSP 外螺纹平面底座 AGR FLACH DICHTEND MASCHIO GAS CILINDRICO SEDE PIANA	168
M20612	BSP FEMALE FLAT SEAT (THRUST-WIRE NUT) BSP 内螺纹平面底座 (带止推金属丝螺母) DKR FLACHDICHTEND (BSP-GEWINDE, GESTIFTETE MUTTER) FEMMINA GAS SEDE PIANA (DADO SPINATO)	169
M20613	BSP FEMALE FLAT SEAT (SLIP-ON NUT) BSP 内螺纹平面底座 (滑套螺母) DKR FLACHDICHTEND (BSP-GEWINDE, HINTERLEGTE MUTTER) FEMMINA GAS SEDE PIANA (DADO PASSANTE)	169

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

SAE STANDARD CONNECTIONS

JIC		
M12510	JIC MALE 37° CONE - SAE J516 / ISO 12151-5 JIC 外螺纹 37° 锥 - SAE J516 / ISO 12151-5 AGJ 37° AUSSENKONUS (UNF-GEWINDE NACH SAE J516 / ISO 12151-5) MASCHIO JIC CONO 37° - SAE J516 / ISO 12151-5	170
		
M22512	JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带止推金属丝螺母) DKJ 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)	171
		
M22513	JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT) JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带滑套螺母) DKJ 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER) FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)	171
		
M22711	JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (CRIMPED-BACK NUT) JIC 内螺纹 37° 锥形底座双六角螺母 - SAE J516 / ISO 12151-5 (带扣压-支撑螺母) DKJ 37° MIT KONTERSECHSKANT (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, VORGEKRIMPT MUTTER) FEMMINA JIC CONO 37° DOPPIO ESAGONO SAE J516 / ISO 12151-5 (DADO PRESSATO)	172
		
M22711K	JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (CRIMPED-BACK COMPACT NUT) JIC 内螺纹 37° 锥形底座双六角螺母 - SAE J516 / ISO 12151-5 (带扣压-支撑紧凑型螺母) DKJ (KOMPAKT) 37° MIT KONTERSECHSKANT (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, VORGEKRIMPT MUTTER) FEMMINA JIC CONO 37° DOPPIO ESAGONO - SAE J516 / ISO 12151-5 (DADO PRESSATO COMPATTO)	172
		
M22712K	JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (THRUST-WIRE COMPACT NUT) JIC 内螺纹 37° 锥形底座双六角螺母 - SAE J516 / ISO 12151-5 (带止推金属丝紧凑型螺母) DKJ KOMPAKT 37° DK MIT KONTERSECHSKANT (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC CONO 37° DOPPIO ESAGONO SAE J516 / ISO 12151-5 (DADO SPINATO COMPATTO)	173
		
M22712	JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) JIC 内螺纹 37° 锥形底座双六角螺母 - SAE J516 / ISO 12151-5 (带止推金属丝紧凑型螺母) DKJ 37° DK MIT KONTERSECHSKANT (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC CONO 37° DOPPIO ESAGONO SAE J516 / ISO 12151-5 (DADO SPINATO)	174
		
M22592	90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) 90° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母) DKJ 90° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC 90° CONO 37° SAE J516 / ISO 12151-5 (DADO SPINATO)	175
		
M22593	90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT) 90° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带滑套螺母) DKJ 90° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER) FEMMINA JIC 90° CONO 37° SAE J516 / ISO 12151-5 (DADO PASSANTE)	175
		
M24792	90° JIC FEMALE LONG DROP ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) 90° JIC 内螺纹加长弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母) DKJ 90° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC 90° CONO 37° CURVA LUNGA - SAE J516 / ISO 12151-5 (DADO SPINATO)	176
		
M24793	90° JIC FEMALE LONG DROP ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT) 90° JIC 内螺纹加长弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带滑套螺母) DKJ 90° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER) FEMMINA JIC 90° CONO 37° CURVA LUNGA - SAE J516 / ISO 12151-5 (DADO PASSANTE)	176
		
M22542	45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) 45° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母) DKJ 45° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)	177
		

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
M22543 	45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT) 45° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带滑套螺母) DKJ 45° BOGEN 37° DICHTKOPF (UND-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER) FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)	177
M22582F 	90° JIC FEMALE COMPACT ELBOW 37° CONE SEAT SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) 90° JIC 内螺纹紧凑型弯头 (37° 锥形底座) SAE J516 / ISO 12151-5 (带止推金属丝螺母) DKJ 90° KOMPAKT BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER) FEMMINA JIC 90° TIPO COMPATTO CONO 37° SAE J516 / ISO 12151-5 (DADO SPINATO)	178
ORFS		
M12410 	ORFS MALE - SAE J516 / ISO 12151-1 ORFS 外螺纹 - SAE J516 / ISO 12151-1 ORFS AUSSENGWINDE NACH SAE J516 / ISO 12151-1 MASCHIO ORFS - SAE J516 / ISO 12151-1	178
M22411 	ORFS FEMALE - SAE J516 / ISO 12151-1 PULLBACK TYPE (CRIMPED BACK-NUT) ORFS 内螺纹 - SAE J516 / ISO 12151-1 回拉式 (带扣压-支撑螺母) ORFS IG - SAE J516 / ISO 12151-1 RÜCKZUGSAUSFÜHRUNG (VERPRESSTE MUTTER) FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE RETRAIBILE (DADO PRESSATO)	179
M27411 	ORFS FEMALE - SAE J516 / ISO 12151-1 SHORT TYPE (CRIMPED BACK-NUT) ORFS 内螺纹 - SAE J516 / ISO 12151-1 短型 (带扣压-支撑螺母) ORFS VERPRESSTE MUTTER - SAE J516 / ISO 12151-1 KURZE AUSFÜHRUNG (CRIMPED BACK-NUT) FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE CORTA (DADO PRESSATO)	180
M22491 	90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT) 90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母) DK 90° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, PRESSMUTTER) FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 (DADO PRESSATO)	181
M22493 	90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT) 90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带滑套螺母) DK 90° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER) FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 (DADO PASSANTE)	181
M24493 	90° ORFS FEMALE LONG DROP ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT) 90° ORFS 内螺纹加长弯头 - SAE J516 / ISO 12151-1 (带滑套螺母) DK 90° BOGEN ORFS LANGE SCHENKEL (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER) FEMMINA ORFS A 90° CURVA LUNGA - SAE J516 / ISO 12151-1 (DADO PASSANTE)	182
M22441 	45° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT) 45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母) DK 45° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, PRESSMUTTER) FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 (DADO PRESSATO)	183
M22443 	45° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT) 45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带滑套螺母) DK 45° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER) FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 (DADO PASSANTE)	183

REFERENCE	DESCRIPTION	PAGE
SAE		
M13010	SAE MALE O-RING BOSS TYPE - SAE J516 / ISO 11926 SAE 外螺纹 O 形圈轮毂型 - SAE J516 / ISO 11926 AGJO SAE O-RING (UNF-GEWINDE NACH SAE J516 / ISO 11926) MASCHIO SAE O-RING - SAE J516 / ISO 11926	184
M14310	SAE SWIVEL MALE O-RING BOSS TYPE - SAE J516 / ISO 11926 SAE 旋转外螺纹 O 形圈轮毂型 - SAE J516 / ISO 11926 AGJO SAE O-RING DREHBAR (UNF-GEWINDE NACH SAE J516 / ISO 11926) MASCHIO SAE O-RING GIREVOLE - SAE J516 / ISO 11926	185
M14390	90° SAE SWIVEL MALE O-RING BOSS TYPE - SAE J516 / ISO 11926 90° SAE 旋转外螺纹 O 形圈轮毂型 - SAE J516 / ISO 11926 AGJO 90° KOMPAKT BOGEN DREHBAR MIT O-RING (UNF-GEWINDE NACH SAE J516 / ISO 11926) MASCHIO SAE O-RING GIREVOLE 90° - SAE J516 / ISO 11926	186
M22612	SAE FEMALE 45° CONE SEAT - SAE J516/J512 (THRUST-WIRE NUT) SAE 内螺纹 45° 锥形底座 - SAE J516/J512 (带止推金属丝螺母) DKJ DICHTKOPF GERADE 45° KONUS (UNF-GEWINDE NACH J516/J512, GESTIFTETE MUTTER) FEMMINA SAE CONO 45° - SAE J516/J512 (DADO SPINATO)	186
M22692	90° SAE FEMALE SWEPT ELBOW 45° CONE SEAT - SAE J516/J512 (THRUST-WIRE NUT) 90° SAE 内螺纹肘弯头 45° 锥形底座 - SAE J516/J512 (带止推金属丝螺母) DKJ 90° BOGEN 45° KONUS (UNF-GEWINDE NACH SAE J516/J512, GESTIFTETE MUTTER) FEMMINA SAE 90° CONO 45° - SAE J516/J512 (DADO SPINATO)	186
NPTF-NPSM		
M12810	NPTF MALE 60° CONE SEAT - SAE J516/J514 NPTF 外螺纹 60° 锥形底座 - SAE J516/J514 AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514 MASCHIO NPTF CONO 60° - SAE J516 / J514	187
M14110R	NPTF SWIVEL MALE 60° CONE SEAT - SAE J516/J514 NPTF 旋转外螺纹 60° 锥形底座 - SAE J516/J514 AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514 MASCHIO NPTF CONO 60° GIREVOLE - SAE J516/J514	188
M22812	NPSM FEMALE 60° CONE - SAE J516/J514 (THRUST-WIRE NUT) NPSM 内螺纹 60° 锥形 - SAE J516/J514 (带止推金属丝螺母) DK NPSM 60° KONUS - SAE J516/J514 (NPTF-GEWINDE, GESTIFTETE MUTTER) FEMMINA NPSM CONO 60° - SAE J516/J514 (DADO SPINATO)	188
SAE FLANGE CODE 61/CODE 62		
M23311	ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	189
M23321	22,5° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 22,5° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 22,5° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 22,5° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	190

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
M23331 	30° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 30° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 30° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 30° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	191
M23341 	45° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 45° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	192
M23361 	60° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 60° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 60° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 60° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	193
M23371 	67,5° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 67,5° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 67,5° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 67,5° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	194
M23391 	90° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 90° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	195
M23391 LONG DROP 	90° LONG DROP ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 90° 加长ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 90° LONG DROP ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 90° CURVA LUNGA ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	196
M23301P 	110° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 110° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 110° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 110° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	196
M23301S 	125° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 125° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 125° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 125° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	197
M23301T 	135° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 135° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 135° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 135° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	197
M23611 	ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 ISO/SAE CODE 62 FLANSCH - SAE J516/ISO 12151-3 FLANGIA ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	198
M23691 	90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	199
M23641 	45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	200

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

DIN STANDARD CONNECTIONS

DIN STANDPIPE

M22010	METRIC STANDPIPE LIGHT DUTY - DIN 2353 / ISO 8434-1 公制立管轻型系列 - DIN 2353 / ISO 8434-1 BEL - DIN 2353 / ISO 8434-1 ESTREMITÀ TUBOLARE SERIE LEGGERA - DIN 2353 / ISO 8434-1	201
		
M22110	METRIC STANDPIPE HEAVY DUTY - DIN 2353 / ISO 8434-1 公制立管重型系列 - DIN 2353 / ISO 8434-1 BES - DIN 2353 / ISO 8434-1 ESTREMITÀ TUBOLARE SERIE PESANTE - DIN 2353 / ISO 8434-1	202
		
M22090	90° METRIC STANDPIPE LIGHT DUTY - DIN 2353 / ISO 8434-1 90° 公制立管轻型系列 - DIN 2353 / ISO 8434-1 BEL 90° BOGEN - DIN 2353 / ISO 8434-1 ESTREMITÀ TUBOLARE 90° SERIE LEGGERA - DIN 2353 / ISO 8434-1	203
		
M22190	90° METRIC STANDPIPE HEAVY DUTY - DIN 2353 / ISO 8434-1 90° 公制立管重型系列 - DIN 2353 / ISO 8434-1 BES 90° BOGEN - DIN 2353 / ISO 8434-1 ESTREMITÀ TUBOLARE 90° SERIE PESANTE - DIN 2353 / ISO 8434-1	203
		
M22040	45° METRIC STANDPIPE LIGHT DUTY - DIN 2353 / ISO 8434-1 45° 公制立管轻型系列 - DIN 2353 / ISO 8434-1 BEL 45° BOGEN - DIN 2353 / ISO 8434-1 ESTREMITÀ TUBOLARE 45° SERIE LEGGERA - DIN 2353 / ISO 8434-1	204
		
M22140	45° METRIC STANDPIPE HEAVY DUTY - DIN 2353 / ISO 8434-1 45° 公制立管重型系列 - DIN 2353 / ISO 8434-1 BES 45° BOGEN - DIN 2353 / ISO 8434-1 ESTREMITÀ TUBOLARE 45° SERIE PESANTE - DIN 2353 / ISO 8434-1	204
		


DIN METRIC 60° CONE

M21013	METRIC FEMALE 60° CONE - DIN 20078/3863 公制60°锥内螺纹 - DIN 20078/3863 DKM 60° KONUS - DIN 20078/3863 FEMMINA METRICA CONO 60° - DIN 20078/3863	205
		
M21093	90° METRIC FEMALE SWEPT ELBOW 60° CONE - DIN 20078/3863 90°公制60°锥内螺纹巨肘弯头 - DIN 20078/3863 DKM 90° BOGEN 60° KONUS - DIN 20078/3863 FEMMINA METRICA 90° CONO 60° - DIN 20078/3863	205
		

DIN METRIC MULTISEAL

M21312	METRIC FEMALE MULTISEAL - DIN 20078/3868 (THRUST-WIRE NUT) 公制内螺纹组合密封 - DIN 20078/3868 (带止推金属螺母) DKL UNIVERSALKONUS - DIN 20078/3868 (GESTIFTETE MUTTER) FEMMINA METRICA CONO UNIVERSALE - DIN 20078/3868 (DADO SPINATO)	206
		
M21313	METRIC FEMALE MULTISEAL - DIN 20078/3868 (SLIP-ON NUT) 公制内螺纹组合密封 - DIN 20078/3868 (带滑套螺母) DKL UNIVERSALKONUS - DIN 20078/3868 (HINTERLEGTE MUTTER) FEMMINA METRICA CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)	206
		

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
	M21392 90° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (THRUST-WIRE NUT) 90° 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带止推金属丝螺母) DKL UNIVERSALKONUS 90° BOGEN - DIN 20078/3868 (GESTIFTETE MUTTER) FEMMINA METRICA 90° CONO UNIVERSALE - DIN 20078/3868 (DADO SPINATO)	207
	M21393 90° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (SLIP-ON NUT) 90° 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带滑套螺母) DKL UNIVERSALKONUS 90° BOGEN - DIN 20078/3868 (HINTERLEGTE MUTTER) FEMMINA METRICA 90° CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)	207
	M21342 45° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (THRUST-WIRE NUT) HEMBA METRICA CODO DE 45° ASIEN TO UNIVERSAL DIN 20078/3868 (TUERCA CON SEGURO) DKL UNIVERSALKONUS 45° BOGEN - DIN 20078/3868 (GESTIFTETE MUTTER) FEMMINA METRICA 45° CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)	208
	M21343 45° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (SLIP-ON NUT) 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带滑套螺母) DKL UNIVERSALKONUS 45° BOGEN - DIN 20078/3868 (HINTERLEGTE MUTTER) FEMMINA METRICA 45° CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)	208
DIN METRIC 24° CONE LIGHT TYPE		
	M11110 METRIC MALE 24° CONE SEAT LIGHT DUTY - DIN 20066 / ISO 12151-2 公制外螺纹 24° 锥形底座轻型系列 DIN 20066 / ISO 12151-2 CEL - DIN 20066 / ISO 12151-2 MASCHIO METRICO 24° SERIE LEGGERA - DIN 20066 / ISO 12151-2	209
	M21512 METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 公制内螺纹 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOL - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)	210
	M21513 METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 公制内螺纹 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带滑套螺母) DKOL - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)	210
	M21592 90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 90° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOL 90° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA 90° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)	211
	M21593 90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 90° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带滑套螺母) DKOL 90° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA 90° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)	211
	M21542 45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 45° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOL 45° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA 45° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)	212
	M21543 45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 45° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带滑套螺母) DKOL 45° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA 45° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)	212

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

DIN METRIC 24° CONE HEAVY TYPE

M11210	METRIC MALE 24° CONE SEAT HEAVY DUTY - DIN 20066 / ISO 12151-2 公制外螺纹 24° - 锥形底座重型系列 DIN 20066 / ISO 12151-2 CES - DIN 20066 / ISO 12151-2 MASCHIO METRICO 24° - SERIE PESANTE DIN 20066 / ISO 12151-2	213
M21612	METRIC O-RING FEMALE 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 公制内螺纹 24° 锥带O型圈重型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOS - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)	214
M21613	METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 公制内螺纹 24° 锥带O型圈重型系列 DIN 20066 / ISO 12151-2 (带滑套螺母) DKOS - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)	214
M21692	90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)	215
M21693	90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 DIN 20066 / ISO 12151-2 (带滑套螺母) DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)	215
M21642	45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)	216
M21643	45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 DIN 20066 / ISO 12151-2 (带滑套螺母) DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)	216

NF STANDARD CONNECTIONS

FRENCH MILLIMETRIC TYPE

M11710	FRENCH METRIC MALE 24° CONE SEAT MILLIMETRIC TYPE 法国外螺纹 24° 锥形底座毫米公制型 AGFM 24° INNENKONUS (FR. REIHE MILL.) MASCHIO METRICO 24° SERIE MILLIMETRICA FRANCESE	217
M21713	FRENCH METRIC FEMALE MILLIMETRIC TYPE (SLIP-ON NUT) 法国内螺纹锥毫米公制型 (滑套螺母) DKFM (FR. REIHE MILL., HINTERLEGTE MUTTER) FEMMINA METRICA SERIE MILLIMETRICA FRANCESE (DADO PASSANTE)	217

FRENCH GAZ TYPE

M11810	FRENCH METRIC MALE 24° CONE SEAT GAZ TYPE 法国外螺纹 24° 锥形底座 GAZ 型 AGF 24° INNENKONUS (FR. REIHE GAS) MASCHIO METRICO 24° SERIE GAZ FRANCESE	217
---------------	--	------------

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
M21813 	FRENCH METRIC FEMALE GAZ TYPE (SLIP-ON NUT) 法国内螺纹公制 GAZ型 (滑套螺母) DKF (FR. REIHE GAS, HINTERLEGTE MUTTER) FEMMINA METRICA SERIE GAZ FRANCESE (DADO PASSANTE)	218
M21893 	90° FRENCH METRIC FEMALE GAZ TYPE (SLIP-ON NUT) 90° 法国公制内螺纹 GAZ型 (滑套螺母) DKF 90° BOGEN (FR. REIHE MILL., HINTERLEGTE MUTTER) FEMMINA METRICA 90° SERIE GAZ FRANCESE (DADO PASSANTE)	218

JIS STANDARD CONNECTIONS

M24011 	JIS METRIC FEMALE 60° CONE SEAT (KOMATSU) JIS B 8363 (CRIMPED-BACK NUT) JIS 公制内螺纹 60° 锥形底座 (小松标准) JIS B 8363 (扣压-支撑螺母) DK KOMATSU MIT 60° KONUS (NACH JIS B 8363, PRESSMUTTER) FEMMINA METRICA GIAPPONESE CONO 60° TIPO KOMATSU JIS B 8363 (DADO PRESSATO)	219
M24012 	JIS METRIC FEMALE 60° CONE SEAT (KOMATSU) JIS B 8363 (THRUST-WIRE NUT) JIS 公制内螺纹 60° 锥形底座 (小松标准) JIS B 8363 (带止推金属丝螺母) DK KOMATSU MIT 60° KONUS (NACH JIS B 8363, GESTIFTETE MUTTER) FEMMINA METRICA GIAPPONESE CONO 60° TIPO KOMATSU JIS B 8363 (DADO SPINATO)	219
M23811 	JIS BSP FEMALE 60° CONE SEAT (TOYOTA) - JIS B 8363 (CRIMPED-BACK NUT) HEMBRA JIS BSP ASIEN TO A 60° (TOYOTA) - JIS B 8363 (TUERCA PRENSADA) DK TOYOTA MIT 60° KONUS MIT KONTERSECHSKANT (NACH JIS B 8363, PRESSMUTTER) FEMMINA GAS GIAPPONESE CONO 60° TIPO TOYOTA JIS B 8363 (DADO PRESSATO)	220
M20711 	JIS BSP FEMALE 60° CONE (NISSAN) - JIS B 8363 (CRIMPED-BACK NUT) JIS BSP 英制内螺纹 60° 锥 (尼桑标准) - JIS B 8363 (带扣压-支撑螺母) DK NISSAN MIT 60° KONUS MIT KONTERSECHSKANT (NACH JIS B 8363, PRESSMUTTER) FEMMINA GIAPPONESE CONO 60° TIPO NISSAN JIS B 8363 (DADO PRESSATO)	220
M20712 	JIS BSP FEMALE 60° CONE (NISSAN) - JIS B 8363 (THRUST-WIRE NUT) JIS BSP 英制内螺纹 60° 锥 (尼桑标准) - JIS B 8363 (带止推金属丝螺母) DK NISSAN MIT 60° KONUS MIT KONTERSECHSKANT (NACH JIS B 8363, GESTIFTETE MUTTER) FEMMINA GIAPPONESE CONO 60° TIPO NISSAN JIS B 8363 (DADO SPINATO)	220

ORIGINAL EQUIPMENT CONNECTIONS

KOMATSU, POCLAIN, SUPERCAT FLANGES

M24111 	STRAIGHT KOMATSU FLANGE 直式小松法兰 FLANSCH GERADE KOMATSU FLANGIA DITTA SERIE KOMATSU	221
M24191 	90° KOMATSU FLANGE 90° 度小松法兰 FLANSCH 90° BOGEN KOMATSU FLANGIA 90° SERIE KOMATSU	221
M24141 	45° KOMATSU FLANGE 45° 度小松法兰 FLANSCH 45° BOGEN KOMATSU FLANGIA 45° SERIE KOMATSU	221

REFERENCE	DESCRIPTION	PAGE
M23911	STRAIGHT SUPERCAT FLANGE 山猫直式法兰 FLANSCH GERADE SUPERCAT FLANGIA DITTA SERIE SUPERCAT	222
	M23991	
90° SUPERCAT FLANGE 90° 度山猫法兰 FLANSCH 90° BOGEN SUPERCAT FLANGIA 90° SERIE SUPERCAT	222	
	M23941	
45° SUPERCAT FLANGE 45° 度山猫法兰 FLANSCH 45° BOGEN SUPERCAT FLANGIA 45° SERIE SUPERCAT	222	

BANJO CONNECTIONS

O20310	BSP BANJO BSP 绞接式接头 RINGNIPPEL, ZÖLLIG (BSP GEWINDE) OCCHIELLO GAS	223
		
O20910	METRIC BANJO - DIN 7642 公制绞接式 - DIN 7642 RINGNIPPEL, METRISCH - DIN 7642 OCCHIELLO METRICO - DIN 7642	223
		

ACCESSORIES

M...IP	BRAZING TAIL 铜焊接头插芯 EINLÖTNIPPEL INSERTO A SILDARE	224
		
M10050	DOUBLE CONNECTOR 双插芯接头 SCHLAUCHVERBINDER - DOPPELNIPPEL DOPPIO INSERTO	225
		
O80210	BSP BOLT BSP 螺栓 HOHLSCHRAUBE ZÖLLIG VITE GAS FORATA	226
		
O80810	METRIC BOLT - DIN 7643 公制螺栓 - DIN 7643 HOHLSCHRAUBE - METRISCH - DIN 7643 VITE METRICA FORATA - DIN 7643	226
		

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

MF2000® INTERLOCK PLUS TYPE FERRULE

M01500 	DOUBLE SKIVE FERRULE FOR HEAVY DUTY SPIRAL HOSES (4 PLY) 重型缠绕软管 (四层) 双面剥胶套筒 PRESSFASSUNG INNEN- UND AUSSENSCHÄLUNG FÜR HÖCHSTDRUCKSCHLÄUCHE (4 PLY) GHIERA PER TUBI SPIRALATI CON DOPPIA PELATURA (4 SPIRALI)	227
M01600 	DOUBLE SKIVE FERRULE FOR HEAVY DUTY SPIRAL HOSES (6 PLY) 重型缠绕软管 (六层) 双面剥胶套筒 PRESSFASSUNG INNEN- UND AUSSENSCHÄLUNG FÜR HÖCHSTDRUCKSCHLÄUCHE (6 PLY) GHIERA PER TUBI SPIRALATI CON DOPPIA PELATURA (6 SPIRALI)	227
M01800 	DOUBLE SKIVE FERRULE FOR EXTRA DUTY SPIRAL HOSES (6 PLY) 超重型缠绕软管 (六层) 双面剥胶套筒 PRESSFASSUNG FÜR INNEN- UND AUSSENSCHÄLUNG FÜR SPEZIAL-SPIRALSCHLÄUCHE (6 PLY) GHIERA A PELATURA INTERNA/ESTERNA PER TUBI SPIRALATI (6 SPIRALI) PER APPLICAZIONI ESTREMAMENTE SEVERE	227

MF2000® INTERLOCK PLUS TYPE INSERT BS STANDARD CONNECTIONS

M30510 	BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6 BSP 平行外螺纹 60° 锥形底座 - BS5200 / ISO 8434-6 AGR 60° INNENKONUS - BS5200/ISO 8464-6 MASCHIO GAS CILINDRICO CONO 60° - BS5200 / ISO 8434-6	228
M40812 	BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT) BSP O型圈内螺纹 60° 锥 - BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER) FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)	228
M40892 	90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 90° O型圈BSP内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 90° BOGEN 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER) FEMMINA GAS 90° CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)	229
M40842 	45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT) 45° O型圈BSP内螺纹巨肘弯头 (60° 锥) BS5200 / ISO 12151-6 (带止推金属丝螺母) DKOR 45° BOGEN 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER) FEMMINA GAS 45° CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)	229

SAE STANDARD CONNECTIONS

NPTF/JIC


M32810 	NPTF MALE 60° CONE SEAT - SAE J516/J514 NPTF 外螺纹 60° 锥形底座 - SAE J516/J514 AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514 MASCHIO NPTF CONO 60° - SAE J516/J514	230
M42512 	JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带止推金属丝螺母) JDKJ 37° KONUS - SAE J516 / ISO 12151-5 (KONTERSECHSKANT UND STIFTMUTTER) FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)	230
M42592 	90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) 90° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母) JDKJ 90° BOGEN, 37° KONUS - SAE J516 / ISO 12151-5 (STIFTMUTTER) FEMMINA JIC 90° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)	231

REFERENCE	DESCRIPTION	PAGE
M42542	45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT) 45° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母) DKJ 45° BOGEN 37° KONUS - SAE J516 / ISO 12151-5 (STIFTMUTTER) FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)	231
ORFS		
M42411	ORFS FEMALE - SAE J516 / ISO 12151-1 PULLBACK TYPE (CRIMPED BACK-NUT) ORFS 内螺纹 - SAE J516 / ISO 12151-1 回拉式 (带扣压-支撑螺母) ORFS IG - SAE J516 / ISO 12151-1 RÜCKZUGSAUSFÜHRUNG (VERPRESSTE MUTTER) FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE RETRAIBILE (DADO PRESSATO)	232
M42412	ORFS FEMALE - SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE NUT) ORFS 内螺纹 - SAE J516 / ISO 12151-1 重型 (带止推金属丝螺母) ORFS MUTTER GESTIFTET - SAE J516 / ISO 12151-1 SCHWERE REIHE (THRUST-WIRE NUT) FEMMINA ORFS - SAE J516 / ISO 12151-1 SERIE PESANTE (DADO SPINATO)	232
M42491	90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT) 90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母) 90° ORFS BOGEN (VERPRESSTE MUTTER) - SAE J516 / ISO 12151-1 FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 (DADO PRESSATO)	233
M42492	90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE-NUT) 90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 重型 (带止推金属丝螺母) 90° ORFS BOGEN - SCHWERE REIHE SAE J516 / ISO 12151-1 (GESHTETE MUTTER) FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 SERIE PESANTE (DADO SPINATO)	233
M42441	45° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT) 45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母) DK ORFS 45° - SAE J516 / ISO 12151-1 (PRESSMUTTER) FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 (DADO PRESSATO)	234
M42442	45° ORFS FEMALE SWEPT ELBOW SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE-NUT) 45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 重型 (带止推金属丝螺母) 45° ORFS BOGEN (GESHTETE MUTTER) - SAE J516 / ISO 12151-1 FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 SERIE PESANTE (DADO SPINATO)	234


SAE FLANGE CODE 61/CODE 62

M43310	ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 SAE FLANSCH GERADE 3000 PSI (NACH SAE J516/J518) FLANGIA ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	235
M43390	90° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 SAE FLANSCH 90° BOGEN - SAE J516 / ISO 12151-3 FLANGIA 90° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	235
M43340	45° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3 SAE FLANSCH 45° BOGEN - SAE J516 / ISO 12151-3 FLANGIA 45° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3	236

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
M43610 	ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	236
M43690 	90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	237
M43640 	45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	237
M43630 	30° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 30° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 30° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 30° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	238
M43660 	60° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 60° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 60° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 60° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	238

ORIGINAL EQUIPEMENT CONNECTIONS

M43710 	FLANGE PLUS (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 法兰增强式 (SAE J518 CODE 62 - ISO 6162-2 端口兼容) GERADER FLANSCH SCHWERE REIHE (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS) FLANGIA PLUS (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	239
M43740 	45° FLANGE PLUS (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 45° 法兰增强式 (SAE J518 CODE 62 - ISO 6162-2 端口兼容) 45°-BOGEN FLANSCH SCHWERE REIHE (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS) FLANGIA PLUS 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	239
M43790 	90° FLANGE PLUS (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 90° 法兰增强式 (SAE J518 CODE 62 - ISO 6162-2 端口兼容) 90°-BOGEN FLANSCH SCHWERE REIHE (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS) FLANGIA PLUS 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	239
M43910 	STRAIGHT SUPERCAT SERIES FLANGE 山猫系列直式法兰 FLANSCH GERADE SUPERCAT FLANGIA DRITTA SERIE SUPERCAT	240
M43920 	22,5° SUPERCAT SERIES FLANGE 22,5° 山猫系列法兰 22,5° FLANSCH SERIE SUPERCAT FLANGIA 22,5° SERIE SUPERCAT	240
M43930 	30° SUPERCAT SERIES FLANGE 30° 山猫系列法兰 30° FLANSCH SERIE SUPERCAT FLANGIA 30° SERIE SUPERCAT	241

REFERENCE	DESCRIPTION	PAGE
M43940	45° SUPERCAT SERIES FLANGE 45° 山猫系列法兰 FLANSCH 45° BOGEN SUPERCAT FLANGIA 45° SERIE SUPERCAT	241
M43960	60° SUPERCAT SERIES FLANGE 60° 山猫系列法兰 60° FLANSCH SERIE SUPERCAT FLANGIA 60° SERIE SUPERCAT	242
M43970	67,5° SUPERCAT SERIES FLANGE 67,5° 山猫系列法兰 67,5° FLANSCH SERIE SUPERCAT FLANGIA 67,5° SERIE SUPERCAT	242
M43990	90° SUPERCAT SERIES FLANGE 90° 加长山猫系列法兰 FLANSCH 90° BOGEN SUPERCAT FLANGIA 90° SERIE SUPERCAT	243
M43990 LONG DROP	90° LONG DROP SUPERCAT SERIES FLANGE 90° 加长山猫系列法兰 90° LONG DROP FLANSCH SERIE SUPERCAT FLANGIA 90° SERIE SUPERCAT CURVA LUNGA	243

XTRAFLANGE

M48510	XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容) XTRAFLANSCH GERADE (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS) XTRAFLANGIA (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	244
M48540	45° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 45° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容) 45°-BOGEN XTRAFLANSCH (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS) XTRAFLANGIA 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	244
M48590	90° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 90° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容) XTRAFLANSCH 90° BOGEN (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS) XTRAFLANGIA 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	244

DIN STANDARD CONNECTIONS

DIN METRIC 24° CONE HEAVY TYPE

M31210	METRIC MALE 24° CONE SEAT HEAVY DUTY - DIN 20066 / ISO 12151-2 公制外螺纹 24° 锥形底座重型系列 - DIN 20066 / ISO 12151-2 CES - DIN 20066 / ISO 12151-2 MASCHIO METRICO 24° - SERIE PESANTE DIN 20066 / ISO 12151-2	245
M41612	METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 公制内螺纹 24° 锥形O型圈重型系列 - DIN 20066 / ISO 12151-2 (带止推金属螺母) DKOS - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)	245

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
	30° SUPERCAT SERIES FLANGE 30° 山猫系列法兰 30° FLANSCH SERIE SUPERCAT FLANGIA 30° SERIE SUPERCAT	
M41613 	METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 公制内螺纹 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带滑套螺母) DKOS - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)	245
M41692 	90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)	246
M41693 	90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带滑套螺母) DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)	246
M41642 	45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT) 45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带止推金属丝螺母) DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER) FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)	247
M41643 	45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带滑套螺母) DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)	247
M41293 	90° METRIC O-RING FEMALE MEDIUM/LONG DROP ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 90° 公制内螺纹中型/加长弯头 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带滑套螺母) 90° O-RING METRISCH M RÜCKBOGEN 24° KONUS H.T. DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA O-RING SERIE PESANTE CONO 24° CURVA 90° MEDIO/LUNGA DIN 20066 / ISO 12151-2 (DADO PASSANTE)	248
M41243 	45° METRIC O-RING FEMALE MEDIUM/LONG DROP ELBOW 24° CONE HEAVY DUTY DIN 20066 / ISO 12151-2 (SLIP-ON NUT) 45° 公制内螺纹中型/加长弯头 24° 锥带O型圈重型系列 - DIN 20066 / ISO 12151-2 (带滑套螺母) 45° O-RING METRISCH M RÜCKBOGEN 24° KONUS H.T. DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER) FEMMINA METRICA O-RING SERIE PESANTE CONO 24° CURVA 45° MEDIO/LUNGA DIN 20066 / ISO 12151-2 (DADO PASSANTE)	248
M30050 	DOUBLE CONNECTOR 双插芯接头 DOPPELVERBINDER DOPPIO INSERTO	249
M49510WL 	WELDING TAIL 焊接插芯 SCHWEISSENDE INSERTO A SALDARE	249
J029 	OPTIONAL INTERLOCK PLUS O-RING 可选内锁增强式O型圈 OPTIONAL INTERLOCK PLUS O-RING O-RING INTERLOCK PLUS OPZIONALE	249

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

MF2000® XTRALOCK TYPE FERRULE

M01750 	DOUBLE SKIVE FERRULE FOR EXTRA DUTY SPIRAL HOSES (4 PLY) 超重型缠绕软管 (四层) 双面剥胶套筒 PRESSFASSUNG FÜR INNEN- UND AUSSENSCHÄLUNG FÜR SPEZIAL-SPIRALSCHLÄUCHE (4-LAGIG) GHIERA A PELATURA INTERNA/ESTERNA PER TUBI SPIRALATI (4 SPIRALI) PER APPLICAZIONI ESTREMAMENTE SEVERE	250
M01800 	DOUBLE SKIVE FERRULE FOR EXTRA DUTY SPIRAL HOSES (6 PLY) 超重型缠绕软管 (六层) 双面剥胶套筒 PRESSFASSUNG FÜR INNEN- UND AUSSENSCHÄLUNG FÜR SPEZIAL-SPIRALSCHLÄUCHE (6-LAGIG) GHIERA A PELATURA INTERNA/ESTERNA PER TUBI SPIRALATI (6 SPIRALI) PER APPLICAZIONI ESTREMAMENTE SEVERE	250

MF2000® XTRALOCK TYPE INSERTS

M52810/M57810 	NPTF MALE 60° CONE SEAT - SAE J516/J514 NPTF 外螺纹 60° 锥形底座 - SAE J516/J514 AG NPTF KONUS 60° - SAE J516/J514 MASCHIO NPTF CONO 60° - SAE J516/J514	251
M68610 	ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA DITTA SAE CODE 62 - SAE J516 / ISO 12151-3	251
M68690 	90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 90° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	252
M68640 	45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3 45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3 FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3	252
M53410 	API MALE WITH HEXAGONAL BODY (API 5B THREAD) 六角形 API 外螺纹接头 (API 5B 螺纹) VERBINDER API SECHSKANT (API 5B GEWINDE) MASCHIO API CON CORPO ESAGONALE (FILETTATURA API 5B)	253
M53410...H00 	API MALE WITH CYLINDRICAL BODY (API 5B THREAD) 圆柱形 API 外螺纹接头 (API 5B 螺纹) VERBINDER API ZYLINDRISCH API 5B (API 5B GEWINDE) MASCHIO API CON CORPO CILINDRICO (FILETTATURA API 5B)	253
M53510 	NPT MALE NPT 外螺纹 NPT-SCHRAUBVERBINDUNG NPT MASCHIO	253
M68510 	XTRAFLLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) XTRAFLLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容) XTRAFLLANSCH GERADE (SAE J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS) XTRAFLLANGIA (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	254
M68590 	90° XTRAFLLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 90° XTRAFLLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容) XTRAFLLANSCH 90° BOGEN (J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS) XTRAFLLANGIA 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	254

VISUAL INDEX

REFERENCE	DESCRIPTION	PAGE
-----------	-------------	------

M68540	 45° XTRAFANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE) 45° XTRAFANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容) XTRAFANSCH 45° BOGEN (SAE J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS) XTRAFANGIA 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)	254
---------------	---	------------

ACCESSORIES

O83308	 ISO/SAE CODE 61 SPLIT FLANGE CLAMPS - SAE J518 / ISO 6162-1 ISO/SAE CODE 61 分片法兰管夹 - SAE J518 / ISO 6162-1 ISO/SAE CODE 61 GETEILTE FLANSCHHÄLFTEN - SAE J518 / ISO 6162-1 SEMIFLANGIA ISO/SAE CODE 61- SAE J518 / ISO 6162-1	255
O83609	 ISO/SAE CODE 62 SPLIT FLANGE CLAMPS - SAE J518 / ISO 6162-2 ISO/SAE CODE 62 分片法兰管夹 - SAE J518 / ISO 6162-2 ISO/SAE CODE 62 GETEILTE FLANSCHHÄLFTEN - SAE J518 / ISO 6162-2 SEMIFLANGIA ISO/SAE CODE 62 - SAE J518 / ISO 6162-2	255
O83607	 ONE-PIECE FLANGE CLAMP ISO 6162-2 / SAE J518 CODE 62 整片法兰管夹 - ISO 6162-2 / SAE J518 VOLLFLANSCH - ISO 6162-2 / SAE J518 CODE 62 SEMIFLANGIA INTERA - ISO 6162-2 / SAE J518 CODICE 62	256
O88507	 ONE-PIECE XTRAFANGE CLAMP ISO 6162-2 / SAE J518 CODE 62 PORT COMPATIBLE 整片 XTRAFANGE 管夹 ISO 6162-2 / SAE J518 CODE 62 端口兼容 VOLLFLANSCH FÜR XTRAFANSCH ISO 6162-2 / SAE J518 CODE 62 KOMPATIBLER ANSCHLUSS SEMIFLANGIA INTERA XTRAFANGIA ISO 6162-2 / SAE J518 COMPATIBILE CON PORTA CODE 62	256
O820..	 ANTI-KINK SLEEVE 抗扭曲套筒 ABKNICKSCHUTZ-FÜHRUNG CHIARA ANTI-KINK	257

MF2000® PUSH-LOCK TYPE INSERT

BS STANDARD CONNECTIONS

L10510	 BSP MALE PARALLEL 60° CONE SEAT - BS5200/ISO 8434-6 BSP 平行外螺纹 (60° 锥形底座) - BS5200/ISO 8434-6 AGR 60° INNENKONUS (BSP-GEWINDE) - BS5200/ISO 8434-6 MASCHIO GAS CILINDRICO - BS5200/ISO 8434-6	260
L20513	 BSP FEMALE 60° CONE - BS5200/ISO 12151-6 (SLIP-ON NUT) BSP 内螺纹 (60° 锥) - BS5200/ISO 12151-6 (带滑套螺母) DKR 90° KONUS (BSP-GEWINDE) - HINTERLEGTE MUTTER BS5200/ISO 12151-6 FEMMINA GAS CONO 90° - BS5200/ISO 12151-6 (DADO PASSANTE)	260
L20593	 90° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200/ISO 12151-6 (SLIP-ON NUT) 90° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200/ISO 12151-6 (带滑套螺母) DKR 90° BOGEN 60° KONUS (BSP-GEWINDE) - BS5200/ISO 12151-6 (HINTERLEGTE MUTTER) FEMMINA GAS 90° CONO 60° - BS5200/ISO 12151-6 (DADO PASSANTE)	261
L20543	 45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200/ISO 12151-6 (SLIP-ON NUT) 45° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200/ISO 12151-6 (带滑套螺母) DKR 45° BOGEN 60° KONUS (BSP-GEWINDE) - BS5200/ISO 12151-6 (HINTERLEGTE MUTTER) FEMMINA GAS 45° CONO 60° - BS5200/ISO 12151-6 (DADO PASSANTE)	261

REFERENCE	PAGE
J029	249
L10510	260
L20513	260
L20543	261
L20593	261
M00110/M00120	157
M00310	159
M00820/M00830	159
M00910/M00920	157
M01500	227
M01600	227
M01750	250
M01800	227/250
M03400	158
M10050	225
M10510	161
M10610	168
M10710	160
M11110	209
M11210	213
M11710	217
M11810	217
M12410	178
M12510	170
M12810	187
M13010	184
M14110R	188
M14310	185
M14390	186
M20512	162
M20513	162
M20542	164
M20543	164
M20592	163

REFERENCE	PAGE
M20593	163
M20612	169
M20613	169
M20711	220
M20712	220
M20812	165
M20813	165
M20842	167
M20843	167
M20882F	168
M20892	166
M20893	166
M21013	205
M21093	205
M21312	206
M21313	206
M21342	208
M21343	208
M21392	207
M21393	207
M21512	210
M21513	210
M21542	212
M21543	212
M21592	211
M21593	211
M21612	214
M21613	214
M21642	216
M21643	216
M21692	215
M21693	215
M21713	217
M21813	218


REFERENCE	PAGE
M21893	218
M22010	201
M22040	204
M22090	203
M22110	202
M22140	204
M22190	203
M22411	179
M22441	183
M22443	183
M22491	181
M22493	181
M22512	171
M22513	171
M22542	177
M22543	177
M22582F	178
M22592	175
M22593	175
M22612	186
M22692	186
M22711	172
M22711K	172
M22712	174
M22712K	173
M22812	188
M23301P	196
M23301S	197
M23301T	197
M23311	189
M23321	190
M23331	191
M23341	192
M23361	193

INDEX

REFERENCE	PAGE
M23371	194
M23391	195
M23391 LONG DROP	196
M23611	198
M23641	200
M23691	199
M23811	220
M23911	222
M23941	222
M23991	222
M24011	219
M24012	219
M24111	221
M24141	221
M24191	221
M24493	182
M24792	176
M24793	176
M27411	180
M30050	249
M30510	228
M31210	245
M32810	230
M40812	228
M40842	229
M40892	229
M41243	248
M41293	248
M41612	245
M41613	245
M41642	247
M41643	247
M41692	246
M41693	246

REFERENCE	PAGE
M42411	232
M42412	232
M42441	234
M42442	234
M42491	233
M42492	233
M42512	230
M42542	231
M42592	231
M43310	235
M43340	236
M43390	235
M43610	236
M43630	238
M43640	237
M43660	238
M43690	237
M43710	239
M43740	239
M43790	239
M43910	240
M43920	240
M43930	241
M43940	241
M43960	242
M43970	242
M43990	243
M43990 LONG DROP	243
M48510	244
M48540	244
M48590	244
M49510WL	249
M52810/M57810	251
M53410	253

REFERENCE	PAGE
M53410...H00	253
M53510	253
M68510	254
M68540	254
M68590	254
M68610	251
M68640	252
M68690	252
M...IP	224
O820..	257
O20310	223
O20910	223
O80210	226
O80810	226
O83308	255
O83607	256
O83609	255
O88507	256



M00110/M00120


SKIVE FERRULE FOR WIRE BRAID HOSES

钢丝编织管剥胶套筒

SCHÄLFASSUNG FÜR STAHLGEFLECHTSCHLÄUCHE

GHIERA PER TUBI TRECCIATI CON PELATURA

PART. REF.	HOSE BORE				DIMENSIONS mm				
	DN	inch	Size		D	L			
M00120-03	5	3/16"	- 03		17,0	23,9			
M00120-04	6	1/4"	- 04		19,5	28,0			
M00120-05	8	5/16"	- 05		20,0	28,6			
M00120-06	10	3/8"	- 06		23,0	30,0			
M00120-08	12	1/2"	- 08		26,7	32,0			
M00120-10	16	5/8"	- 10		32,0	38,0			
M00120-12	19	3/4"	- 12		35,8	41,7			
M00120-16	25	1"	- 16		43,0	47,0			
M00110-20	31	1.1/4"	- 20		50,5	59,0			
M00110-24	38	1.1/2"	- 24		57,0	70,0			
M00110-32	51	1"	- 32		70,0	72,0			



M00910/M00920

SKIVE FERRULE FOR WIRE BRAID AND SPIRAL HOSES

钢丝编织/缠绕管剥胶套筒

SCHÄLFASSUNG FÜR STAHLGEFLECHT- UND SPIRALSCHLÄUCHE

GHIERA PER TUBI TRECCIATI E SPIRALATI CON PELATURA

PART. REF.	HOSE BORE				DIMENSIONS mm				
	DN	inch	Size		D	L			
M00910-03	5	3/16"	- 03		20,6	26,0			
M00910-04	6	1/4"	- 04		22,0	30,0			
M00910-05	8	5/16"	- 05		24,0	31,0			
M00910-06	10	3/8"	- 06		26,0	33,0			
M00910-08	12	1/2"	- 08		30,0	34,0			
M00910-10	16	5/8"	- 10		33,0	39,0			
M00920-12	19	3/4"	- 12		38,0	40,0			
M00920-16	25	1"	- 16		46,0	54,0			
M00920-20	31	1.1/4"	- 20		57,0	60,0			
M00910-24	38	1.1/2"	- 24		65,0	70,0			
M00910-32	51	2"	- 32		79,0	72,0			

FERRULE


M03400

NO-SKIVE FERRULE FOR WIRE BRAID HOSES

钢丝编织管不剥胶套筒

NICHT-SCHÄLFASSUNG FÜR STAHLGEFLECHTSCHLÄUCHE

GHIERA PER TUBI TRECCIATI SENZA PELATURA



PART. REF.	HOSE BORE			DIMENSIONS mm					
	DN	inch	Size		D	L			
M03400-03	5	3/16"	- 03		21,0	23,0			
M03400-04	6	1/4"	- 04		23,0	30,1			
M03400-05	8	5/16"	- 05		24,0	30,0			
M03400-06	10	3/8"	- 06		26,0	31,1			
M03400-08	12	1/2"	- 08		29,0	33,4			
M03400-10	16	5/8"	- 10		33,0	37,0			
M03400-12	19	3/4"	- 12		37,0	42,0			
M03400-16	25	1"	- 16		46,0	51,0			
M03400-20	31	1.1/4"	- 20		59,0	57,2			
M03400-24	38	1.1/2"	- 24		67,0	64,8			
M03400-32	51	2"	- 32		80,0	68,3			
M03400-38	60	2.3/8"	- 38		82,5	69,0			
M03400-40	63	2. 1/2"	- 40		88,2	68,8			
M03400-48	76	3"	- 48		103,0	75,0			

! Available no-skive ferrule for one braid hoses for DN 6 (M03100-04) and DN 10 (M03100-06).

可为单层钢丝编织管提供不剥胶套筒 DN 6 (M03100-04) 和 DN 10 (M03100-06).

Verfügbar hülsen ohne abschälen für 1-drahtgeflechschläuche für DN 6 (M03100-04) und DN 10 (M03100-06)

Disponibile ghiera per tubi a una treccia senza pelatura per DN 6 (M03100-04) e DN 10 (M03100-06).


M00310

NO-SKIVE FERRULE FOR TEXTILE BRAID HOSES


棉线编织管不剥胶套筒

NICHT-SCHÄLFASSUNG FÜR TEXTILGEFLECHTSCHLÄUCHE

GHIERA PER TUBI TESSILI SENZA PELATURA



PART. REF.	HOSE BORE			DIMENSIONS mm						
	DN	inch	Size		D	L				
M00310-03	5	3/16"	- 03		17,5	27,0				
M00310-04	6	1/4"	- 04		19,3	30,0				
M00310-05	8	5/16"	- 05		21,0	32,0				
M00310-06	10	3/8"	- 06		24,0	32,0				
M00310-08	12	1/2"	- 08		28,4	34,0				
M00310-10	16	5/8"	- 10		33,0	37,0				
M00310-12	19	3/4"	- 12		37,0	43,0				
M00310-16	25	1"	- 16		43,5	51,0				
M00310-20	31	1.1/4"	- 20		50,0	59,0				



M00820/M00830

NO-SKIVE FERRULE FOR COMPACT HOSES

紧凑型胶管不剥胶套筒

NICHT-SCHÄLFASSUNG FÜR KOMPAKT-SCHLÄUCHE

GHIERA PER TUBI COMPATTI SENZA PELATURA

PART. REF.	HOSE BORE			DIMENSIONS mm						
	DN	inch	Size		D	L				
M00820-03	5	3/16"	- 03		14,0	26,4				
M00830-04	6	1/4"	- 04		18,0	29,6				
M00830-05	8	5/16"	- 05		19,0	31,9				
M00820-06	10	3/8"	- 06		22,0	33,0				
M00820-08	12	1/2"	- 08		26,0	33,9				
M00820-10	16	5/8"	- 10		29,0	35,9				
M00820-12	19	3/4"	- 12		33,0	41,7				
M00820-16	25	1"	- 16		41,0	49,7				
M00820-20	31	1.1/4"	- 20		48,0	57,0				
M00820-24	38	1.1/2"	- 24		55,5	66,0				
M00820-32	51	2"	- 32		68,6	70,0				

new
new

BS STANDARD CONNECTIONS


M10710

BSP MALE TAPERED - ISO 7


BSP 外锥形外螺纹 - ISO 7

AGR KONISCH (BSPT GEWINDE NACH) - ISO 7

MASCHIO CONICO GAS - ISO 7



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₁
M10710-03-02	5	3/16"	- 03	1/8" - 28	4,5	20,6	8,0			12
M10710-03-04	5	3/16"	- 03	1/4" - 19	4,5	24,5	12,0			14
M10710-04-02	6	1/4"	- 04	1/8" - 28	4,5	21,0	8,0			12
M10710-04-04	6	1/4"	- 04	1/4" - 19	4,5	25,0	12,0			14
M10710-04-06	6	1/4"	- 04	3/8" - 19	7,0	26,0	12,0			19
M10710-04-08	6	1/4"	- 04	1/2" - 14	10,0	29,5	15,0			22
M10710-05-04	8	5/16"	- 05	1/4" - 19	5,5	25,0	12,0			14
M10710-05-06	8	5/16"	- 05	3/8" - 19	7,0	26,5	12,0			19
M10710-05-08	8	5/16"	- 05	1/2" - 14	10,0	30,0	15,0			22
M10710-06-06	10	3/8"	- 06	3/8" - 19	7,0	27,1	12,0			19
M10710-06-08	10	3/8"	- 06	1/2" - 14	10,0	30,6	15,0			22
M10710-08-04	12	1/2"	- 08	1/4" - 19	4,5	26,0	12,0			19
M10710-08-08	12	1/2"	- 08	1/2" - 14	10,0	31,1	15,0			22
M10710-10-08	16	5/8"	- 10	1/2" - 14	10,0	31,0	15,0			22
M10710-10-12	16	5/8"	- 10	3/4" - 14	17,0	37,0	17,0			27
M10710-12-12	19	3/4"	- 12	3/4" - 14	17,0	35,5	17,0			27
M10710-16-12	25	1"	- 16	3/4" - 14	17,0	38,0	17,0			32
M10710-16-16	25	1"	- 16	1" - 11	22,5	41,8	21,0			36
M10710-20-20	31	1.1/4"	- 20	1.1/4" - 11	28,5	47,5	23,0			46
M10710-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	50,0	23,0			50
M10710-32-32	51	2"	- 32	2" - 11	44,0	55,4	27,0			65



M10510

BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6

BSP 平行外螺纹 (60° 锥形底座) - BS5200 / ISO 8434-6

AGR 60° INNENKONUS (BSP-GEWINDE NACH BS5200 / ISO 8434-6)

MASCHIO GAS CILINDRICO 60° - BS5200 / ISO 8434-6

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
------------	-----------	--	--	--------	------------------	--	--	--	--

	DN	inch	Size	T	B	A	C		H ₁	
M10510-03-02	5	3/16"	- 03	1/8" - 28	3,5	22,5	10,0		14	
M10510-03-04	5	3/16"	- 03	1/4" - 19	5,0	25,0	11,0		19	
M10510-04-02	6	1/4"	- 04	1/8" - 28	3,5	22,5	10,0		14	
M10510-04-04	6	1/4"	- 04	1/4" - 19	5,0	25,5	11,0		19	
M10510-04-06	6	1/4"	- 04	3/8" - 19	8,0	27,0	12,0		22	
M10510-04-08	6	1/4"	- 04	1/2" - 14	11,0	30,0	14,0		27	
M10510-05-04	8	5/16"	- 05	1/4" - 19	5,0	26,0	11,0		19	
M10510-05-06	8	5/16"	- 05	3/8" - 19	8,0	27,5	12,0		22	
M10510-06-04	10	3/8"	- 06	1/4" - 19	5,0	26,0	11,0		19	
M10510-06-06	10	3/8"	- 06	3/8" - 19	8,0	28,1	12,0		22	
M10510-06-08	10	3/8"	- 06	1/2" - 14	11,0	30,6	14,0		27	
M10510-08-06	12	1/2"	- 08	3/8" - 19	8,0	28,1	12,0		22	
M10510-08-08	12	1/2"	- 08	1/2" - 14	11,0	31,1	14,0		27	
M10510-08-10	12	1/2"	- 08	5/8" - 14	14,5	33,1	16,0		30	
M10510-08-12	12	1/2"	- 08	3/4" - 14	17,0	34,1	16,0		32	
M10510-10-10	16	5/8"	- 10	5/8" - 14	14,5	33,1	16,0		30	
M10510-10-12	16	5/8"	- 10	3/4" - 14	17,0	34,1	16,0		32	
M10510-12-08	19	3/4"	- 12	1/2" - 14	11,0	32,0	14,0		27	
M10510-12-12	19	3/4"	- 12	3/4" - 14	17,0	35,5	16,0		32	
M10510-12-16	19	3/4"	- 12	1" - 11	22,5	39,5	19,0		41	
M10510-16-12	25	1"	- 16	3/4" - 14	17,0	36,5	16,0		32	
M10510-16-16	25	1"	- 16	1" - 11	22,5	40,8	19,0		41	
M10510-16-20	25	1"	- 16	1.1/4" - 11	28,5	44,8	20,0		50	
M10510-20-20	31	1.1/4"	- 20	1.1/4" - 11	28,5	46,5	20,0		50	
M10510-20-24	31	1.1/4"	- 20	1.1/2" - 11	33,5	48,5	22,0		55	
M10510-24-24	38	1.1/2"	- 24	1.1/2" - 11	33,5	49,5	22,0		55	
M10510-32-32	51	2"	- 32	2" - 11	46,0	53,9	25,0		70	

BS STANDARD CONNECTIONS


M20512

BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

BSP 内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)

DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)

FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)




M20513

BSP FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)


BSP 内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)

DKR 60° KONUS (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)

FEMMINA GAS CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M20512-03-02	5	3/16"	- 03	1/8" - 28	3,1	14,8	4,4			14
M20513-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	5,4			19
M20512-04-02	6	1/4"	- 04	1/8" - 28	3,1	15,5	4,4			14
M20513-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,0	5,4			19
M20513-04-06	6	1/4"	- 04	3/8" - 19	7,0	19,1	6,0			22
M20512-05-04	8	5/16"	- 05	1/4" - 19	4,1	17,5	4,2			19
M20513-05-06	8	5/16"	- 05	3/8" - 19	7,0	19,1	6,0			22
M20513-05-08	8	5/16"	- 05	1/2" - 14	9,3	20,5	6,5			27
M20512-06-04	10	3/8"	- 06	1/4" - 19	4,1	18,1	4,2			19
M20513-06-06	10	3/8"	- 06	3/8" - 19	7,0	19,6	6,0			22
M20513-06-08	10	3/8"	- 06	1/2" - 14	9,3	20,0	6,5			27
M20512-08-06	12	1/2"	- 08	3/8" - 19	7,1	20,9	6,0			22
M20513-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5			27
M20512-08-10	12	1/2"	- 08	5/8" - 14	12,1	21,9	10,2			28
M20512-08-12	12	1/2"	- 08	3/4" - 14	15,0	23,4	9,0			32
M20512-10-08	16	5/8"	- 10	1/2" - 14	9,8	24,0	6,5			27
M20512-10-10	16	5/8"	- 10	5/8" - 14	12,5	21,7	10,2			28
M20512-10-12	16	5/8"	- 10	3/4" - 14	15,0	23,2	9,0			32
M20512-12-08	19	3/4"	- 12	1/2" - 14	9,8	25,0	6,5			27
M20512-12-12	19	3/4"	- 12	3/4" - 14	15,0	24,5	9,0			32
M20512-12-16	19	3/4"	- 12	1" - 11	19,8	26,0	10,5			38
M20512-16-12	25	1"	- 16	3/4" - 14	15,0	25,5	9,0			32
M20512-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,5			38



M20592

90° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 90° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKR 90° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)
 FEMMINA GAS 90° CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)

M20593

90° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)
 90° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)
 DKR 90° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)
 FEMMINA GAS 90° CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M20592-03-02	5	3/16"	- 03	1/8" - 28	3,1	21,5	4,4	26,0		14
M20593-03-04	5	3/16"	- 03	1/4" - 19	4,0	29,0	5,4	29,0		19
M20592-04-02	6	1/4"	- 04	1/8" - 28	3,1	28,5	4,4	27,0		14
M20593-04-04	6	1/4"	- 04	1/4" - 19	4,0	29,5	5,4	29,0		19
M20593-04-06	6	1/4"	- 04	3/8" - 19	7,0	29,5	6,0	31,0		22
M20592-05-04	8	5/16"	- 05	1/4" - 19	4,1	26,5	5,4	29,5		19
M20593-05-06	8	5/16"	- 05	3/8" - 19	7,0	32,0	6,0	27,5		22
M20593-05-08	8	5/16"	- 05	1/2" - 14	9,3	36,5	6,5	32,0		27
M20592-06-04	10	3/8"	- 06	1/4" - 19	4,0	27,0	4,2	29,5		19
M20593-06-06	10	3/8"	- 06	3/8" - 19	7,0	36,5	6,0	31,5		22
M20593-06-08	10	3/8"	- 06	1/2" - 14	9,3	36,5	6,5	32,0		27
M20592-08-06	12	1/2"	- 08	3/8" - 19	7,0	45,0	6,0	41,0		22
M20593-08-08	12	1/2"	- 08	1/2" - 14	9,3	45,0	6,5	36,5		27
M20592-08-10	12	1/2"	- 08	5/8" - 14	12,1	44,0	10,2	44,0		28
M20592-08-12	12	1/2"	- 08	3/4" - 14	15,0	44,0	9,0	45,5		32
M20592-10-08	16	5/8"	- 10	1/2" - 14	9,3	53,5	6,5	54,5		27
M20592-10-10	16	5/8"	- 10	5/8" - 14	12,5	53,5	10,2	53,5		28
M20592-10-12	16	5/8"	- 10	3/4" - 14	15,0	53,5	9,0	55,0		32
M20592-12-08	19	3/4"	- 12	1/2" - 14	9,3	45,5	6,5	44,0		27
M20592-12-12	19	3/4"	- 12	3/4" - 14	15,5	61,5	9,0	59,5		32
M20592-12-16	19	3/4"	- 12	1" - 11	19,8	61,5	10,5	62,0		38
M20592-16-12	25	1"	- 16	3/4" - 14	15,0	64,5	9,0	59,5		32
M20592-16-16	25	1"	- 16	1" - 11	19,8	79,5	10,5	76,0		38

BS STANDARD CONNECTIONS


M20542

45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

45° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)

DKR 45° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)

FEMMINA GAS 45° CONO 60° - BS5200 / ISO 12151-6 (DADO SPINATO)




M20543

45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)

45° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)

DRK 45° BOGEN 60° KONUS - (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)

FEMMINA GAS 45° CONO 60° - BS5200 / ISO 12151-6 (DADO PASSANTE)





PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M20542-03-02	5	3/16"	- 03	1/8" - 28	3,1	31,0	4,4	15,0		14
M20543-03-04	5	3/16"	- 03	1/4" - 19	4,0	35,5	5,4	14,5		19
M20542-04-02	6	1/4"	- 04	1/8" - 28	3,1	35,5	4,4	14,5		14
M20543-04-04	6	1/4"	- 04	1/4" - 19	4,0	36,0	5,4	15,0		19
M20543-04-06	6	1/4"	- 04	3/8" - 19	7,0	37,5	6,0	16,0		19
M20542-05-04	8	5/16"	- 05	1/4" - 19	4,0	35,5	5,4	16,0		19
M20543-05-06	8	5/16"	- 05	3/8" - 19	7,0	38,0	6,0	13,5		22
M20543-06-06	10	3/8"	- 06	3/8" - 19	7,0	42,0	6,0	15,0		22
M20543-06-08	10	3/8"	- 06	1/2" - 14	9,3	42,5	6,5	16,0		27
M20542-08-06	12	1/2"	- 08	3/8" - 19	7,1	52,0	6,0	20,0		22
M20543-08-08	12	1/2"	- 08	1/2" - 14	9,3	49,5	6,5	17,0		27
M20542-08-10	12	1/2"	- 08	5/8" - 14	12,1	54,5	10,2	22,5		28
M20542-08-12	12	1/2"	- 08	3/4" - 14	15,0	57,0	9,0	25,0		32
M20542-10-10	16	5/8"	- 10	5/8" - 14	12,5	63,0	10,2	26,0		28
M20542-10-12	16	5/8"	- 10	3/4" - 14	15,0	64,0	9,0	27,0		32
M20542-12-08	19	3/4"	- 12	1/2" - 14	9,3	55,5	6,5	22,5		27
M20542-12-12	19	3/4"	- 12	3/4" - 14	15,5	70,5	9,0	28,5		32
M20542-12-16	19	3/4"	- 12	1" - 11	19,8	72,5	10,5	30,0		38
M20542-16-16	25	1"	- 16	1" - 11	19,8	91,0	10,5	36,5		38

M20812

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 BSP O型圈内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 60° KONUS MIT O-RING -
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6 GESTIFTETE MUTTER)
 FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)

M20813

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)
 BSP O型圈内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)
 DKOR 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6 HINTERLEGETE MUTTER)
 FEMMINA GAS CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C		H ₂
M20813-03-04	5	3/16"	- 03	1/4" - 19	4,0	16,5	4,9			19
M20813-04-04	6	1/4"	- 04	1/4" - 19	4,0	17,5	4,9			19
M20812-06-04	10	3/8"	- 06	1/4" - 19	4,0	18,1	4,9			19
M20813-06-06	10	3/8"	- 06	3/8" - 19	7,0	20,4	6,1			22
M20813-06-08	10	3/8"	- 06	1/2" - 14	9,3	21,0	6,5			27
M20813-08-08	12	1/2"	- 08	1/2" - 14	9,3	20,4	6,5			27
M20812-10-10	16	5/8"	- 10	5/8" - 14	12,5	22,1	9,7			28
M20812-12-12	19	3/4"	- 12	3/4" - 14	15,0	25,0	8,5			32
M20812-16-12	25	1"	- 16	3/4" - 14	15,0	26,0	8,5			32
M20812-16-16	25	1"	- 16	1" - 11	19,8	27,3	10,6			38
M20812-16-20	25	1"	- 16	1 1/4" - 11	26,1	30,8	10,5			50
M20812-20-16	31	1 1/4"	- 20	1" - 11	19,8	29,0	10,5			38
M20812-20-20	31	1 1/4"	- 20	1 1/4" - 11	26,0	31,5	10,5			50
M20812-20-24	31	1 1/4"	- 20	1 1/2" - 11	32,1	29,5	12,5			60
M20812-24-20	38	1 1/2"	- 24	1 1/4" - 11	26,0	31,5	10,5			50
M20812-24-24	38	1 1/2"	- 24	1 1/2" - 11	32,0	30,5	12,5			60
M20812-24-32	38	1 1/2"	- 24	2" - 11	42,0	30,0	16,1			70
M20812-32-32	51	2"	- 32	2" - 11	42,0	31,9	16,1			70

BS STANDARD CONNECTIONS


M20892

90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

90° BSP O型圈内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)

DKOR 90° BOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)

FEMMINA GAS 90° CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)




M20893

90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE - BS5200 / ISO 12151-6 (SLIP-ON NUT)

90° BSP O型圈内螺纹巨肘弯头 (60° 锥) - BS5200 / ISO 12151-6 (带滑套螺母)


DKOR 90° BOGEN 60° KONUS MIT O-RING (BSP-GEWINDE NACH BS5200 / ISO 12151-6 HINTERLEGTE MUTTER)

FEMMINA GAS 90° CONO 60° O-RING BS5200 / ISO 12151-6 (DADO PASSANTE)




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M20893-03-04	5	3/16"	- 03	1/4" - 19	4,0	29,0	4,9	29,0		19
M20893-04-04	6	1/4"	- 04	1/4" - 19	4,0	28,5	4,9	28,5		19
M20892-06-04	10	3/8"	- 06	1/4" - 19	4,0	35,5	4,9	33,0		19
M20893-06-06	10	3/8"	- 06	3/8" - 19	7,0	35,5	6,1	36,0		22
M20893-08-08	12	1/2"	- 08	1/2" - 14	9,3	44,5	6,5	42,0		27
M20892-10-10	16	5/8"	- 10	5/8" - 14	12,5	53,0	9,7	55,0		30
M20892-12-12	19	3/4"	- 12	3/4" - 14	15,0	61,5	8,5	60,0		32
M20892-12-16	19	3/4"	- 12	1" - 11	19,8	61,5	10,5	62,0		38
M20892-16-12	25	1"	- 16	3/4" - 14	15,0	79,5	8,5	60,0		32
M20892-16-16	25	1"	- 16	1" - 11	19,8	79,5	10,6	76,0		38
M20892-16-20	25	1"	- 16	1.1/4" - 11	26,1	79,5	10,5	78,5		50
M20892-20-16	31	1.1/4"	- 20	1" - 11	19,8	79,5	10,5	76,0		38
M20892-20-20	31	1.1/4"	- 20	1.1/4" - 11	26,0	90,5	10,5	83,5		50
M20892-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,1	90,5	12,5	84,5		60
M20892-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	95,0	10,5	90,5		50
M20892-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	108,0	12,5	98,5		60
M20892-32-32	51	2"	- 32	2" - 11	42,0	131,0	16,1	110,5		70

M20842



45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 45° BSP O型圈内螺纹巨肘弯头 (60° 锥)
 BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 45° BOGEN 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)
 FEMMINA GAS 45° CONO 60° O-RING
 BS5200 / ISO 12151-6 (DADO SPINATO)

M20843




45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (SLIP-ON NUT)
 45° BSP O型圈内螺纹巨肘弯头 (60° 锥)
 BS5200 / ISO 12151-6 (带滑套螺母)
 DKOR 45° BOGEN 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6, HINTERLEGTE MUTTER)
 FEMMINA GAS 45° CONO 60° O-RING
 BS5200 / ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C	E	H ₂
M20843-04-04	6	1/4"	- 04		1/4" -19	4,0	36,0	4,9	15,0	19
M20843-06-06	10	3/8"	- 06		3/8" -19	7,0	44,5	6,1	18,5	22
M20843-08-08	12	1/2"	- 08		1/2" -14	9,3	52,0	6,5	20,5	27
M20842-10-10	16	5/8"	- 10		5/8" -14	12,5	63,5	9,7	27,5	30
M20842-12-12	19	3/4"	- 12		3/4" -14	15,5	71,0	8,5	29,0	32
M20842-16-12	25	1"	- 16		3/4" -14	15,0	79,5	8,5	29,0	32
M20842-16-16	25	1"	- 16		1" -11	19,8	90,5	10,6	35,6	38
M20842-16-20	25	1"	- 16		1 1/4" - 11	26,0	93,0	10,5	38,0	50
M20842-20-20	31	1 1/4"	- 20		1 1/4" - 11	26,0	101,5	10,5	39,0	50
M20842-20-24	31	1 1/4"	- 20		1 1/2" - 11	32,0	118,5	12,5	40,5	60
M20842-24-20	38	1 1/2"	- 24		1 1/4" - 11	26,0	106,5	10,5	42,0	50
M20842-24-24	38	1 1/2"	- 24		1 1/2" -11	32,0	118,0	12,5	45,0	60
M20842-32-32	51	2"	- 32		2" -11	42,0	134,0	16,1	47,0	70

BS STANDARD CONNECTIONS

M20882F


90° BSP O-RING FEMALE COMPACT ELBOW 60° CONE
 BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 90° BSP O型圈内螺纹紧凑型弯头 (60° 锥)
 BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 90° KOMPAKTBOGEN 60° KONUS MIT O-RING
 (BSP-GEWINDE NACH BS5200 / ISO 12151-6, GESTIFTETE MUTTER)
 FEMMINA GAS 90° CONO 60° O-RING TIPO COMPATTO
 BS5200 / ISO 12151-6 (DADO SPINATO)




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E	H ₁	H ₂
M20882-04-04F	6	1/4"	- 04	1/4" - 19	4,0	20,0	4,9	22,0	14	19
M20882-06-06F	10	3/8"	- 06	3/8" - 19	7,0	23,1	6,1	27,5	19	22
M20882-08-08F	12	1/2"	- 08	1/2" - 14	9,3	24,9	6,5	31,1	22	27
M20882-10-10F	16	5/8"	- 10	5/8" - 14	12,5	24,6	9,7	32,5	24	28
M20882-12-12F	19	3/4"	- 12	3/4" - 14	15,0	37,5	8,5	36,0	27	32
M20882-16-16F	25	1"	- 16	1" - 11	20,0	51,8	10,6	44,0	36	38

M10610

BSP MALE FLAT SEAT
 BSP 外螺纹平面底座
 AGR FLACH DICHEND
 MASCHIO GAS CILINDRICO SEDE PIANA



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M10610-04-04	6	1/4"	- 04	1/4" - 19	6,0	25,5	11,0		19	
M10610-06-06	10	3/8"	- 06	3/8" - 19	9,5	28,1	12,0		22	
M10610-06-08	10	3/8"	- 06	1/2" - 14	13,0	30,6	14,0		27	
M10610-08-08	12	1/2"	- 08	1/2" - 14	13,0	31,1	14,0		27	
M10610-12-12	19	3/4"	- 12	3/4" - 14	18,0	35,5	16,0		32	




M20612

BSP FEMALE FLAT SEAT (THRUST-WIRE NUT)

BSP 内螺纹平面底座 (带止推金属丝螺母)

DKR FLACHDICHTEND (BSP-GEWINDE, GESTIFTETE MUTTER)

FEMMINA GAS SEDE PIANA (DADO SPINATO)



M20613

BSP FEMALE FLAT SEAT (SLIP-ON NUT)

BSP 内螺纹平面底座 (滑套螺母)

DKR FLACHDICHTEND (BSP-GEWINDE, HINTERLEGTE MUTTER)

FEMMINA GAS SEDE PIANA (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm						
	DN	inch	Size		T	B	A	C			H ₂
M20613-04-04	6	1/4"	- 04	1/4" - 19	4,0	14,5	7,9				19
M20613-05-06	8	5/16"	- 05	3/8" - 19	7,0	16,0	9,0				22
M20613-06-06	10	3/8"	- 06	3/8" - 19	7,0	16,6	9,0				22
M20613-06-08	10	3/8"	- 06	1/2" - 14	9,3	17,5	9,8				27
M20613-08-08	12	1/2"	08	1/2" - 14	9,3	17,9	9,8				27
M20612-08-12	12	1/2"	- 08	3/4" - 14	15,0	20,9	11,5				32
M20612-10-12	16	5/8"	- 10	3/4" - 14	15,0	20,7	11,5				32
M20612-12-12	19	3/4"	- 12	3/4" - 14	15,0	22,0	11,5				32
M20612-12-16	19	3/4"	- 12	1" - 11	19,8	23,5	13,0				38
M20612-16-16	25	1"	- 16	1" - 11	19,8	24,8	13,0				38

SAE STANDARD CONNECTIONS


M12510

JIC MALE 37° CONE - SAE J516 / ISO 12151-5

JIC 外螺纹 37° 锥 - SAE J516 / ISO 12151-5


AGJ 37° AUSSENKONUS (UNF-GEWINDE NACH SAE J516 / ISO 12151-5)

MASCHIO JIC CONO 37° - SAE J516 / ISO 12151-5




PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M12510-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,0	14,0		12	
M12510-04-05	6	1/4"	- 04	1/2" - 20	5,5	29,0	14,0		14	
M12510-04-06	6	1/4"	- 04	9/16" - 18	7,0	29,0	14,0		17	
M12510-05-04	8	5/16"	- 05	7/16" - 20	4,0	29,0	14,0		14	
M12510-05-05	8	5/16"	- 05	1/2" - 20	5,5	29,0	14,0		14	
M12510-05-06	8	5/16"	- 05	9/16" - 18	7,0	29,0	14,0		17	
M12510-06-05	10	3/8"	- 06	1/2" - 20	5,5	29,5	14,0		17	
M12510-06-06	10	3/8"	- 06	9/16" - 18	7,0	29,6	14,0		17	
M12510-06-08	10	3/8"	- 06	3/4" - 16	9,3	34,1	16,5		19	
M12510-06-10	10	3/8"	- 06	7/8" - 14	12,5	38,6	19,5		24	
M12510-08-06	12	1/2"	- 08	9/16" - 18	7,0	32,0	14,0		19	
M12510-08-08	12	1/2"	- 08	3/4" - 16	9,3	34,4	16,5		19	
M12510-08-10	12	1/2"	- 08	7/8" - 14	12,5	38,9	19,5		24	
M12510-08-12	12	1/2"	- 08	1.1/16" - 12	15,0	42,9	22,0		27	
M12510-10-10	16	5/8"	- 10	7/8" - 14	12,5	39,2	19,5		24	
M12510-10-12	16	5/8"	- 10	1.1/16" - 12	15,0	42,7	22,0		27	
M12510-12-10	19	3/4"	- 12	7/8" - 14	12,5	41,5	19,5		27	
M12510-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	44,0	22,0		27	
M12510-12-14	19	3/4"	- 12	1.3/16" - 12	16,0	44,5	22,5		32	
M12510-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	47,0	23,0		34	
M12510-16-12	25	1"	- 16	1.1/16" - 12	15,0	44,8	22,0		32	
M12510-16-16	25	1"	- 16	1.5/16" - 12	19,8	47,8	23,0		34	
M12510-16-20	25	1"	- 16	1.5/8" - 12	26,0	52,8	24,3		42	
M12510-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	53,5	24,3		42	
M12510-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	60,5	27,5		50	
M12510-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	60,5	27,5		50	
M12510-32-32	51	2"	- 32	2.1/2" - 12	42,0	71,8	34,0		65	

M22512



JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带止推金属丝螺母)
 DKJ 37° DICKTOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)

M22513



JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)
 JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带滑套螺母)
 DKJ 37° DICKTOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)
 FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm						
	DN	inch	Size	T	B	A	C				H ₂
M22513-03-04	5	3/16"	- 03	7/16" - 20	3,0	15,1	9,0				15
M22512-03-05	5	3/16"	- 03	1/2" - 20	4,0	15,5	9,2				17
M22512-04-04	6	1/4"	- 04	7/16" - 20	4,0	15,5	8,2				17
M22512-04-05	6	1/4"	- 04	1/2" - 20	4,0	15,8	9,2				17
M22513-04-06	6	1/4"	- 04	9/16" - 18	4,0	16,5	9,8				19
M22512-05-04	8	5/16"	- 05	7/16" - 20	4,0	15,5	8,2				17
M22512-05-05	8	5/16"	- 05	1/2" - 20	5,5	16,0	9,2				17
M22512-05-06	8	5/16"	- 05	9/16" - 18	7,0	15,7	9,7				19
M22513-05-08	8	5/16"	- 05	3/4" - 16	5,5	16,7	10,7				22
M22512-06-05	10	3/8"	- 06	1/2" - 20	5,5	16,6	9,5				17
M22512-06-06	10	3/8"	- 06	9/16" - 18	7,0	16,1	9,2				19
M22513-06-08	10	3/8"	- 06	3/4" - 16	7,0	17,3	10,7				22
M22513-06-10	10	3/8"	- 06	7/8" - 14	9,3	18,1	12,4				27
M22512-08-08	12	1/2"	- 08	3/4" - 16	9,3	19,9	10,2				22
M22513-08-10	12	1/2"	- 08	7/8" - 14	9,3	18,5	12,4				27
M22513-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	21,8	13,8				32
M22512-10-10	16	5/8"	- 10	7/8" - 14	12,5	19,9	12,3				27
M22513-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	21,7	13,8				32
M22512-12-08	19	3/4"	- 12	3/4" - 16	9,3	21,5	10,2				22
M22512-12-10	19	3/4"	- 12	7/8" - 14	12,5	21,5	12,3				27
M22512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	22,5	14,2				32
M22512-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	23,1	14,8				36
M22512-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	23,0	15,2				38
M22512-16-12	25	1"	- 16	1.1/16" - 12	15,0	23,3	14,4				32
M22512-16-16	25	1"	- 16	1.5/16" - 12	19,8	23,8	15,2				38
M22512-16-20	25	1"	- 16	1.5/8" - 12	26,0	29,8	16,2				50
M22512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	30,0	16,2				50
M22512-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	35,0	18,8				60
M22512-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	35,0	18,8				60
M22512-32-24	51	2"	- 32	1.7/8" - 12	32,0	37,0	18,8				60
M22512-32-32	51	2"	- 32	2.1/2" - 12	44,0	35,4	24,0				75

SAE STANDARD CONNECTIONS

M22711

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (CRIMPED-BACK NUT)

JIC 内螺纹 37° 锥形底座双六角螺母 - SAE J516 / ISO 12151-5 (带扣压-支撑螺母)

DKJ 37° MIT KONTERSECHSKANT (UNF GEWINDE NACH SAE J516 / ISO 12151-5, VORGEKRIMPTE MUTTER)

FEMMINA JIC CONO 37° DOPPIO ESAGONO SAE J516 / ISO 12151-5 (DADO PRESSATO)

M22711K

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (CRIMPED-BACK COMPACT NUT)

JIC 内螺纹 37° 锥形底座双六角螺母


SAE J516 / ISO 12151-5 (带扣压-支撑紧凑型螺母)

DKJ (KOMPAKT) 37° MIT KONTERSECHSKANT

(UNF GEWINDE NACH SAE J516 / ISO 12151-5, VORGEKRIMPTE MUTTER)

FEMMINA JIC CONO 37° DOPPIO ESAGONO

SAE J516 / ISO 12151-5 (DADO PRESSATO COMPATTO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M22711-03-04K	5	3/16"	- 03	7/16" - 20	4,0	20	9		12	15
M22711-04-04K	6	1/4"	- 04	7/16" - 20	4,0	20,5	9		12	15
M22711-04-06K	6	1/4"	- 04	9/16" - 18	7,0	21,6	9,5		14	17
M22711-06-06K	10	3/8"	- 06	9/16" - 18	7,0	22,1	9,5		17	17
M22711-06-08	10	3/8"	- 06	3/4" - 16	9,3	21,7	10,7		19	22
M22711-08-08	12	1/2"	- 08	3/4" - 16	9,3	26,9	10,7		19	22
M22711-08-10K	12	1/2"	- 08	7/8" - 14	9,3	29,6	12,5		22	25
M22711-10-10K	16	5/8"	- 10	7/8" - 14	9,3	29,5	12,5		22	25
M22711-12-12	19	3/4"	- 12	1.1/16" - 12	15	30,1	14,1		27	32
M22711-16-16	25	1"	- 16	1.5/16" - 12	19,8	35,5	15,3		32	38
M22711-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	42,0	16,1		41	50
M22711-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	46,5	18,6		50	60
M22711-32-32	51	2"	- 32	2.1/2" - 12	42,0	50,5	23,5		65	75

M22712K

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON - SAE J516 / ISO 12151-5 (THRUST-WIRE COMPACT NUT)

JIC 内螺纹 37° 锥形底座双六角螺母


SAE J516 / ISO 12151-5 (带止推金属丝紧凑型螺母)

DKJ KOMPAKT 37° DK MIT KONTERSECHSKANT

(UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)

FEMMINA JIC CONO 37° DOPPIO ESAGONO

SAE J516 / ISO 12151-5 (DADO SPINATO COMPATTO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm						
	DN	inch	Size		T	B	A	C		H ₁	H ₂
M22712-03-04K	5	3/16"	- 03		7/16" - 20	4,0	20,5	8,2		12	15
M22712-04-04K	6	1/4"	- 04		7/16" - 20	4,0	21,0	8,2		12	15
M22712-04-06K	6	1/4"	- 04		9/16" - 18	7,0	24,1	9,2		14	17
M22712-06-06K	10	3/8"	- 06		9/16" - 18	7,0	24,6	9,2		17	17
M22712-08-10K	12	1/2"	- 08		7/8" - 14	12,5	28,4	12,6		22	25
M22712-10-10K	16	5/8"	- 10		7/8" - 14	12,5	29,0	12,6		22	25

SAE STANDARD CONNECTIONS

M22712

JIC FEMALE 37° CONE SEAT DOUBLE HEXAGON SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)


JIC 内螺纹 37° 锥形底座双六角螺母 SAE J516 / ISO 12151-5 (带止推金属丝紧凑型螺母)

DKJ 37° DK MIT KONTERSECHSKANT


(UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)

FEMMINA JIC CONO 37° DOPPIO ESAGONO

SAE J516 / ISO 12151-5 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		B	A	C		H ₁	H ₂
M22712-03-04	5	3/16"	- 03	7/16" - 20	4,0	20,5	8,2		12	17
M22712-04-04	6	1/4"	- 04	7/16" - 20	4,0	21,0	8,2		12	17
M22712-04-05	6	1/4"	- 04	1/2" - 20	4,0	21,5	9,2		12	17
M22712-04-06	6	1/4"	- 04	9/16" - 18	7,0	24,1	9,2		14	19
M22712-05-05	8	5/16"	- 05	1/2" - 20	5,5	21,5	9,2		14	17
M22712-05-06	8	5/16"	- 05	9/16" - 18	7,0	24,1	9,2		14	19
M22712-05-08	8	5/16"	- 05	3/4" - 16	9,3	26,0	10,6		19	22
M22712-06-04	10	3/8"	- 06	7/16" - 20	4,0	24,5	8,2		17	17
M22712-06-05	10	3/8"	- 06	1/2" - 20	5,5	25,0	9,2		17	17
M22712-06-06	10	3/8"	- 06	9/16" - 18	7,0	24,6	9,2		17	19
M22712-06-08	10	3/8"	- 06	3/4" - 16	9,3	27,1	10,2		19	22
M22712-06-10	10	3/8"	- 06	7/8" - 14	12,5	28,0	12,3		22	27
M22712-08-06	12	1/2"	- 08	9/16" - 18	7,0	24,7	9,2		19	19
M22712-08-08	12	1/2"	- 08	3/4" - 16	9,3	27,4	10,2		19	22
M22712-08-10	12	1/2"	- 08	7/8" - 14	12,5	28,4	12,3		22	27
M22712-08-12	12	1/2"	- 08	1.1/16" - 12	14,0	30,0	14,2		27	32
M22712-10-08	16	5/8"	- 10	3/4" - 16	9,3	28,5	10,2		22	22
M22712-10-10	16	5/8"	- 10	7/8" - 14	12,5	29,0	12,3		22	27
M22712-10-12	16	5/8"	- 10	1.1/16" - 12	15,0	29,5	14,2		27	32
M22712-12-08	19	3/4"	- 12	3/4" - 16	9,3	30,0	10,2		27	22
M22712-12-10	19	3/4"	- 12	7/8" - 14	12,5	30,0	12,3		27	27
M22712-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	31,5	14,2		27	32
M22712-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	33,0	14,8		30	36
M22712-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	32,5	15,2		32	38
M22712-16-12	25	1"	- 16	1.1/16" - 12	12,5	33,8	14,2		32	32
M22712-16-16	25	1"	- 16	1.5/16" - 12	19,8	34,3	15,2		32	38
M22712-16-20	25	1"	- 16	1.5/8" - 12	26,0	42,8	16,2		41	50
M22712-20-16	31	1.1/4"	- 20	1.5/16" - 12	19,8	36,0	15,2		38	38
M22712-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	43,5	16,2		41	50
M22712-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	51,0	18,8		50	60
M22712-32-32	51	2"	- 32	2.1/2" - 12	42,0	55,5	24,0		65	75



M22592

90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 90° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母)
 DKJ 90° BOGEN 37° DICKTOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC 90° CONO 37° SAE J516 / ISO 12151-5 (DADO SPINATO)

M22593

90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)
 90° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带滑套螺母)
 DKJ 90° BOGEN 37° DICKTOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)
 FEMMINA JIC 90° CONO 37° SAE J516 / ISO 12151-5 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M22593-03-04	5	3/16"	- 03	7/16" - 20	3,0	26,0	9,0	23,5		15
M22592-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,5	8,2	27,0		17
M22592-04-05	6	1/4"	- 04	1/2" - 20	4,0	28,5	9,2	27,5		17
M22593-04-06	6	1/4"	- 04	9/16" - 18	4,0	29,5	9,8	28,0		19
M22593-04-08	6	1/4"	- 04	3/4" - 16	7,0	29,3	11,0	30,5		22
M22592-05-05	8	5/16"	- 05	1/2" - 20	5,5	29,5	9,2	27,5		17
M22592-05-06	8	5/16"	- 05	9/16" - 18	7,0	31,0	9,2	28,5		19
M22592-06-05	10	3/8"	- 06	1/2" - 20	5,5	30,1	9,5	26,5		17
M22592-06-06	10	3/8"	- 06	9/16" - 18	7,0	35,5	9,2	32,5		19
M22593-06-08	10	3/8"	- 06	3/4" - 16	7,0	36,5	10,7	29,5		22
M22593-06-10	10	3/8"	- 06	7/8" - 14	9,3	36,5	12,4	31,5		27
M22592-08-06	12	1/2"	- 08	9/16" - 18	7,0	37,0	9,2	33,0		19
M22592-08-08	12	1/2"	- 08	3/4" - 16	9,3	44,0	10,2	41,0		22
M22593-08-10	12	1/2"	- 08	7/8" - 14	9,3	45,0	12,4	36,0		27
M22593-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	45,0	13,8	36,0		32
M22592-10-10	16	5/8"	- 10	7/8" - 14	12,5	53,5	12,3	52,5		27
M22593-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	51,5	13,8	50,0		32
M22592-12-10	19	3/4"	- 12	7/8" - 14	12,5	55,0	12,3	52,5		27
M22592-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	62,0	14,2	58,0		32
M22592-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	62,0	14,8	58,0		36
M22592-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	62,0	15,2	57,5		38
M22592-16-16	25	1"	- 16	1.5/16" - 12	19,8	77,0	15,2	67,0		38
M22592-16-20	25	1"	- 16	1.5/8" - 12	26,0	77,5	16,2	74,5		50
M22592-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	90,5	16,2	86,5		50
M22592-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	90,5	18,8	91,0		60
M22592-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	108,0	18,8	100,5		60
M22592-32-32	51	2"	- 32	2.1/2" - 12	44,0	142,0	24,0	137,0		75

SAE STANDARD CONNECTIONS


M24792

90° JIC FEMALE LONG DROP ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)

90° JIC 内螺纹加长弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母)

DKJ 90° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)

FEMMINA JIC 90° CONO 37° CURVA LUNGA - SAE J516 / ISO 12151-5 (DADO SPINATO)




M24793

90° JIC FEMALE LONG DROP ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)


90° JIC 内螺纹加长弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带滑套螺母)

DKJ 90° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)

FEMMINA JIC 90° CONO 37° CURVA LUNGA - SAE J516 / ISO 12151-5 (DADO PASSANTE)




PART. REF.	HOSE BORE			THREAD	DIMENSIONS						
	DN	inch	Size		mm						
M24792-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,5	8,2	45,0			17
M24792-04-05	6	1/4"	- 04	1/2" - 20	4,0	28,5	9,2	45,0			17
M24793-04-06	6	1/4"	- 04	9/16" - 18	4,0	29,5	9,8	55,5			19
M24792-06-06	10	3/8"	- 06	9/16" - 18	7,0	35,5	9,2	55,0			19
M24793-06-08	10	3/8"	- 06	3/4" - 16	7,0	36,5	10,7	61,5			22
M24792-08-08	12	1/2"	- 08	3/4" - 16	9,4	40,6	10,3	61,5			22
M24793-08-10	12	1/2"	- 08	7/8" - 14	9,4	45,0	12,4	65,0			27
M24792-10-10	16	5/8"	- 10	7/8" - 14	12,5	53,5	12,3	65,5			27
M24792-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	62,0	14,2	94,5			32
M24792-16-16	25	1"	- 16	1.5/16" - 12	19,8	77,0	15,2	110,0			38



M22542

45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 45° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母)
 DKJ 45° BOGEN 37° DICHTKOPF (UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)
 FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)



M22543

45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (SLIP-ON NUT)
 45° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带滑套螺母)
 DKJ 45° BOGEN 37° DICHTKOPF (UND-GEWINDE NACH SAE J516 / ISO 12151-5, HINTERLEGTE MUTTER)
 FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M22542-03-04	5	3/16"	- 03	7/16" - 20	4,0	35,0	8,2	14,5		17
M22542-04-04	6	1/4"	- 04	7/16" - 20	4,0	35,5	8,2	14,5		17
M22542-04-05	6	1/4"	- 04	1/2" - 20	4,0	35,7	9,2	14,5		17
M22543-04-06	6	1/4"	- 04	9/16" - 18	4,0	35,5	9,8	14,0		19
M22542-05-05	8	5/16"	- 05	1/2" - 20	5,5	37,5	9,2	14,5		17
M22542-05-06	8	5/16"	- 05	9/16" - 18	7,0	38,0	9,2	14,5		19
M22542-06-06	10	3/8"	- 06	9/16" - 18	7,0	42,0	9,2	16,5		19
M22543-06-08	10	3/8"	- 06	3/4" - 16	7,0	41,0	10,7	14,0		22
M22543-06-10	10	3/8"	- 06	7/8" - 14	9,3	42,5	12,4	15,5		27
M22542-08-08	12	1/2"	- 08	3/4" - 16	9,3	52,0	10,2	20,0		22
M22543-08-10	12	1/2"	- 08	7/8" - 14	9,3	49,5	12,4	17,0		27
M22543-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	50,0	13,8	17,0		32
M22542-10-10	16	5/8"	- 10	7/8" - 14	12,5	62,0	12,3	25,5		27
M22543-10-12	16	5/8"	- 10	1.1/16" - 12	12,5	60,0	13,8	24,0		32
M22542-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	70,0	14,2	27,5		32
M22542-12-14	19	3/4"	- 12	1.3/16" - 12	15,0	69,0	14,8	27,5		36
M22542-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	70,0	15,2	27,5		38
M22542-16-12	25	1"	- 16	1.1/16" - 12	15,0	72,5	14,2	27,5		32
M22542-16-16	25	1"	- 16	1.5/16" - 12	19,8	86,0	15,2	32,0		38
M22542-16-20	25	1"	- 16	1.5/8" - 12	26,0	90,0	16,2	36,0		50
M22542-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	103,5	16,2	41,5		50
M22542-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	106,5	18,8	44,5		60
M22542-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	119,0	18,8	46,5		60
M22542-32-32	51	2"	- 32	2.1/2" - 12	44,0	163,0	24,0	68,0		75

SAE STANDARD CONNECTIONS

M22582F

90° JIC FEMALE COMPACT ELBOW 37° CONE SEAT

SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)

90° JIC 内螺纹紧凑型弯头 (37° 锥形底座)


SAE J516 / ISO 12151-5 (带止推金属丝螺母)

DKJ 90° KOMPAKT BOGEN 37° DICHTKOPF

(UNF-GEWINDE NACH SAE J516 / ISO 12151-5, GESTIFTETE MUTTER)

FEMMINA JIC 90° TIPO COMPATTO CONO 37°

SAE J516 / ISO 12151-5 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E	H ₁	H ₂
M22582-04-04F	6	1/4"	- 04	7/16" - 20	4,0	20,0	8,2	20,5	14	17
M22582-04-06F	6	1/4"	- 04	9/16" - 18	7,0	20,0	9,2	21,5	14	19
M22582-06-06F	10	3/8"	- 06	9/16" - 18	7,0	23,1	9,2	24,0	19	19
M22582-06-08F	10	3/8"	- 06	3/4" - 16	9,3	26,6	10,2	28,0	22	22
M22582-08-08F	12	1/2"	- 08	3/4" - 16	9,3	24,9	10,2	28,0	22	22
M22582-08-10F	12	1/2"	- 08	7/8" - 14	12,5	24,9	12,3	29,0	22	27
M22582-12-12F	19	3/4"	- 12	1.1/16" - 12	15,0	37,5	14,2	33,0	27	32
M22582-16-16F	25	1"	- 16	1.5/16" - 12	20,0	51,8	15,2	40,0	36	38


M12410

ORFS MALE - SAE J516 / ISO 12151-1

ORFS 外螺纹 - SAE J516 / ISO 12151-1


ORFS AUSSENGEWINDE NACH SAE J516 / ISO 12151-1

MASCHIO ORFS - SAE J516 / ISO 12151-1



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M12410-04-04	6	1/4"	- 04	9/16" - 18	4,0	24,0	9,8		16	
M12410-04-06	6	1/4"	- 04	11/16" - 16	6,7	26,6	11,2		19	
M12410-05-06	8	5/16"	- 05	11/16" - 16	6,7	27,0	11,2		19	
M12410-06-06	10	3/8"	- 06	11/16" - 16	6,7	27,6	11,2		19	
M12410-06-08	10	3/8"	- 06	13/16" - 16	9,3	30,0	12,8		22	
M12410-08-08	12	1/2"	- 08	13/16" - 16	9,3	30,6	12,8		22	
M12410-08-10	12	1/2"	- 08	1" - 14	12,5	35,0	15,5		27	
M12410-08-12	12	1/2"	- 08	1.3/16" - 12	15,0	37,5	17,0		32	
M12410-10-08	16	5/8"	- 10	13/16" - 16	9,3	30,5	12,8		22	
M12410-10-10	16	5/8"	- 10	1" - 14	12,5	34,7	15,5		27	
M12410-10-12	16	5/8"	- 10	1.3/16" - 12	15,0	37,5	17,0		32	
M12410-12-12	19	3/4"	- 12	1.3/16" - 12	15,0	39,0	17,0		32	
M12410-12-16	19	3/4"	- 12	1.7/16" - 12	19,8	40,5	17,5		38	
M12410-16-16	25	1"	- 16	1.7/16" - 12	19,8	41,8	17,5		38	
M12410-16-20	25	1"	- 16	1.11/16" - 12	26,0	44,0	17,5		46	
M12410-20-20	31	1.1/4"	- 20	1.11/16" - 12	26,0	46,3	17,5		46	
M12410-24-24	38	1.1/2"	- 24	2" - 12	32,0	48,6	17,5		55	

M22411



ORFS FEMALE - SAE J516 / ISO 12151-1 PULLBACK TYPE (CRIMPED BACK-NUT)
 ORFS 内螺纹 - SAE J516 / ISO 12151-1 回拉式 (带扣压-支撑螺母)
 ORFS IG - SAE J516 / ISO 12151-1 RÜCKZUGSAUSFÜHRUNG (VERPRESSTE MUTTER)
 FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE RETRAIBILE (DADO PRESSATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M22411-04-04	6	1/4"	- 04	9/16" - 18	4,0	27,5	8,0		13	19
M22411-04-06	6	1/4"	- 04	11/16" - 16	7,0	30,0	9,5		16	22
M22411-04-08	6	1/4"	- 04	13/16" - 16	9,3	34,5	11,0		19	24
M22411-05-04	8	5/16"	- 05	9/16" - 18	4,0	28,5	8,0		16	19
M22411-05-06	8	5/16"	- 05	11/16" - 16	7,0	30,5	9,5		16	22
M22411-06-04	10	3/8"	- 06	9/16" - 18	4,0	29,0	8,0		16	19
M22411-06-06	10	3/8"	- 06	11/16" - 16	7,0	31,1	9,5		16	22
M22411-06-08	10	3/8"	- 06	13/16" - 16	9,3	35,6	11,0		19	24
M22411-08-06	12	1/2"	- 08	11/16" - 16	7,0	31,9	9,5		19	22
M22411-08-08	12	1/2"	- 08	13/16" - 16	9,3	35,9	11,0		19	24
M22411-08-10	12	1/2"	- 08	1" - 14	11,5	38,4	13,5		24	30
M22411-08-12	12	1/2"	- 08	1.3/16" - 12	13,9	41,9	14,5		28	36
M22411-10-08	16	5/8"	- 10	13/16" - 16	9,3	36,0	11,0		24	24
M22411-10-10	16	5/8"	- 10	1" - 14	11,5	38,7	13,5		24	30
M22411-10-12	16	5/8"	- 10	1.3/16" - 12	13,9	42,0	14,5		28	36
M22411-12-10	19	3/4"	- 12	1" - 14	11,5	41,0	13,5		28	30
M22411-12-12	19	3/4"	- 12	1.3/16" - 12	13,9	43,5	14,5		28	36
M22411-12-16	19	3/4"	- 12	1.7/16" - 12	19,8	45,5	15,0		36	41
M22411-16-12	25	1"	- 16	1.3/16" - 12	13,9	45,8	14,5		36	36
M22411-16-16	25	1"	- 16	1.7/16" - 12	19,8	46,3	15,0		36	41
M22411-16-20	25	1"	- 16	1.11/16" - 12	26,0	49,5	14,8		41	50
M22411-20-20	31	1.1/4"	- 20	1.11/16" - 12	26,0	49,0	14,8		41	50
M22411-24-24	38	1.1/2"	- 24	2" - 12	32,0	54,0	15,8		50	60

SAE STANDARD CONNECTIONS

M27411


ORFS FEMALE - SAE J516 / ISO 12151-1 SHORT TYPE (CRIMPED BACK-NUT)

ORFS 内螺纹 - SAE J516 / ISO 12151-1 短型 (带扣压-支撑螺母)


ORFS VERPRESSTE MUTTER - SAE J516 / ISO 12151-1

KURZE AUSFÜHRUNG (CRIMPED BACK-NUT)

FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE CORTA (DADO PRESSATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M27411-04-04	6	1/4"	- 04	9/16" - 18	4,0	20,5	8,0		13	19
M27411-04-06	6	1/4"	- 04	11/16" - 16	7,0	22,0	9,5		16	22
M27411-05-06	8	5/16"	- 05	11/16" - 16	7,0	25,5	9,5		16	22
M27411-06-06	10	3/8"	- 06	11/16" - 16	7,0	26,0	9,5		16	22
M27411-06-08	10	3/8"	- 06	13/16" - 16	9,3	25,0	11,0		19	24
M27411-08-08	12	1/2"	- 08	13/16" - 16	9,3	25,5	11,0		19	24
M27411-08-10	12	1/2"	- 08	1" - 14	11,5	26,5	13,5		24	30
M27411-08-12	12	1/2"	- 08	1.3/16" - 12	13,9	29,0	14,5		28	36
M27411-10-10	16	5/8"	- 10	1" - 14	11,5	26,5	13,5		24	30
M27411-10-12	16	5/8"	- 10	1.3/16" - 12	13,9	29,0	14,5		28	36
M27411-12-12	19	3/4"	- 12	1.3/16" - 12	13,9	30,5	14,5		28	36
M27411-16-16	25	1"	- 16	1.7/16" - 12	19,8	33,0	15,0		36	41




M22491

90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT)

90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母)

DK 90° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, PRESSMUTTER)

FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 (DADO PRESSATO)



M22493

90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT)

90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带滑套螺母)

DK 90° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER)

FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm						
	DN	inch	Size	T	B	A	C	E		H ₂	
M22493-04-04	6	1/4"	- 04	9/16" - 18	4,0	27,5	8,2	22,0		17	
M22493-04-06	6	1/4"	- 04	11/16" - 16	7,0	27,5	9,5	22,0		22	
M22493-05-06	8	5/16"	- 05	11/16" - 16	7,0	32,0	9,5	23,0		22	
M22491-06-04	10	3/8"	- 06	9/16" - 18	4,0	28,0	8,0	23,0		19	
M22493-06-06	10	3/8"	- 06	11/16" - 16	6,0	30,0	9,5	24,0		22	
M22493-06-08	10	3/8"	- 06	13/16" - 16	9,3	30,0	11,0	26,5		24	
M22491-08-06	12	1/2"	- 08	11/16" - 16	7,0	30,9	9,5	24,5		22	
M22493-08-08	12	1/2"	- 08	13/16" - 16	9,3	40,5	11,0	30,0		24	
M22493-08-10	12	1/2"	- 08	1" - 14	11,5	40,5	13,5	30,0		30	
M22493-08-12	12	1/2"	- 08	1.3/16" - 12	13,9	39,5	14,5	37,5		36	
M22491-10-08	16	5/8"	- 10	13/16" - 16	9,3	41,5	11,0	34,0		24	
M22493-10-10	16	5/8"	- 10	1" - 14	11,5	48,0	13,5	37,5		30	
M22493-10-12	16	5/8"	- 10	1.3/16" - 12	13,9	48,0	14,5	41,0		36	
M22491-12-10	19	3/4"	- 12	1" - 14	11,5	49,0	13,5	38,0		30	
M22493-12-12	19	3/4"	- 12	1.3/16" - 12	13,9	56,5	14,5	48,0		36	
M22493-12-16	19	3/4"	- 12	1.7/16" - 12	19,8	56,5	14,8	47,5		41	
M22491-16-12	25	1"	- 16	1.3/16" - 12	13,9	57,6	14,5	48,0		36	
M22493-16-16	25	1"	- 16	1.7/16" - 12	19,8	71,5	14,8	56,0		41	
M22493-16-20	25	1"	- 16	1.11/16" - 12	26,0	71,5	14,8	58,5		50	
M22493-20-20	31	1.1/4"	- 20	1.11/16" - 12	26,0	83,0	14,8	66,0		50	
M22493-24-24	38	1.1/2"	- 24	2" - 12	32,0	102,0	14,8	79,5		60	

SAE STANDARD CONNECTIONS


M24493*

90° ORFS FEMALE LONG DROP ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT)

90° ORFS 内螺纹加长弯头 - SAE J516 / ISO 12151-1 (带滑套螺母)

DK 90° BOGEN ORFS LANGE SCHENKEL (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER)


FEMMINA ORFS A 90° CURVA LUNGA - SAE J516 / ISO 12151-1 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M24493-04-04	6	1/4"	- 04	9/16" - 18	4,4	24,5	8,2	45,5		17
M24493-04-06	6	1/4"	- 04	11/16" - 16	7,0	24,5	9,5	53,5		22
M24493-06-06	10	3/8"	- 06	11/16" - 16	7,0	31,5	9,5	53,5		22
M24493-06-08	10	3/8"	- 06	13/16" - 16	6,7	32,0	11,0	53,5		24
M24493-08-08	12	1/2"	- 08	13/16" - 16	10,0	37,0	11,0	63,5		24
M24493-08-10	12	1/2"	- 08	1" - 14	9,6	37,0	13,5	64,0		30
M24493-10-10	16	1/2"	- 10	1" - 14	9,6	41,0	13,5	69,0		30
M24493-10-12	16	5/8"	- 10	1.3/16" - 12	12,7	41,0	14,5	73,0		36
M24493-12-12	19	5/8"	- 12	1.3/16" - 12	15,5	45,5	14,5	96,0		36
M24493-16-16	25	1"	- 16	1.7/16" - 12	20,6	58,5	14,8	113,5		41


* Brazed solution / 使用焊接工艺 / Lötanschluss / Con saldatura

M22441



45° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED-BACK NUT)
 45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母)
 DK 45° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, PRESSMUTTER)
 FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 (DADO PRESSATO)

M22443



45° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (SLIP-ON NUT)
 45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带滑套螺母)
 DK 45° BOGEN ORFS (UNF-GEWINDE NACH SAE J516 / ISO 12151-1, HINTERLEGTE MUTTER)
 FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M22443-04-04	6	1/4"	- 04	9/16" - 18	4,0	31,0	8,2	10,5		17
M22443-04-06	6	1/4"	- 04	11/16" - 16	7,0	31,0	9,5	10,5		22
M22443-05-06	8	5/16"	- 05	11/16" - 16	7,0	34,0	9,5	10,5		22
M22443-06-06	10	3/8"	- 06	11/16" - 16	7,0	32,5	9,5	11,0		22
M22443-06-08	10	3/8"	- 06	13/16" - 16	9,3	34,0	11,0	12,5		24
M22441-08-06	12	1/2"	- 08	11/16" - 16	7,0	33,0	9,5	11,0		22
M22443-08-08	12	1/2"	- 08	13/16" - 16	9,3	42,0	11,0	13,0		24
M22443-08-10	12	1/2"	- 08	1" - 14	11,5	42,0	13,5	13,5		30
M22443-08-12	12	1/2"	- 08	1.3/16" - 12	13,9	46,5	14,5	18,5		36
M22443-10-10	16	5/8"	- 10	1" - 14	11,5	49,0	13,5	16,0		30
M22443-10-12	16	5/8"	- 10	1.3/16" - 12	13,9	51,5	14,5	18,5		36
M22441-12-10	19	3/4"	- 12	1" - 14	11,5	50,5	13,5	16,5		30
M22443-12-12	19	3/4"	- 12	1.3/16" - 12	13,9	60,5	14,5	21,5		36
M22443-12-16	19	3/4"	- 12	1.7/16" - 12	19,8	61,0	14,8	21,0		41
M22441-16-12	25	1"	- 16	1.3/16" - 12	14,5	66,0	14,5	21,0		36
M22443-16-16	25	1"	- 16	1.7/16" - 12	19,8	72,0	14,8	23,5		41
M22443-16-20	25	1"	- 16	1.11/16" - 12	26,0	74,0	14,8	25,2		50
M22443-20-20	31	1.1/4"	- 20	1.11/16" - 12	26,0	82,0	14,8	27,0		50
M22443-24-24	38	1.1/2"	- 24	2" - 12	32,0	98,0	14,8	31,5		60

SAE STANDARD CONNECTIONS


M13010

SAE MALE O-RING BOSS TYPE - SAE J516 / ISO 11926

SAE 外螺纹 O形圈轮毂型 - SAE J516 / ISO 11926


AGJO SAE O-RING (UNF-GEWINDE NACH SAE J516 / ISO 11926)

MASCHIO SAE O-RING - SAE J516 / ISO 11926



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M13010-04-04	6	1/4"	- 04	7/16" - 20	4,0	24,0	9,1		14	
M13010-04-06	6	1/4"	- 04	9/16" - 18	7,1	24,5	9,9		17	
M13010-06-06	10	3/8"	- 06	9/16" - 18	7,0	25,6	9,9		17	
M13010-06-08	10	3/8"	- 06	3/4" - 16	9,3	28,6	11,1		22	
M13010-06-10	10	3/8"	- 06	7/8" - 14	12,5	31,5	12,7		25	
M13010-08-08	12	1/2"	- 08	3/4" - 16	9,3	28,9	11,1		22	
M13010-08-10	12	1/2"	- 08	7/8" - 14	12,5	31,9	12,7		25	
M13010-08-12	12	1/2"	- 08	1.1/16" - 12	15,0	38,5	15,1		32	
M13010-10-10	16	5/8"	- 10	7/8" - 14	12,5	32,0	12,7		25	
M13010-10-12	16	5/8"	- 10	1.1/16" - 12	15,0	37,7	15,1		32	
M13010-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	39,5	15,1		32	
M13010-12-16	19	3/4"	- 12	1.5/16" - 12	19,8	40,0	15,1		38	
M13010-16-16	25	1"	- 16	1.5/16" - 12	19,8	41,0	15,1		38	
M13010-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	43,5	15,1		46	

M14310*



SAE SWIVEL MALE O-RING BOSS TYPE - SAE J516 / ISO 11926

SAE 旋转外螺纹 O 型圈轮毂型 - SAE J516 / ISO 11926

AGJO SAE O-RING DREHBAR (UNF-GEWINDE NACH SAE J516 / ISO 11926)

MASCHIO SAE O-RING GIREVOLE - SAE J516 / ISO 11926

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M14310-04-04	6	1/4"	- 04	7/16" - 20	4,0	41,0	9,1			17
M14310-04-06	6	1/4"	- 04	9/16" - 18	7,0	44,0	9,9			22
M14310-06-06	10	3/8"	- 06	9/16" - 18	7,0	45,9	9,9			22
M14310-06-08	10	3/8"	- 06	3/4" - 16	7,0	47,8	11,1			22
M14310-08-08	12	1/2"	- 08	3/4" - 16	9,3	50,9	11,1			27
M14310-08-10	12	1/2"	- 08	7/8" - 14	9,3	42,2	13,0			27
M14310-08-12	12	1/2"	- 08	1.1/16" - 12	12,5	49,4	15,0			32
M14310-10-10	16	5/8"	- 10	7/8" - 14	9,3	41,4	13,0			27
M14310-12-12	19	3/4"	- 12	1.1/16" - 12	12,5	47,8	15,0			32

* Not to be used as a live swivel / 不可用作活动旋转接头 / Nicht zu benutzen als Drehverschraubung / Da non usare come applicazione rotante

SAE STANDARD CONNECTIONS


M14390*

90° SAE SWIVEL MALE O-RING BOSS TYPE - SAE J516 / ISO 11926

90° SAE 旋转外螺纹 O型圈轮毂型 - SAE J516 / ISO 11926

AGJO 90° KOMPAKT BOGEN DREHBAR MIT O-RING (UNF-GEWINDE NACH J516 / ISO 11926)

MASCHIO SAE O-RING GIREVOLE 90° - SAE J516 / ISO 11926



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E	H ₁	H ₂
M14390-06-06	10	3/8"	- 06	9/16" - 18	5,7	20,1	9,9	40,0	22	17
M14390-06-08	10	3/8"	- 06	3/4" - 16	7,0	20,1	11,1	44,4	22	22
M14390-08-08	12	1/2"	- 08	3/4" - 16	9,3	22,1	11,1	49,0	27	22
M14390-08-10	12	1/2"	- 08	7/8" - 14	9,3	27,5	13,0	47,5	27	27
M14390-10-10	16	5/8"	- 10	7/8" - 14	9,3	28,0	13,0	47,5	27	27
M14390-12-12	19	3/4"	- 12	1.1/16" - 12	12,5	27,5	15,0	55,5	32	32

* Brazed solution - Not to be used as a live swivel / 使用焊接工艺 - 不可用作活动旋转接头 / Lötanschluss - Nicht zu benutzen als Drehverschraubung / Con saldatura - Da non usare come applicazione rotante


M22612

SAE FEMALE 45° CONE SEAT - SAE J516/J512 (THRUST-WIRE NUT)

SAE 内螺纹 45° 锥形底座 - SAE J516/J512 (带止推金属丝螺母)

DKJ DICKTKOPF GERADE 45° KONUS (UNF-GEWINDE NACH J516/J512, GESTIFTETE MUTTER)

FEMMINA SAE CONO 45° - SAE J516/J512 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M22612-04-04	6	1/4"	- 04	7/16" - 20	4,0	15,5	8,2			17
M22612-05-06	8	5/16"	- 05	5/8" - 18	7,0	16,5	10,8			22
M22612-06-06	10	3/8"	- 06	5/8" - 18	7,0	16,6	10,8			22
M22612-12-12	19	3/4"	- 12	1.1/16" - 14	15,0	22,7	14,4			32


M22692

90° SAE FEMALE SWEPT ELBOW 45° CONE SEAT - SAE J516/J512 (THRUST-WIRE NUT)


90° SAE 内螺纹巨肘弯头 45° 锥形底座 - SAE J516/J512 (带止推金属丝螺母)

DKJ 90° BOGEN 45° KONUS (UNF-GEWINDE NACH SAE J516/J512, GESTIFTETE MUTTER)

FEMMINA SAE 90° CONO 45° - SAE J516/J512 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M22692-04-04	6	1/4"	- 04	7/16" - 20	4,0	28,3	8,0	27,0		17
M22692-06-06	10	3/8"	- 06	5/8" - 18	7,0	35,5	10,8	33,0		22
M22692-12-12	19	3/4"	- 12	1.1/6" - 14	15,0	62,0	14,4	58,0		32



M12810

NPTF MALE 60° CONE SEAT - SAE J516/J514

NPTF 外螺纹 60° 锥形底座 - SAE J516/J514

AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514

MASCHIO NPTF CONO 60° - SAE J516 /J514

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm				
------------	-----------	--	--	--------	------------------	--	--	--	--

	DN	inch	Size	T	B	A	C		H ₁	
M12810-03-02	5	3/16"	- 03	1/8" - 27	4,0	23,6	10,0		12	
M12810-03-04	5	3/16"	- 03	1/4" - 18	5,5	29,1	14,5		14	
M12810-04-02	6	1/4"	- 04	1/8" - 27	4,0	24,1	10,0		12	
M12810-04-04	6	1/4"	- 04	1/4" - 18	5,5	29,0	14,5		14	
M12810-04-06	6	1/4"	- 04	3/8" - 18	9,3	31,5	14,5		19	
M12810-04-08	6	1/4"	- 04	1/2" - 14	9,3	33,5	19,2		24	
M12810-05-04	8	5/16"	- 05	1/4" - 18	5,5	30,0	14,5		14	
M12810-05-06	8	5/16"	- 05	3/8" - 18	9,3	32,0	14,5		19	
M12810-06-04	10	3/8"	- 06	1/4" - 18	5,5	30,1	14,5		14	
M12810-06-06	10	3/8"	- 06	3/8" - 18	9,3	28,6	14,5		19	
M12810-06-08	10	3/8"	- 06	1/2" - 14	12,5	34,6	19,2		24	
M12810-08-06	12	1/2"	- 08	3/8" - 18	9,3	28,9	14,5		19	
M12810-08-08	12	1/2"	- 08	1/2" - 14	12,5	34,9	19,2		24	
M12810-08-12	12	1/2"	- 08	3/4" - 14	16,0	35,4	19,2		27	
M12810-10-08	16	5/8"	- 10	1/2" - 14	12,5	38,7	19,2		24	
M12810-10-12	16	5/8"	- 10	3/4" - 14	16,0	40,2	19,2		27	
M12810-12-12	19	3/4"	- 12	3/4" - 14	16,0	36,5	19,2		27	
M12810-12-08	19	3/4"	- 12	1/2" - 14	12,5	36,5	13,6		27	
M12810-12-16	19	3/4"	- 12	1" - 11,5	19,8	46,0	24,2		36	
M12810-16-12	25	1"	- 16	3/4" - 14	15,5	38,8	19,2		32	
M12810-16-16	25	1"	- 16	1" - 11,5	19,8	43,8	24,2		36	
M12810-16-20	25	1"	- 16	1.1/4" - 11,5	26,0	56,3	25,0		46	
M12810-20-20	31	1.1/4"	- 20	1.1/4" - 11,5	26,0	56,5	25,0		46	
M12810-24-24	38	1.1/2"	- 24	1.1/2" - 11,5	32,0	57,6	26,0		50	
M12810-32-32	51	2"	- 32	2" - 11,5	45,0	64,3	26,5		65	
M12810-40-40	63	2.1/2"	- 40	2.1/2" - 8	55,4	78,0	39,9		80	
M12810-48-48	76	3"	- 48	3" - 8	68,9	86,0	41,5		100	

MULTIFIT TYPE



SAE STANDARD CONNECTIONS


M14110R*

NPTF SWIVEL MALE 60° CONE SEAT - SAE J516/J514

NPTF 旋转外螺纹 60° 锥形底座 - SAE J516/J514

AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514

MASCHIO NPTF CONO 60° GIREVOLE - SAE J516/J514



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M14110-04-02R	6	1/4"	- 04	1/8" - 27	3,0	41,9	10,0			17
M14110-04-04R	6	1/4"	- 04	1/4" - 18	4,0	46,4	14,5			17
M14110-04-06R	6	1/4"	- 04	3/8" - 18	7,0	46,4	14,5			19
M14110-06-04R	10	3/8"	- 06	1/4" - 18	4,0	50,5	14,5			22
M14110-06-06R	10	3/8"	- 06	3/8" - 18	7,0	50,5	14,5			22
M14110-06-08R	10	3/8"	- 06	1/2" - 14	9,3	55,2	19,2			24
M14110-08-06R	12	1/2"	- 08	3/8" - 18	7,0	51,5	14,5			27
M14110-08-08R	12	1/2"	- 08	1/2" - 14	9,3	59,0	19,2			27
M14110-12-12R	19	3/4"	- 12	3/4" - 14	16,0	57,9	19,2			32
M14110-16-16R	25	1"	- 16	1" - 11,5	19,8	65,8	24,2			38

* Not to be used as a live swivel / 不可用作活动旋转接头 / Nicht zu benutzen als Drehverschraubung / Da non usare come applicazione rotante


M22812

NPSM FEMALE 60° CONE - SAE J516/J514 (THRUST-WIRE NUT)

NPSM 内螺纹 60° 锥形 - SAE J516/J514 (带止推金属丝螺母)

DK NPSM 60° KONUS - SAE J516/J514 (NPTF-GEWINDE, GESTIFTETE MUTTER)

FEMMINA NPSM CONO 60° - SAE J516/J514 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M22812-04-04	6	1/4"	- 04	1/4" - 18	4,0	17,5	4,2			19
M22812-06-04	10	3/8"	- 06	1/4" - 18	4,0	18,0	4,2			19
M22812-06-06	10	3/8"	- 06	3/8" - 18	7,0	20,9	6,0			22
M22812-08-08	12	1/2"	- 08	1/2" - 14	9,3	22,8	6,5			27
M22812-12-12	19	3/4"	- 12	3/4" - 14	15,0	24,5	9,0			32
M22812-16-16	25	1"	- 16	1" - 11,5	19,8	27,3	10,5			38


M23311

ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D			
M23311-08-08	12	1/2"	- 08	1/2"	9,3	50,9	30,3			
M23311-08-12	12	1/2"	- 08	3/4"	15,0	57,7	38,0			
M23311-10-08	16	5/8"	- 10	3/4"	9,3	51,0	30,3			
M23311-10-12	16	1/2"	- 10	3/4"	15,0	65,7	38,0			
M23311-12-12	19	3/4"	- 12	3/4"	15,0	58,0	38,0			
M23311-12-16	19	3/4"	- 12	1"	20,0	58,0	44,6			
M23311-12-20	19	3/4"	- 12	1.1/4"	26,0	69,5	51,0			
M23311-16-12	25	1"	- 16	3/4"	15,0	60,5	38,0			
M23311-16-16	25	1"	- 16	1"	19,8	64,3	44,6			
M23311-16-20	25	1"	- 16	1.1/4"	26,0	70,3	51,0			
M23311-20-16	31	1.1/4"	- 20	1"	20,0	64,5	44,6			
M23311-20-20	31	1.1/4"	- 20	1.1/4"	26,0	70,5	51,0			
M23311-20-24	31	1.1/4"	- 20	1.1/2"	32,0	72,5	60,5			
M23311-24-24	38	1.1/2"	- 24	1.1/2"	32,0	75,6	60,5			
M23311-24-32	38	1.1/2"	- 24	2"	42,0	75,6	71,6			
M23311-32-32	51	2"	- 32	2"	42,0	78,9	71,6			
M23311-32-40	51	2"	- 32	2.1/2"	56,0	80,9	84,3			
M23311-38-40	60	2.3/8"	- 38	2.1/2"	56,0	84,0	84,3			
M23311-40-32	63	2.1/2"	- 40	2"	42,0	78,5	71,6			
M23311-40-40	63	2.1/2"	- 40	2.1/2"	56,0	84,0	84,3			
M23311-40-48	63	2.1/2"	- 40	3"	68,9	79,0	101,6			
M23311-40-56	63	2.1/2"	- 40	3.1/2"	79,0	90,5	114,3			
M23311-40-64	63	2.1/2"	- 40	4"	90,0	96,5	127,0			
M23311-48-48	76	3"	- 48	3"	69,0	86,0	101,6			
M23311-56-56	90	3.1/2"	- 56	3.1/2"	79,0	94,5	114,3			
M23311-64-64	102	4"	- 64	4"	90,0	100,5	127,0			


M23321

22,5° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

22,5° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

22,5° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3


FLANGIA 22,5° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23321-08-08	12	1/2"	- 08	1/2"	9,3	63,9	30,3	8,0		
M23321-12-12	19	3/4"	- 12	3/4"	15,0	74,7	38,0	9,8		
M23321-12-16	19	3/4"	- 12	1"	20,0	74,7	44,6	9,8		
M23321-16-16	25	1"	- 16	1"	19,8	88,8	44,6	11,5		
M23321-16-20	25	1"	- 16	1.1/4"	26,0	88,5	51,0	11,5		
M23321-16-24	25	1"	- 16	1.1/2"	32,0	88,5	60,5	11,5		
M23321-20-20	31	1.1/4"	- 20	1.1/4"	26,0	100,0	51,0	12,0		
M23321-20-20018	31	1.1/4"	- 20	1.1/4"	26,0	99,0	51,0	18,0		
M23321-20-24	31	1.1/4"	- 20	1.1/2"	32,0	101,8	60,5	12,8		
M23321-24-24	38	1.1/2"	- 24	1.1/2"	32,0	116,5	60,5	14,0		
M23321-24-24023	38	1.1/2"	- 24	1.1/2"	32,0	115,0	60,5	23,0		
M23321-24-32	38	1.1/2"	- 24	2"	42,0	116,5	71,6	14,0		
M23321-32-32	51	2"	- 32	2"	42,0	134,5	71,6	15,0		
M23321-40-40*	63	2.1/2"	- 40	2.1/2"	52,0	72,0	84,3	14,0		
M23321-40-48*	63	2.1/2"	- 40	3"	52,0	79,0	101,6	17,0		
M23321-48-48*	76	3"	- 48	3"	61,0	111,0	101,6	20,5		

* All items are made from solid with the exception of (*) / 所有规格都由实体棒材加工而成，带有(*)的规格除外。 / Mit Ausnahme der mit (*) bezeichneten Positionen sind alle Armaturen in einteiliger Ausführung / Ad eccezione di (*) tutte le referenze sono a pezzo unico

M23331



30° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

30° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

30° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 30° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23331-08-08	12	1/2"	- 08	1/2"	9,3	62,6	30,3	11,2		
M23331-08-12	12	1/2"	- 08	3/4"	15,0	63,5	38,0	11,5		
M23331-12-12	19	3/4"	- 12	3/4"	15,0	73,2	38,0	13,9		
M23331-12-16	19	3/4"	- 12	1"	20,0	73,2	44,6	13,9		
M23331-16-16	25	1"	- 16	1"	19,8	86,8	44,6	16,4		
M23331-16-20	25	1"	- 16	1.1/4"	26,0	87,0	51,0	16,5		
M23331-20-20	31	1.1/4"	- 20	1.1/4"	26,0	98,0	51,0	17,4		
M23331-20-24	31	1.1/4"	- 20	1.1/2"	32,0	100,0	60,5	18,5		
M23331-20-24044	31	1.1/4"	- 20	1.1/2"	32,0	131,5	60,5	44,0		
M23331-24-24	38	1.1/2"	- 24	1.1/2"	32,0	114,3	60,5	20,0		
M23331-24-32	38	1.1/2"	- 24	2"	42,0	114,5	71,6	20,0		
M23331-32-32	51	2"	- 32	2"	42,0	132,0	71,6	22,0		
M23331-40-40*	63	2.1/2"	- 40	2.1/2"	52,0	79,5	84,3	20,5		
M23331-40-48*	63	2.1/2"	- 40	3"	52,0	85,5	101,6	24,5		
M23331-48-48*	76	3"	- 48	3"	61,0	110,5	101,6	27,5		

* All items are made from solid with the exception of (*) / 所有规格都由实体棒材加工而成，带有 (*) 的规格除外。 / Mit Ausnahme der mit (*) bezeichneten Positionen sind alle Armaturen in einteiliger Ausführung / Ad eccezione di (*) tutte le referenze sono a pezzo unico

SAE STANDARD CONNECTIONS


M23341

45° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

45° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3


45° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 45° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm						
	DN	inch	Size		B	A	D	E			
M23341-06-08	10	3/8"	- 06	1/2"	9,3	52,5	30,3	17,0			
M23341-08-08	12	1/2"	- 08	1/2"	9,3	58,5	30,3	18,5			
M23341-08-12	12	1/2"	- 08	3/4"	15,0	59,5	38,0	19,0			
M23341-08-16	12	1/2"	- 08	1"	20,0	59,5	44,6	19,0			
M23341-10-12	16	5/8"	- 10	3/4"	15,0	61,0	38,0	22,0			
M23341-12-12	19	3/4"	- 12	3/4"	15,0	68,5	38,0	23,0			
M23341-12-16	19	3/4"	- 12	1"	20,0	68,5	44,6	23,0			
M23341-16-12	25	1"	- 16	3/4"	15,0	74,5	38,0	23,0			
M23341-16-16	25	1"	- 16	1"	19,8	81,5	44,6	27,5			
M23341-16-20	25	1"	- 16	1.1/4"	26,0	81,5	51,0	27,5			
M23341-20-16	31	1.1/4"	- 20	1"	19,8	84,5	44,6	29,5			
M23341-20-20	31	1.1/4"	- 20	1.1/4"	26,0	92,0	51,0	29,5			
M23341-20-24	31	1.1/4"	- 20	1.1/2"	32,0	93,5	60,5	31,0			
M23341-24-24	38	1.1/2"	- 24	1.1/2"	32,0	107,5	60,5	34,5			
M23341-24-32	38	1.1/2"	- 24	2"	42,0	107,5	71,6	34,5			
M23341-32-32	51	2"	- 32	2"	42,0	124,0	71,6	39,0			
M23341-32-40	51	2"	- 32	2.1/2"	56,0	136,5	84,3	49,5			
M23341-40-32	63	2.1/2"	- 40	2"	42,0	152,0	71,5	48,5			
M23341-40-40*	63	2.1/2"	- 40	2.1/2"	56,0	74,5	84,3	30,0			
M23341-40-48*	63	2.1/2"	- 40	3"	52,0	79,5	101,6	36,0			
M23341-48-48*	76	3"	- 48	3"	61,0	109,0	101,6	41,0			
M23341-56-56*	90	3.1/2"	- 56	3.1/2"	79,0	115,0	114,3	47,5			
M23341-56-64*	90	3.1/2"	- 56	4"	79,0	118,5	127,0	51,0			
M23341-64-64*	102	4"	- 64	4"	90,0	132,0	127,0	56,5			

* All items are made from solid with the exception of (*) / 所有规格都由实体棒材加工而成，带有 (*) 的规格除外。 / Mit Ausnahme der mit (*) bezeichneten Positionen sind alle Armaturen in einteiliger Ausführung / Ad eccezione di (*) tutte le referenze sono a pezzo unico



M23361

60° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

60° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

60° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 60° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm						
	DN	inch	Size		B	A	D	E			
M23361-08-08	12	1/2"	- 08	1/2"	9,3	71,5	30,3	25,8			
M23361-08-12	12	1/2"	- 08	3/4"	15,0	72,5	38,0	26,5			
M23361-12-12	19	3/4"	- 12	3/4"	15,0	86,9	38,0	33,0			
M23361-12-16	19	3/4"	- 12	1"	20,0	87,0	44,6	33,0			
M23361-16-16	25	1"	- 16	1"	19,8	104,0	44,6	39,0			
M23361-16-20	25	1"	- 16	1.1/4"	26,0	104,0	44,6	39,0			
M23361-20-20	31	1.1/4"	- 20	1.1/4"	26,0	120,0	51,0	43,0			
M23361-20-20065	31	1.1/4"	- 20	1.1/4"	26,0	107,5	51,0	65,0			
M23361-20-24	31	1.1/4"	- 20	1.1/2"	32,0	121,0	60,5	44,7			
M23361-24-20	38	1.1/2"	- 24	1.1/4"	26,0	141,5	51,0	46,5			
M23361-24-24	38	1.1/2"	- 24	1.1/2"	32,0	143,6	60,5	50,7			
M23361-24-32	38	1.1/2"	- 24	2"	42,0	143,5	71,6	51,0			
M23361-32-32	51	2"	- 32	2"	42,0	129,0	71,6	58,0			
M23361-40-40*	63	2.1/2"	- 40	2.1/2"	52,0	84,5	84,3	47,5			
M23361-40-48*	63	2.1/2"	- 40	3"	52,0	88,5	101,6	55,0			
M23361-48-48*	76	3"	- 48	3"	61,0	120,0	101,6	64,0			

* All items are made from solid with the exception of (*) / 所有规格都由实体棒材加工而成，带有(*)的规格除外。 / Mit Ausnahme der mit (*) bezeichneten Positionen sind alle Armaturen in einteiliger Ausführung / Ad eccezione di (*) tutte le referenze sono a pezzo unico

SAE STANDARD CONNECTIONS


M23371

67,5° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

67,5° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3


67,5° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 67,5° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23371-08-08	12	1/2"	- 08	1/2"	9,3	67,9	30,3	29,3		
M23371-08-12	12	1/2"	- 08	3/4"	15,0	68,5	38,0	30,5		
M23371-08-16	12	1/2"	- 08	1"	20,0	68,5	44,6	30,5		
M23371-12-12	19	3/4"	- 12	3/4"	15,0	82,2	38,0	38,0		
M23371-12-16	19	3/4"	- 12	1"	20,0	82,2	44,6	38,0		
M23371-12-20	19	3/4"	- 12	1.1/4"	26,0	82,5	51,0	38,0		
M23371-16-16	25	1"	- 16	1"	19,8	98,6	44,6	45,0		
M23371-16-20	25	1"	- 16	1.1/4"	26,0	98,5	51,0	45,0		
M23371-20-20	31	1.1/4"	- 20	1.1/4"	26,0	114,0	51,0	50,0		
M23371-20-24	31	1.1/4"	- 20	1.1/2"	32,0	115,0	60,5	52,0		
M23371-24-24	38	1.1/2"	- 24	1.1/2"	32,0	136,4	60,5	59,2		
M23371-24-32	38	1.1/2"	- 24	2"	42,0	136,5	71,6	59,0		
M23371-32-32	51	2"	- 32	2"	42,0	162,0	71,6	68,5		
M23371-32-32085	51	2"	- 32	2"	42,0	151,5	71,6	85,0		
M23371-32-40	51	2"	- 32	2.1/2"	56,0	171,5	84,3	83,5		
M23371-40-40*	63	2.1/2"	- 40	2.1/2"	52,0	87,5	84,3	57,5		
M23371-40-48*	63	2.1/2"	- 40	3"	52,0	91,0	101,6	65,0		

* All items are made from solid with the exception of (*) / 所有规格都由实体棒材加工而成，带有 (*) 的规格除外。 / Mit Ausnahme der mit (*) bezeichneten Positionen sind alle Armaturen in einteiliger Ausführung / Ad eccezione di (*) tutte le referenze sono a pezzo unico



M23391

90° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 90° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23391-06-08	10	3/8"	- 06	1/2"	9,3	45,0	30,3	35,0		
M23391-06-08041	10	3/8"	- 06	1/2"	9,3	45,0	30,3	41,0		
M23391-08-08	12	1/2"	- 08	1/2"	9,3	54,5	30,3	40,0		
M23391-08-12	12	1/2"	- 08	3/4"	15,0	54,5	38,0	41,0		
M23391-08-16	12	1/2"	- 08	1"	20,0	54,5	44,6	66,0		
M23391-10-08	16	5/8"	- 10	1/2"	9,3	56,0	30,3	46,5		
M23391-10-12	16	5/8"	- 10	3/4"	15,0	56,0	38,0	47,5		
M23391-12-12	19	3/4"	- 12	3/4"	15,0	64,5	38,0	52,0		
M23391-12-16	19	3/4"	- 12	1"	20,0	64,5	44,6	52,0		
M23391-12-20	19	3/4"	- 12	1.1/4"	26,0	64,5	51,0	52,0		
M23391-16-16	25	1"	- 16	1"	19,8	77,5	44,6	62,0		
M23391-16-20	25	1"	- 16	1.1/4"	26,0	77,5	51,0	62,0		
M23391-16-24	25	1"	- 16	1.1/2"	32,0	77,5	60,5	64,0		
M23391-20-16	31	1.1/4"	- 20	1"	20,0	80,0	44,6	66,0		
M23391-20-20	31	1.1/4"	- 20	1.1/4"	26,0	90,5	51,0	70,0		
M23391-20-24	31	1.1/4"	- 20	1.1/2"	32,0	90,5	60,5	72,0		
M23391-20-32	31	1.1/4"	- 20	2"	42,0	93,5	71,6	76,0		
M23391-24-20	38	1.1/2"	- 24	1.1/4"	26,0	104,5	51,0	75,0		
M23391-24-24	38	1.1/2"	- 24	1.1/2"	32,0	108,0	60,5	84,0		
M23391-24-32	38	1.1/2"	- 24	2"	42,0	108,0	71,6	84,0		
M23391-32-24	51	2"	- 32	1.1/2"	32,0	133,0	60,5	84,0		
M23391-32-32	51	2"	- 32	2"	42,0	129,0	71,6	99,0		
M23391-32-40	51	2"	- 32	2.1/2"	56,0	132,5	84,3	116,0		
M23391-40-32	63	2.1/2"	- 40	2"	42,0	149,5	71,6	114,0		
M23391-40-40*	63	2.1/2"	- 40	2.1/2"	52,0	88,5	84,3	88,0		
M23391-40-48*	63	2.1/2"	- 40	3"	52,0	88,5	101,6	95,0		
M23391-48-48*	76	3"	- 48	3"	61,0	124,0	101,6	115,0		
M23391-48-56*	76	3"	- 48	3.1/2"	61,0	124,0	114,3	115,0		
M23391-56-56*	90	3.1/2"	- 56	3.1/2"	79,0	134,5	114,3	134,5		
M23391-64-64*	102	4"	- 64	4"	90,0	153,5	127,0	158,5		

* All items are made from solid with the exception of (*) / 所有规格都由实体棒材加工而成，带有 (*) 的规格除外。 / Mit Ausnahme der mit (*) bezeichneten Positionen sind alle Armaturen in einteiliger Ausführung / Ad eccezione di (*) tutte le referenze sono a pezzo unico

SAE STANDARD CONNECTIONS


M23391 LONG DROP

90° LONG DROP ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

90° 加长 ISO/SAE CODIGO 61 法兰 - SAE J516 / ISO 12151-3

90° LONG DROP ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 90° CURVA LUNGA ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23391-16-20117	25	1"	- 16	1.1/4"	26,0	77,5	51,0	117		
M23391-16-24107	25	1"	- 16	1.1/2"	32,0	77,5	60,5	107		
M23391-20-20091	31	1.1/4"	- 20	1.1/4"	26,0	90,5	51,0	91		
M23391-20-20100	31	1.1/4"	- 20	1.1/4"	26,0	90,5	51,0	100		
M23391-20-20112	31	1.1/4"	- 20	1.1/4"	26,0	90,5	51,0	112		
M23391-20-20130	31	1.1/4"	- 20	1.1/4"	26,0	90,5	51,0	130		
M23391-20-20168	31	1.1/4"	- 20	1.1/4"	26,0	90,5	51,0	168		
M23391-20-24118	31	1.1/4"	- 20	1.1/2"	32,0	90,5	60,5	118		
M23391-20-24130	31	1.1/4"	- 20	1.1/2"	32,0	90,5	60,5	130		
M23391-24-24148	38	1.1/2"	- 24	1.1/2"	32,0	108,0	60,5	148		
M23391-24-24172	38	1.1/2"	- 24	1.1/2"	32,0	108,0	60,5	172		
M23391-24-32115	38	1.1/2"	- 24	2"	42,0	108,0	71,6	115		
M23391-24-32172	38	1.1/2"	- 24	2"	42,0	108,0	71,6	172		
M23391-32-32203	51	2"	- 32	2"	42,0	129,0	71,6	203		


M23301P

110° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3


110° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

110° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 110° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23301-08-12P	12	1/2"	- 08	3/4"	15,0	47,5	38,0	48,5		
M23301-12-12P	19	3/4"	- 12	3/4"	15,0	89,0	38,0	62		
M23301-12-16P	19	3/4"	- 12	1"	20,0	89,0	44,6	62		
M23301-16-16P	25	1"	- 16	1"	19,8	88,5	44,6	79		
M23301-16-20133P	25	1"	- 16	1.1/4"	26,0	77,0	51,0	133		
M23301-20-20P	31	1.1/4"	- 20	1.1/4"	26,0	102,0	51,0	89		
M23301-20-24P	31	1.1/4"	- 20	1.1/2"	32,0	108,5	60,5	93		
M23301-24-24119P	38	1.1/2"	- 24	1.1/2"	32,0	105,5	60,5	119		
M23301-32-32P	51	2"	- 32	2"	42,0	142,0	71,6	123		



M23301S


125° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

125° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

125° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 125° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23301-32-32151S	51	2"	- 32	2"	42,0	118,5	71,6	151,0		



M23301T

135° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

135° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

135° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3


FLANGIA 135° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23301-12-12T	19	3/4"	- 12	3/4"	15,0	74,5	38,0	70,0		
M23301-12-16T	19	3/4"	- 12	1"	20,0	74,5	44,6	70,0		
M23301-16-16T	25	1"	- 16	1"	19,8	70,0	44,6	88,5		


SAE STANDARD CONNECTIONS

M23611

ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3
ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3
ISO/SAE CODE 62 FLANSCH - SAE J516/ISO 12151-3
FLANGIA ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D			
M23611-08-08	12	1/2"	- 08	1/2"	9,3	52,1	31,8			
M23611-08-12	12	1/2"	- 08	3/4"	15,0	68,4	41,5			
M23611-10-08	16	5/8"	- 10	1/2"	9,3	52,0	31,8			
M23611-10-12	16	5/8"	- 10	3/4"	15,0	70,2	41,5			
M23611-10-16	16	5/8"	- 10	1"	20,0	80,0	47,7			
M23611-12-12	19	3/4"	- 12	3/4"	15,0	69,0	41,5			
M23611-12-16	19	3/4"	- 12	1"	20,0	81,0	47,7			
M23611-16-16	25	1"	- 16	1"	19,8	82,3	47,7			
M23611-16-20	25	1"	- 16	1.1/4"	26,0	89,8	54,2			
M23611-20-16	31	1.1/4"	- 20	1"	20,0	82,5	47,7			
M23611-20-20	31	1.1/4"	- 20	1.1/4"	26,0	84,5	54,2			
M23611-20-24	31	1.1/4"	- 20	1.1/2"	32,0	90,5	63,7			
M23611-24-24	38	1.1/2"	- 24	1.1/2"	32,0	92,6	63,7			
M23611-32-32	51	2"	- 32	2"	42,0	107,9	79,6			



M23691

90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 61 FLANSCH - SAE J516 / ISO 12151-3


FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23691-08-08	12	1/2"	- 08	1/2"	9,3	54,5	31,8	45,0		
M23691-08-12	12	1/2"	- 08	3/4"	15,0	54,5	41,5	53,0		
M23691-10-08	16	5/8"	- 10	1/2"	9,3	57,5	31,8	45,0		
M23691-10-12	16	5/8"	- 10	3/4"	15,0	56,0	41,5	58,0		
M23691-10-16	16	5/8"	- 10	1"	19,8	55,7	47,7	65,0		
M23691-12-12	19	3/4"	- 12	3/4"	15,0	64,0	41,5	59,0		
M23691-12-16	19	3/4"	- 12	1"	20,0	64,5	47,7	65,0		
M23691-16-16	25	1"	- 16	1"	19,8	73,5	47,7	68,0		
M23691-16-20	25	1"	- 16	1.1/4"	26,0	73,5	54,2	75,0		
M23691-20-16	31	1.1/4"	- 20	1"	20,0	82,5	47,7	68,0		
M23691-20-20	31	1.1/4"	- 20	1.1/4"	26,0	85,5	54,2	81,0		
M23691-20-24	31	1.1/4"	- 20	1.1/2"	32,0	85,5	63,7	91,5		
M23691-24-24	38	1.1/2"	- 24	1.1/2"	32,0	106,0	63,7	94,5		
M23691-24-32	38	1.1/2"	- 24	2"	42,0	106,0	79,6	110,5		
M23691-32-32	51	2"	- 32	2"	42,0	138,0	79,6	132,0		

SAE STANDARD CONNECTIONS

M23641

45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3
45° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3
45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3
FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M23641-08-08	12	1/2"	- 08	1/2"	9,3	62,0	31,8	22,0		
M23641-08-12	12	1/2"	- 08	3/4"	15,0	68,0	41,5	27,5		
M23641-10-08	16	5/8"	- 10	1/2"	9,3	62,5	31,8	23,5		
M23641-10-12	16	5/8"	- 10	3/4"	15,0	67,5	41,5	31,0		
M23641-12-12	19	3/4"	- 12	3/4"	15,0	73,0	41,5	28,0		
M23641-12-16	19	3/4"	- 12	1"	20,0	77,0	47,7	32,5		
M23641-16-12	25	1"	- 16	3/4"	15,0	80,0	41,5	30,0		
M23641-16-16	25	1"	- 16	1"	19,8	83,5	47,7	32,5		
M23641-16-20	25	1"	- 16	1.1/4"	26,0	88,5	54,2	37,5		
M23641-20-20	31	1.1/4"	- 20	1.1/4"	26,0	95,5	54,2	37,5		
M23641-20-24	31	1.1/4"	- 20	1.1/2"	32,0	102,5	63,7	45,0		
M23641-24-24	38	1.1/2"	- 24	1.1/2"	32,0	118,0	63,7	44,0		
M23641-24-32	38	1.1/2"	- 24	2"	42,0	129,0	79,6	55,5		
M23641-32-32	51	2"	- 32	2"	42,0	151,5	79,6	60,5		


M22010

METRIC STANDPIPE LIGHT DUTY - DIN 2353 / ISO 8434-1

公制立管轻型系列 - DIN 2353 / ISO 8434-1

BEL - DIN 2353 / ISO 8434-1

ESTREMITÀ TUBOLARE SERIE LEGGERA - DIN 2353 / ISO 8434-1



PART. REF.	HOSE BORE			PIPE	DIMENSIONS mm					
	DN	inch	Size	D	B	A	C			
M22010-03-04	5	3/16"	- 03	4	2,0	29,6	22,0			
M22010-03-06	5	3/16"	- 03	6	3,0	28,6	22,0			
M22010-04-06	6	1/4"	- 04	6	3,0	29,5	22,0			
M22010-05-08	8	5/16"	- 05	8	5,5	30,0	22,0			
M22010-05-10	8	5/16"	- 05	10	7,0	30,5	23,0			
M22010-06-10	10	3/8"	- 06	10	7,0	30,6	23,0			
M22010-06-12	10	3/8"	- 06	12	8,0	30,6	23,0			
M22010-06-15	10	3/8"	- 06	15	10,5	32,6	25,0			
M22010-08-12	12	1/2"	- 08	12	8,0	30,9	23,0			
M22010-08-15	12	1/2"	- 08	15	10,5	32,9	25,0			
M22010-08-18	12	1/2"	- 08	18	12,5	33,9	26,0			
M22010-10-18	16	5/8"	- 10	18	12,5	34,2	26,0			
M22010-10-22	16	5/8"	- 10	22	15,0	36,2	28,0			
M22010-12-18	19	3/4"	- 12	18	15,0	36,2	26,0			
M22010-12-22	19	3/4"	- 12	22	15,0	38,0	28,0			
M22010-16-28	25	1"	- 16	28	20,5	41,3	30,0			
M22010-20-35	31	1.1/4"	- 20	35	26,0	48,5	36,0			
M22010-24-42	38	1.1/2"	- 24	42	32,0	52,6	40,0			

DIN STANDARD CONNECTIONS


M22110

METRIC STANDPIPE HEAVY DUTY - DIN 2353 / ISO 8434-1


公制立管重型系列 - DIN 2353 / ISO 8434-1

BES - DIN 2353 / ISO 8434-1

ESTREMITÀ TUBOLARE SERIE PESANTE - DIN 2353 / ISO 8434-1



PART. REF.	HOSE BORE			PIPE	DIMENSIONS mm					
	DN	inch	Size	D	B	A	C			
M22110-03-08	5	3/16"	- 03	8	3,0	30,6	24,0			
M22110-03-10	5	3/16"	- 03	10	3,0	29,5	22,0			
M22110-04-08	6	1/4"	- 04	8	4,0	31,5	24,0			
M22110-04-10	6	1/4"	- 04	10	4,0	33,5	26,0			
M22110-04-12	6	1/4"	- 04	12	7,0	33,5	26,0			
M22110-05-12	8	5/16"	- 05	12	7,0	33,5	26,0			
M22110-06-14	10	3/8"	- 06	14	8,0	36,6	29,0			
M22110-08-14	12	1/2"	- 08	14	9,3	36,9	29,0			
M22110-08-16	12	1/2"	- 08	16	10,5	37,9	30,0			
M22110-10-20	16	5/8"	- 10	20	12,5	44,2	36,0			
M22110-12-20	19	3/4"	- 12	20	15,0	46,0	36,0			
M22110-12-25	19	3/4"	- 12	25	15,0	50,0	40,0			
M22110-16-25	25	1"	- 16	25	15,0	51,3	40,0			
M22110-16-30	25	1"	- 16	30	20,5	55,3	44,0			
M22110-16-38	25	1"	- 16	38	26,0	61,3	50,0			
M22110-20-30	31	1.1/4"	- 20	30	20,5	56,5	44,0			
M22110-20-38	31	1.1/4"	- 20	38	26,0	62,5	50,0			
M22110-24-38	38	1.1/2"	- 24	38	26,0	62,6	50,0			



M22090


90° METRIC STANDPIPE LIGHT DUTY - DIN 2353 / ISO 8434-1

90° 公制立管轻型系列 - DIN 2353 / ISO 8434-1

BEL 90° BOGEN - DIN 2353 / ISO 8434-1

ESTREMITÀ TUBOLARE 90° SERIE LEGGERA - DIN 2353 / ISO 8434-1

PART. REF.	HOSE BORE			PIPE	DIMENSIONS mm					
	DN	inch	Size	D	B	A	E			
M22090-03-06	5	3/16"	- 03	6	3,0	22,5	34,0			
M22090-04-06	6	1/4"	- 04	6	3,0	23,0	34,0			
M22090-05-10	8	5/16"	- 05	10	7,0	29,5	40,0			
M22090-06-10	10	3/8"	- 06	10	7,0	34,0	42,5			
M22090-06-12	10	3/8"	- 06	12	8,0	34,0	45,0			
M22090-08-12	12	1/2"	- 08	12	8,0	34,5	45,0			
M22090-08-15	12	1/2"	- 08	15	10,5	42,0	52,0			
M22090-08-18	12	1/2"	- 08	18	12,5	42,0	55,0			
M22090-10-18	16	5/8"	- 10	18	12,5	49,0	59,0			
M22090-10-22	16	5/8"	- 10	22	15,0	53,5	63,0			
M22090-12-22	19	3/4"	- 12	22	15,0	54,5	63,0			
M22090-16-28	25	1"	- 16	28	19,8	67,5	75,0			
M22090-20-35	31	1 1/4"	- 20	35	26,0	80,5	94,0			



M22190

90° METRIC STANDPIPE HEAVY DUTY - DIN 2353 / ISO 8434-1

90° 公制立管重型系列 - DIN 2353 / ISO 8434-1

BES 90° BOGEN - DIN 2353 / ISO 8434-1

ESTREMITÀ TUBOLARE 90° SERIE PESANTE - DIN 2353 / ISO 8434-1

PART. REF.	HOSE BORE			PIPE	DIMENSIONS mm					
	DN	inch	Size	D	B	A	E			
M22190-04-08	6	1/4"	- 04	8	4,0	27,0	38,0			
M22190-04-10	6	1/4"	- 04	10	6,0	27,0	41,0			
M22190-04-12	6	1/4"	- 04	12	7,0	27,0	44,0			
M22190-05-12	8	5/16"	- 05	12	7,0	30,5	44,0			
M22190-06-14	10	3/8"	- 06	14	9,3	35,0	51,0			
M22190-08-14	12	1/2"	- 08	14	9,3	42,0	53,5			
M22190-08-16	12	1/2"	- 08	16	10,5	43,0	55,0			
M22190-10-20	16	5/8"	- 10	20	12,5	49,0	66,5			
M22190-12-20	19	3/4"	- 12	20	15,0	54,5	69,0			
M22190-12-25	19	3/4"	- 12	25	15,0	57,5	75,0			
M22190-16-25	25	1"	- 16	25	15,0	61,5	76,5			
M22190-16-30	25	1"	- 16	30	19,8	69,5	87,0			

DIN STANDARD CONNECTIONS


M22040

45° METRIC STANDPIPE LIGHT DUTY - DIN 2353 / ISO 8434-1

45° 公制立管轻型系列 - DIN 2353 / ISO 8434-1

BEL 45° BOGEN - DIN 2353 / ISO 8434-1

ESTREMITÀ TUBOLARE 45° SERIE LEGGERA - DIN 2353 / ISO 8434-1



PART. REF.	HOSE BORE			PIPE	DIMENSIONS mm					
	DN	inch	Size	D	B	A	E			
M22040-03-06	5	3/16"	- 03	6	3,0	37,5	20,5			
M22040-04-06	6	1/4"	- 04	6	3,0	38,0	20,5			
M22040-05-10	8	5/16"	- 05	10	7,0	44,5	22,5			
M22040-06-10	10	3/8"	- 06	10	7,0	47,5	23,0			
M22040-06-12	10	3/8"	- 06	12	8,0	49,5	25,0			
M22040-08-15	12	1/2"	- 08	15	10,5	58,0	28,0			
M22040-10-18	16	5/8"	- 10	18	12,5	63,5	30,5			
M22040-12-22	19	3/4"	- 12	22	15,0	69,0	32,0			
M22040-16-28	25	1"	- 16	28	19,8	81,5	37,0			


M22140

45° METRIC STANDPIPE HEAVY DUTY - DIN 2353 / ISO 8434-1


45° 公制立管重型系列 - DIN 2353 / ISO 8434-1

BES 45° BOGEN - DIN 2353 / ISO 8434-1

ESTREMITÀ TUBOLARE 45° SERIE PESANTE - DIN 2353 / ISO 8434-1




PART. REF.	HOSE BORE			PIPE	DIMENSIONS mm					
	DN	inch	Size	D	B	A	E			
M22140-04-08	6	1/4"	- 04	8	4,0	42,0	22,0			
M22140-04-10	6	1/4"	- 04	10	6,0	44,0	24,0			
M22140-06-14	10	3/8"	- 06	14	9,3	54,5	29,0			
M22140-08-16	12	1/2"	- 08	16	10,5	61,0	30,0			
M22140-10-20	16	5/8"	- 10	20	12,5	69,0	36,0			
M22140-12-25	19	3/4"	- 12	25	15,0	80,5	40,5			
M22140-16-25	25	1"	- 16	25	15,0	82,0	41,0			



M21013

METRIC FEMALE 60° CONE - DIN 20078/3863
 公制 60° 锥内螺纹 - DIN 20078/3863
 DKM 60° KONUS - DIN 20078/3863
 FEMMINA METRICA CONO 60° - DIN 20078/3863

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
M21013-10-30	16	5/8"	- 10	M 30x1,5	20,0	20,0	8,1			36
M21013-12-30	19	3/4"	- 12	M 30x1,5	20,0	21,0	8,1			36
M21013-16-38	25	1"	- 16	M 38x1,5	26,0	22,8	7,6			46
M21013-20-45	31	1.1/4"	- 20	M 45x1,5	33,0	23,5	8,1			50
M21013-24-52	38	1.1/2"	- 24	M 52x1,5	40,0	25,0	8,1			60



M21093

90° METRIC FEMALE SWEPT ELBOW 60° CONE - DIN 20078/3863
 90° 公制 60° 锥内螺纹巨肘弯头 - DIN 20078/3863
 DKM 90° BOGEN 60° KONUS - DIN 20078/3863
 FEMMINA METRICA 90° CONO 60° - DIN 20078/3863

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M21093-12-30	19	3/4"	- 12	M 30x1,5	20,0	61,5	8,1	54,5		36
M21093-16-38	25	1"	- 16	M 38x1,5	26,0	76,5	7,6	63,0		46
M21093-20-45	31	1.1/4"	- 20	M 45x1,5	33,0	92,0	8,1	81,0		50

DIN STANDARD CONNECTIONS


M21312

METRIC FEMALE MULTISEAL - DIN 20078/3868 (THRUST-WIRE NUT)

公制内螺纹组合密封 - DIN 20078/3868 (带止推金属丝螺母)

DKL UNIVERSALKONUS - DIN 20078/3868 (GESTIFTETE MUTTER)

FEMMINA METRICA CONO UNIVERSALE - DIN 20078/3868 (DADO SPINATO)




M21313

METRIC FEMALE MULTISEAL - DIN 20078/3868 (SLIP-ON NUT)


公制内螺纹组合密封 - DIN 20078/3868 (带滑套螺母)

DKL UNIVERSALKONUS - DIN 20078/3868 (HINTERLEGTE MUTTER)

FEMMINA METRICA CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C			H ₂
M21313-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	18,6	3,7			14
M21312-04-12	6	1/4"	- 04	M 12x1,5	6	4,0	19,5	4,0			17
M21313-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	19,5	3,8			17
M21313-04-16	6	1/4"	- 04	M 16x1,5	10	4,0	19,5	4,0			19
M21313-05-16	8	5/16"	- 05	M 16x1,5	10	5,5	19,5	4,0			19
M21313-05-18	8	5/16"	- 05	M 18x1,5	12	5,5	19,6	4,0			22
M21312-06-14	10	3/8"	- 06	M 14x1,5	8	4,0	19,5	3,9			17
M21312-06-16	10	3/8"	- 06	M 16x1,5	10	7,0	21,6	5,0			19
M21313-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	20,1	4,0			22
M21313-06-22	10	3/8"	- 06	M 22x1,5	15	7,0	21,1	5,2			27
M21312-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	23,0	5,9			22
M21313-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	21,5	5,2			27
M21313-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	22,1	5,5			32




M21392

90° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (THRUST-WIRE NUT)

90° 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带止推金属丝螺母)

DKL UNIVERSALKONUS 90° BOGEN - DIN 20078/3868 (GESTIFTETE MUTTER)

FEMMINA METRICA 90° CONO UNIVERSALE - DIN 20078/3868 (DADO SPINATO)



M21393

90° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (SLIP-ON NUT)

90° 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带滑套螺母)

DKL UNIVERSALKONUS 90° BOGEN - DIN 20078/3868 (HINTERLEGTE MUTTER)

FEMMINA METRICA 90° CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M21393-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	26,0	3,7	27,0		14
M21392-04-12	6	1/4"	- 04	M 12x1,5	6	4,0	28,0	4,0	30,5		17
M21393-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	29,5	3,8	29,5		17
M21393-04-16	6	1/4"	- 04	M 16x1,5	10	4,0	29,5	4,0	29,5		19
M21393-05-16	8	5/16"	- 05	M 16x1,5	10	5,5	32,0	4,0	29,0		19
M21393-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	32,0	4,0	30,5		22
M21392-06-16	10	3/8"	- 06	M 16x1,5	10	7,0	35,5	5,0	38,0		19
M21393-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	36,5	4,0	31,5		22
M21393-06-22	10	3/8"	- 06	M 22x1,5	15	7,0	36,5	5,2	32,0		27
M21393-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	45,0	5,2	36,5		27
M21393-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	51,5	5,5	50,0		32
M21392-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	61,5	3,6	63,0		32

DIN STANDARD CONNECTIONS


M21342

45° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (THRUST-WIRE NUT)

45° 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带止推金属丝螺母)

DKL UNIVERSALKONUS 45° BOGEN - DIN 20078/3868 (GESTIFTETE MUTTER)

FEMMINA METRICA 45° CONO UNIVERSALE - DIN 20078/3868 (DADO SPINATO)




M21343

45° METRIC FEMALE SWEPT ELBOW MULTISEAL DIN 20078/3868 (SLIP-ON NUT)

45° 公制内螺纹巨肘弯头组合密封 DIN 20078/3868 (带滑套螺母)

DKL UNIVERSALKONUS 45° BOGEN - DIN 20078/3868 (HINTERLEGTE MUTTER)

FEMMINA METRICA 45° CONO UNIVERSALE - DIN 20078/3868 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M21343-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	36,5	3,8	15,0		17
M21343-04-16	6	1/4"	- 04	M 16x1,5	10	4,0	36,5	4,0	15,0		19
M21342-05-14	8	5/16"	- 05	M 14x1,5	8	4,0	40,0	3,9	19,5		17
M21343-05-16	8	5/16"	- 05	M 16x1,5	10	5,5	39,0	4,0	15,0		19
M21342-06-16	10	3/8"	- 06	M 16x1,5	10	4,0	46,0	5,0	20,0		19
M21343-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	42,0	4,0	15,5		22
M21343-06-22	10	3/8"	- 06	M 22x1,5	15	7,0	42,5	5,2	15,5		27
M21343-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	49,5	5,2	17,0		27
M21343-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	60,0	5,5	24,0		32


M11110

METRIC MALE 24° CONE SEAT LIGHT DUTY - DIN 20066 / ISO 12151-2

公制外螺纹 24° 锥形底座轻型系列 DIN 20066 / ISO 12151-2

CEL - DIN 20066 / ISO 12151-2

MASCHIO METRICO 24° SERIE LEGGERA - DIN 20066 / ISO 12151-2



PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm						
	DN	inch	Size	T	mm	B	A	C		H ₁	H ₂
M11110-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	21,0	10,0		14	
M11110-04-12	6	1/4"	- 04	M 12x1,5	6	4,0	21,5	10,0		14	
M11110-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	21,5	10,0		14	
M11110-04-16	6	1/4"	- 04	M 16x1,5	10	7,0	23,5	11,0		17	
M11110-04-18	6	1/4"	- 04	M 18x1,5	12	9,0	23,5	11,0		19	
M11110-05-16	8	5/16"	- 05	M 16x1,5	10	7,0	24,0	11,0		17	
M11110-05-18	8	5/16"	- 05	M 18x1,5	12	9,0	24,0	11,0		19	
M11110-06-16	10	3/8"	- 06	M 16x1,5	10	7,0	24,1	11,0		17	
M11110-06-18	10	3/8"	- 06	M 18x1,5	12	9,0	24,6	11,0		19	
M11110-06-22	10	3/8"	- 06	M 22x1,5	15	10,0	25,6	12,0		22	
M11110-06-26	10	3/8"	- 06	M 26x1,5	18	12,5	26,5	12,0		27	
M11110-08-16	12	1/2"	- 08	M 16x1,5	10	7,0	24,5	11,0		22	
M11110-08-18	12	1/2"	- 08	M 18x1,5	12	9,3	24,5	11,0		22	
M11110-08-22	12	1/2"	- 08	M 22x1,5	15	10,0	25,6	12,0		22	
M11110-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	26,4	12,0		27	
M11110-10-22	16	5/8"	- 10	M 22x1,5	15	10,0	25,5	12,0		22	
M11110-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	26,7	12,0		27	
M11110-10-30	16	5/8"	- 10	M 30x2	22	15,0	28,5	14,0		30	
M11110-12-26	19	3/4"	- 12	M 26x1,5	18	15,0	28,5	12,0		27	
M11110-12-30	19	3/4"	- 12	M 30x2	22	15,0	30,0	14,0		30	
M11110-12-36	19	3/4"	- 12	M 36x2	28	19,8	31,2	14,0		36	
M11110-16-36	25	1"	- 16	M 36x2	28	20,0	32,3	14,0		36	
M11110-20-45	31	1.1/4"	- 20	M 45x2	35	26,0	40,5	16,0		46	
M11110-24-52	38	1.1/2"	- 24	M 52x2	42	32,0	42,6	16,0		55	

DIN STANDARD CONNECTIONS


M21512

METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)

公制内螺纹 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOL - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)




M21513

METRIC O-RING FEMALE 24° CONE LIGHT DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

公制内螺纹 24° 锥带O型圈轻型系列 DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOL - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm						
	DN	inch	Size	T	mm	B	A	C			H ₂
M21513-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	21,9	1,7			14
M21513-03-14	5	3/16"	- 03	M 14x1,5	8	4,5	24,5	1,7			17
M21512-04-12	6	1/4"	- 04	M 12x1,5	6	3,0	21,1	2,2			17
M21513-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	22,1	1,7			17
M21513-04-16	6	1/4"	- 04	M 16x1,5	10	6,0	22,6	2,1			19
M21513-04-18	6	1/4"	- 04	M 18x1,5	12	7,0	21,9	2,3			22
M21512-05-14	8	5/16"	- 05	M 14x1,5	8	4,0	20,0	1,7			17
M21513-05-16	8	5/16"	- 05	M 16x1,5	10	6,0	22,6	2,1			19
M21513-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	21,9	2,3			22
M21512-06-16	10	3/8"	- 06	M 16x1,5	10	6,0	23,1	3,0			19
M21513-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	22,4	2,3			22
M21513-06-22	10	3/8"	- 06	M 22x1,5	15	9,3	25,0	2,3			27
M21512-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	29,0	2,9			22
M21513-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	25,4	2,3			27
M21513-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	26,1	2,5			32
M21512-10-18	16	5/8"	- 10	M 18x1,5	12	7,0	29,0	2,9			22
M21512-10-22	16	5/8"	- 10	M 22x1,5	15	9,5	26,5	2,4			27
M21513-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	26,0	2,5			32
M21513-10-30	16	5/8"	- 10	M 30x2	22	15,0	34,0	3,6			36
M21513-10-36	16	5/8"	- 10	M 36x2	28	20,0	30,5	3,8			41
M21512-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	31,1	3,6			32
M21513-12-30	19	3/4"	- 12	M 30x2	22	15,0	28,2	3,6			36
M21513-12-36	19	3/4"	- 12	M 36x2	28	20,0	28,3	3,8			41
M21512-16-30	25	1"	- 16	M 30x2	22	15,0	34,0	3,6			36
M21513-16-36	25	1"	- 16	M 36x2	28	19,8	29,4	3,8			41
M21513-16-45	25	1"	- 16	M 45x2	35	26,0	39,0	5,1			50
M21512-20-36	31	1 1/4"	- 20	M 36x2	28	19,8	35,5	5,0			41
M21513-20-45	31	1 1/4"	- 20	M 45x2	35	26,0	32,9	5,1			50
M21513-20-52	31	1 1/4"	- 20	M 52x2	42	32,0	32,5	5,1			60
M21512-24-45	38	1 1/2"	- 24	M 45x2	35	26,0	42,5	5,8			50
M21513-24-52	38	1 1/2"	- 24	M 52x2	42	32,0	32,8	5,1			60

M21592

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY


DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)

90° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列

DIN 20066 / ISO 12151-2 (带止推金属螺母)

DKOL 90° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA 90° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO SPINATO)



M21593

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY


DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

90° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOL 90° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA 90° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
------------	-----------	--	--	--------	------	------------------	--	--	--	--	--

	DN	inch	Size	T	mm	B	A	C	E		H ₂
M21593-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	26,0	1,7	30,0		14
M21593-03-14	5	3/16"	- 03	M 14x1,5	8	4,0	29,0	1,7	31,5		17
M21592-04-12	6	1/4"	- 04	M 12x1,5	6	3,0	28,5	2,2	32,5		17
M21593-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	29,5	1,7	31,5		17
M21593-04-16	6	1/4"	- 04	M 16x1,5	10	6,0	29,5	2,1	32,0		19
M21593-04-18	6	1/4"	- 04	M 18x1,5	12	7,0	29,5	2,3	33,0		22
M21592-05-14	8	5/16"	- 05	M 14x1,5	8	4,0	31,0	1,7	33,0		17
M21593-05-16	8	5/16"	- 05	M 16x1,5	10	6,0	32,0	2,1	32,5		19
M21593-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	32,0	2,3	32,5		22
M21593-05-22	8	5/16"	- 05	M 22x1,5	15	9,3	36,0	2,3	35,0		27
M21592-06-16	10	3/8"	- 06	M 16x1,5	10	6,0	35,5	3,0	40,0		19
M21593-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	36,5	2,3	33,5		22
M21593-06-22	10	3/8"	- 06	M 22x1,5	15	9,3	36,5	2,3	35,0		27
M21592-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	44,0	2,9	48,0		22
M21593-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	45,0	2,3	39,5		27
M21593-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	45,0	2,5	40,0		32
M21592-10-22	16	5/8"	- 10	M 22x1,5	15	9,3	53,5	3,0	57,5		27
M21593-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	51,5	2,5	53,0		32
M21593-10-30	16	5/8"	- 10	M 30x2	22	15,0	51,5	3,6	54,0		36
M21592-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	61,5	3,6	63,0		32
M21593-12-30	19	3/4"	- 12	M 30x2	22	15,0	61,5	3,6	59,0		36
M21593-12-36	19	3/4"	- 12	M 36x2	28	19,8	61,5	3,8	61,0		41
M21592-16-30	25	1"	- 16	M 30x2	22	15,0	79,5	3,6	80,5		36
M21593-16-36	25	1"	- 16	M 36x2	28	19,8	76,5	3,8	69,5		41
M21592-16-45	25	1"	- 16	M 45x2	35	26,0	79,0	5,1	72,0		50
M21592-20-36	31	1.1/4"	- 20	M 36x2	28	19,8	93,5	5,0	92,0		41
M21593-20-45	31	1.1/4"	- 20	M 45x2	35	26,0	93,5	5,1	81,0		50
M21592-24-36	38	1.1/2"	- 24	M 36x2	28	19,8	97,0	5,0	68,0		41
M21593-24-52	38	1.1/2"	- 24	M 52x2	42	32,0	107,5	5,1	98,0		60

DIN STANDARD CONNECTIONS

M21542

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY

DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


45° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOL 45° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA 45° CONO 24° O-RING SERIE LEGGERA

DIN 20066 / ISO 12151-2 (DADO SPINATO)



M21543

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE LIGHT DUTY


DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

45° 公制内螺纹巨肘弯头 24° 锥带O型圈轻型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOL 45° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA 45° CONO 24° O-RING SERIE LEGGERA DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M21543-03-12	5	3/16"	- 03	M 12x1,5	6	3,0	35,0	1,7	16,0		14
M21542-04-12	6	1/4"	- 04	M 12x1,5	6	3,0	39,0	2,2	18,0		17
M21543-04-14	6	1/4"	- 04	M 14x1,5	8	4,0	38,0	1,7	16,5		17
M21543-04-16	6	1/4"	- 04	M 16x1,5	10	6,0	38,0	2,1	17,0		19
M21543-04-18	6	1/4"	- 04	M 18x1,5	12	7,0	38,5	2,3	17,5		22
M21543-05-16	8	5/16"	- 05	M 16x1,5	10	6,0	41,5	2,1	17,5		19
M21543-05-18	8	5/16"	- 05	M 18x1,5	12	7,0	41,5	2,3	17,0		22
M21542-06-16	10	3/8"	- 06	M 16x1,5	10	6,0	47,5	3,0	21,5		19
M21543-06-18	10	3/8"	- 06	M 18x1,5	12	7,0	43,5	2,3	16,5		22
M21543-06-22	10	3/8"	- 06	M 22x1,5	15	9,3	45,0	2,3	18,0		27
M21542-08-18	12	1/2"	- 08	M 18x1,5	12	7,0	56,5	2,9	25,0		22
M21543-08-22	12	1/2"	- 08	M 22x1,5	15	9,3	52,0	2,3	19,0		27
M21543-08-26	12	1/2"	- 08	M 26x1,5	18	12,5	52,5	2,5	19,5		32
M21542-10-22	16	5/8"	- 10	M 22x1,5	15	9,3	65,5	2,4	29,0		27
M21543-10-26	16	5/8"	- 10	M 26x1,5	18	12,5	62,0	2,5	26,5		32
M21542-12-26	19	3/4"	- 12	M 26x1,5	18	12,5	73,0	3,6	31,0		32
M21543-12-30	19	3/4"	- 12	M 30x2	22	15,0	71,0	3,6	28,5		36
M21543-12-36	19	3/4"	- 12	M 36x2	28	19,8	72,0	3,8	30,0		41
M21543-16-36	25	1"	- 16	M 36x2	28	19,8	85,0	3,8	32,0		41
M21542-20-36	31	1 1/4"	- 20	M 36x2	28	19,8	107,5	5,0	44,0		41
M21543-20-45	31	1 1/4"	- 20	M 45x2	35	26,0	99,5	5,1	36,0		50
M21542-24-36	38	1 1/2"	- 24	M 36x2	28	19,8	117,5	5,0	37,0		41
M21543-24-52	38	1 1/2"	- 24	M 52x2	42	32,0	117,0	5,1	44,5		60


M11210

METRIC MALE 24° CONE SEAT HEAVY DUTY - DIN 20066 / ISO 12151-2

公制外螺纹 24° - 锥形底座重型系列 DIN 20066 / ISO 12151-2

CES - DIN 20066 / ISO 12151-2

MASCHIO METRICO 24° - SERIE PESANTE DIN 20066 / ISO 12151-2



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C		H ₁	
M11210-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	25,5	12,0		17	
M11210-04-18	6	1/4"	- 04	M 18x1,5	10	6,0	26,5	12,0		19	
M11210-04-20	6	1/4"	- 04	M 20x1,5	12	7,0	29,0	12,0		22	
M11210-05-16	8	5/16"	- 05	M 16x1,5	8	5,5	26,0	12,0		17	
M11210-05-18	8	5/16"	- 05	M 18x1,5	10	7,0	26,5	12,0		19	
M11210-05-20	8	5/16"	- 05	M 20x1,5	12	7,0	29,0	12,0		22	
M11210-06-18	10	3/8"	- 06	M 18x1,5	10	7,0	27,1	12,0		19	
M11210-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	29,1	12,0		22	
M11210-06-22	10	3/8"	- 06	M 22x1,5	14	8,0	31,1	14,0		22	
M11210-08-22	12	1/2"	- 08	M 22x1,5	14	9,3	31,5	14,0		22	
M11210-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	31,6	14,0		24	
M11210-10-30	16	5/8"	- 10	M 30x2	20	15,0	35,7	16,0		30	
M11210-10-36	16	5/8"	- 10	M 36x2	25	19,8	40,0	18,0		36	
M11210-12-30	19	3/4"	- 12	M 30x2	20	15,0	37,0	16,0		30	
M11210-12-36	19	3/4"	- 12	M 36x2	25	19,8	41,0	18,0		36	
M11210-16-36	25	1"	- 16	M 36x2	25	19,8	42,3	18,0		36	
M11210-16-42	25	1"	- 16	M 42x2	30	25,0	44,3	20,0		46	
M11210-20-52	31	1 1/4"	- 20	M 52x2	38	30,0	50,5	22,0		55	

DIN STANDARD CONNECTIONS

M21612

METRIC O-RING FEMALE 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


公制内螺纹 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带止推金属螺母)

DKOS - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE PESANTE

DIN 20066 / ISO 12151-2 (DADO SPINATO)



M21613

METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)


公制内螺纹 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOS - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE PESANTE


DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm					
------------	-----------	--	--------	------	---------------	--	--	--	--	--

	DN	inch	Size	T	mm	B	A	C		H ₂
M21613-03-14	5	3/16"	- 03	M 14x1,5	6	2,5	25,5	3,5		17
M21613-03-16	5	3/16"	- 03	M 16x1,5	8	3,2	21,9	3,4		19
M21613-04-14	6	1/4"	- 04	M 14x1,5	6	3,0	23,5	3,5		17
M21613-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	22,2	3,4		19
M21613-04-18	6	1/4"	- 04	M 18x1,5	10	4,0	28,0	3,0		22
M21613-04-20	6	1/4"	04	M 20x1,5	12	7,0	25,7	2,5		24
M21613-05-18	8	5/16"	- 05	M 18x1,5	10	5,5	28,0	3,0		22
M21613-05-20	8	5/16"	- 05	M 20x1,5	12	5,5	24,8	2,5		24
M21613-06-18	10	3/8"	- 06	M 18x1,5	10	7,0	28,5	3,0		22
M21613-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	25,3	2,5		24
M21613-06-22	10	3/8"	- 06	M 22x1,5	14	7,0	32,6	3,0		27
M21613-06-24	10	3/8"	- 06	M 24x1,5	16	7,0	32,0	3,0		30
M21612-08-20	12	1/2"	- 08	M 20x1,5	12	7,0	29,0	2,5		24
M21612-08-22	12	1/2"	- 08	M 22x1,5	14	7,0	27,5	2,5		27
M21613-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	26,7	3,0		30
M21613-08-30	12	1/2"	- 08	M 30x2	20	12,5	37,0	3,5		36
M21612-10-24	16	5/8"	- 10	M 24x1,5	16	9,3	29,5	4,0		30
M21613-10-30	16	5/8"	- 10	M 30x2	20	12,5	30,6	3,5		36
M21613-10-36	16	5/8"	- 10	M 36x2	25	15,0	40,0	4,5		41
M21612-12-24	19	3/4"	- 12	M 24x1,5	16	9,3	30,5	4,0		30
M21612-12-30	19	3/4"	- 12	M 30x2	20	12,5	33,5	2,2		36
M21613-12-36	19	3/4"	- 12	M 36x2	25	15,0	34,1	4,5		41
M21612-16-30	25	1"	- 16	M 30x2	20	12,5	34,5	2,2		36
M21612-16-36	25	1"	- 16	M 36x2	25	15,0	35,3	1,7		41
M21613-16-42	25	1"	- 16	M 42x2	30	19,8	35,4	6,3		50
M21613-20-52	31	1 1/4"	- 20	M 52x2	38	26,0	37,5	8,0		60
M21613-24-52	38	1 1/2"	- 24	M 52x2	38	26,0	49,6	8,0		60

M21692



90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)

M21693



90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
------------	-----------	--	--	--------	------	------------------	--	--	--	--	--

	DN	inch	Size	T	mm	B	A	C	E		H ₂
M21693-03-14	5	3/16"	- 03	M 14x1,5	6	3,0	26,0	3,5	30,0		17
M21693-03-16	5	3/16"	- 03	M 16x1,5	8	3,0	26,0	3,4	29,5		19
M21693-04-14	6	1/4"	- 04	M 14x1,5	6	3,0	29,5	3,5	32,5		17
M21693-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	29,5	3,4	29,5		19
M21693-04-18	6	1/4"	- 04	M 18x1,5	10	4,0	29,5	3,0	31,0		22
M21693-04-20	6	1/4"	- 04	M 20x1,5	12	5,5	29,5	2,5	34,5		24
M21693-05-18	8	5/16"	- 05	M 18x1,5	10	4,0	32,0	3,0	33,5		22
M21693-05-20	8	5/16"	- 05	M 20x1,5	12	5,5	32,0	2,5	34,0		24
M21692-06-18	10	3/8"	- 06	M 18x1,5	10	4,0	35,5	3,9	42,5		22
M21693-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	36,5	2,5	35,0		24
M21693-06-22	10	3/8"	- 06	M 22x1,5	14	7,0	36,5	3,0	37,0		27
M21693-06-24	10	3/8"	- 06	M 24x1,5	16	9,3	36,5	3,0	36,0		30
M21692-08-22	12	1/2"	- 08	M 22x1,5	14	7,0	44,0	2,5	48,5		27
M21693-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	45,0	3,0	40,5		30
M21693-08-30	12	1/2"	- 08	M 30x2	20	12,5	45,0	3,5	44,5		36
M21692-10-24	16	5/8"	- 10	M 24x1,5	16	9,3	55,0	4,0	60,0		30
M21693-10-30	16	5/8"	- 10	M 30x2	20	12,5	51,5	3,5	57,5		36
M21692-12-30	19	3/4"	- 12	M 30x2	20	12,5	61,5	2,2	67,5		36
M21693-12-36	19	3/4"	- 12	M 36x2	25	15,0	61,5	4,5	64,5		41
M21692-16-36	25	1"	- 16	M 36x2	25	15,0	79,5	1,7	86,0		41
M21693-16-42	25	1"	- 16	M 42x2	30	19,8	79,0	6,3	74,5		50
M21693-20-52	31	1 1/4"	- 20	M 52x2	38	26,0	93,5	8,0	85,5		60
M21692-24-52	38	1 1/2"	- 24	M 52x2	38	24,7	91,5	8,8	95,5		60

DIN STANDARD CONNECTIONS

M21642

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE

DIN 20066 / ISO 12151-2 (DADO SPINATO)



M21643

45° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (SLIP-ON NUT)


45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)


DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE

DIN 20066 / ISO 12151-2 (DADO PASSANTE)




PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm						
	DN	inch				B	A	C	E		H ₂
M21643-04-14	6	1/4"	- 04	M 14x1,5	6	3,0	38,5	3,5	17,5		17
M21643-04-16	6	1/4"	- 04	M 16x1,5	8	4,0	36,0	3,4	15,0		19
M21643-04-18	6	1/4"	- 04	M 18x1,5	10	4,0	37,5	3,0	16,5		22
M21643-05-18	8	5/16"	- 05	M 18x1,5	10	4,0	42,5	3,0	18,0		22
M21643-05-20	8	5/16"	- 05	M 20x1,5	12	5,5	42,5	2,5	18,5		24
M21642-06-18	10	3/8"	- 06	M 18x1,5	10	4,0	49,0	3,9	23,0		22
M21643-06-20	10	3/8"	- 06	M 20x1,5	12	7,0	45,0	2,5	18,0		24
M21643-06-22	10	3/8"	- 06	M 22x1,5	14	7,0	46,5	3,0	19,5		27
M21642-08-22	12	1/2"	- 08	M 22x1,5	14	7,0	57,5	2,5	25,5		27
M21643-08-24	12	1/2"	- 08	M 24x1,5	16	9,3	52,5	3,0	20,0		30
M21643-10-30	16	5/8"	- 10	M 30x2	20	12,5	65,5	3,5	29,5		36
M21642-12-30	19	3/4"	- 12	M 30x2	20	12,5	76,5	2,2	34,0		36
M21643-12-36	19	3/4"	- 12	M 36x2	25	15,0	75,0	4,5	32,5		41
M21642-16-36	25	1"	- 16	M 36x2	25	15,0	98,0	1,7	43,5		41
M21643-16-42	25	1"	- 16	M 42x2	30	19,8	90,0	6,3	35,5		50
M21643-20-52	31	1 1/4"	- 20	M 52x2	38	26,0	103,0	8,0	39,5		60



M11710

FRENCH METRIC MALE 24° CONE SEAT MILLIMETRIC TYPE
 法国外螺纹 24° 锥形底座毫米公制型
 AGF 24° INNENKONUS (FR. REIHE MILL.)
 MASCHIO METRICO 24° SERIE MILLIMETRICA FRANCESE


PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C		H ₁	
M11710-10-2718	16	5/8"	- 10	M 27x1,5	18	12,5	28,7	14,0		28	
M11710-10-2720	16	5/8"	- 10	M 27x1,5	20	12,5	28,7	14,0		28	
M11710-12-30	19	3/4"	- 12	M 30x1,5	22	15,0	30,0	14,0		30	
M11710-12-33	19	3/4"	- 12	M 33x1,5	25	15,0	31,0	14,0		34	



M21713

FRENCH METRIC FEMALE MILLIMETRIC TYPE (SLIP-ON NUT)
 法国内螺纹毫米公制型 (滑套螺母)
 DKFM (FR. REIHE MILL., HINTERLEGTE MUTTER)
 FEMMINA METRICA SERIE MILLIMETRICA FRANCESE (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C			H ₂
M21713-10-2718	16	5/8"	- 10	M 27x1,5	18	12,5	22,2	5,1			32
M21713-10-2720	16	5/8"	- 10	M 27x1,5	20	12,5	22,2	5,1			32
M21713-12-30	19	3/4"	- 12	M 30x1,5	22	15,0	25,5	4,1			36
M21713-12-33	19	3/4"	- 12	M 33x1,5	25	15,0	25,5	4,1			38
M21713-16-36	25	1"	- 16	M 36x1,5	28	19,8	27,8	4,8			41
M21713-16-39	25	1"	- 16	M 39x1,5	30	19,8	28,3	4,3			46



M11810

FRENCH METRIC MALE 24° CONE SEAT GAZ TYPE
 法国外螺纹 24° 锥形底座 GAZ 型
 AGF 24° INNENKONUS (FR. REIHE GAS)
 MASCHIO METRICO 24° SERIE GAZ FRANCESE

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C		H ₁	
M11810-05-20	8	5/16"	- 05	M 20x1,5	13,25	8,0	27,0	12,0		22	
M11810-06-20	10	3/8"	- 06	M 20x1,5	13,25	8,0	27,6	12,0		22	
M11810-06-24	10	3/8"	- 06	M 24x1,5	16,75	12,0	28,1	12,0		24	
M11810-08-24	12	1/2"	- 08	M 24x1,5	16,75	12,0	28,4	12,0		24	
M11810-10-30	16	5/8"	- 10	M 30x1,5	21,25	15,0	31,7	14,0		30	
M11810-12-36	19	3/4"	- 12	M 36x1,5	26,75	21,0	34,0	14,0		36	
M11810-16-45	25	1"	- 16	M 45x1,5	33,50	26,0	39,3	16,0		46	

NF STANDARD CONNECTIONS


M21813

FRENCH METRIC FEMALE GAZ TYPE (SLIP-ON NUT)

法国内螺纹公制 GAZ 型 (滑套螺母)

DKF (FR. REIHE GAS, HINTERLEGTE MUTTER)

FEMMINA METRICA SERIE GAZ FRANCESE (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C			H ₂
M21813-04-20	6	1/4"	- 04	M 20x1,5	13,25	7,0	22,1	4,3			24
M21813-05-20	8	5/16"	- 05	M 20x1,5	13,25	7,0	22,1	4,3			24
M21813-06-20	10	3/8"	- 06	M 20x1,5	13,25	7,0	22,6	4,3			24
M21813-06-24	10	3/8"	- 06	M 24x1,5	16,75	9,3	25,6	4,0			30
M21813-08-24	12	1/2"	- 08	M 24x1,5	16,75	9,3	26,5	4,0			30
M21813-08-30	12	1/2"	- 08	M 30x1,5	21,25	12,5	23,6	5,1			36
M21813-10-30	16	5/8"	- 10	M 30x1,5	21,25	12,5	23,7	5,1			36
M21813-12-36	19	3/4"	- 12	M 36x1,5	26,75	15,0	27,0	4,8			41
M21813-16-45	25	1"	- 16	M 45x1,5	33,50	19,8	26,8	4,6			50


M21893

90° FRENCH METRIC FEMALE GAZ TYPE (SLIP-ON NUT)


90° 法国公制内螺纹 GAZ 型 (滑套螺母)

DKF 90° BOGEN (FR. REIHE MILL., HINTERLEGTE MUTTER)

FEMMINA METRICA 90° SERIE GAZ FRANCESE (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M21893-05-20	8	5/16"	- 05	M 20x1,5	13,25	7,0	32,0	4,3	29,5		24
M21893-06-20	10	3/8"	- 06	M 20x1,5	13,25	7,0	36,5	4,3	33,5		24
M21893-08-24	12	1/2"	- 08	M 24x1,5	16,75	12,0	45,0	4,0	41,0		30
M21893-10-30	16	5/8"	- 10	M 30x1,5	21,25	12,5	51,5	5,1	53,5		36
M21893-12-36	19	3/4"	- 12	M 36x1,5	26,75	15,0	61,5	4,8	60,0		41




M24011

JIS METRIC FEMALE 60° CONE SEAT (KOMATSU) JIS B 8363 (CRIMPED-BACK NUT)

JIS 公制内螺纹 60° 锥形底座 (小松标准) JIS B 8363 (扣压-支撑螺母)

DK KOMATSU MIT 60° KONUS (NACH JIS B 8363, PRESSMUTTER)

FEMMINA METRICA GIAPPONESE CONO 60° TIPO KOMATSU JIS B 8363 (DADO PRESSATO)



M24012

JIS METRIC FEMALE 60° CONE SEAT (KOMATSU) JIS B 8363 (THRUST-WIRE NUT)

JIS 公制内螺纹 60° 锥形底座 (小松标准) JIS B 8363 (带止推金属丝螺母)

DK KOMATSU MIT 60° KONUS (NACH JIS B 8363, GESTIFTETE MUTTER)

FEMMINA METRICA GIAPPONESE CONO 60° TIPO KOMATSU JIS B 8363 (DADO SPINATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm						
	DN	inch	Size	T	B	A	C		H ₁	H ₂	
M24011-04-14	6	1/4"	- 04	M 14x1,5	4,0	23,0	10,5		19	19	
M24011-04-18	6	1/4"	- 04	M 18x1,5	4,0	22,6	11,5		24	24	
M24011-05-16	8	5/16"	- 05	M 16x1,5	5,5	22,5	9,3		21	21	
M24011-06-14	10	3/8"	- 06	M 14x1,5	4,0	23,6	10,5		19	19	
M24011-06-18	10	3/8"	- 06	M 18x1,5	7,0	23,6	11,5		24	24	
M24011-08-22	12	1/2"	- 08	M 22x1,5	9,3	24,9	14,0		27	27	
M24011-10-24	16	5/8"	- 10	M 24x1,5	12,5	26,7	15,1		32	32	
M24011-12-30	19	3/4"	- 12	M 30x1,5	15,0	31,5	18,3		36	36	
M24011-16-33	25	1"	- 16	M 33x1,5	19,8	33,3	21,3		41	41	
M24011-20-36	31	1.1/4"	- 20	M 36x1,5	19,8	41,0	20,0		46	46	
M24012-24-42	38	1.1/2"	- 24	M 42x1,5	26,0	44,0	18,8		55	55	

JIS STANDARD CONNECTIONS


M23811

JIS BSP FEMALE 60° CONE SEAT (TOYOTA) - JIS B 8363 (CRIMPED-BACK NUT)

JIS BSP 英制内螺纹 60° 锥形底座 (丰田标准) - JIS B 8363 (带扣压-支撑螺母)

DK TOYOTA MIT 60° KONUS MIT KONTERSECHSKANT (NACH JIS B 8363, PRESSMUTTER)

FEMMINA GAS GIAPPONESE CONO 60° TIPO TOYOTA JIS B 8363 (DADO PRESSATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M23811-04-04	6	1/4"	- 04	1/4" - 19	4,0	18,5	8,3		19	19
M23811-06-06	10	3/8"	- 06	3/8" - 19	7,0	23,1	10,0		22	22
M23811-08-08	12	1/2"	- 08	1/2" - 14	9,3	23,0	11,5		27	27
M23811-12-12	19	3/4"	- 12	3/4" - 14	15,0	26,0	13,5		32	32
M23811-16-16	25	1"	- 16	1" - 11	19,8	30,3	14,5		38	38


M20711

JIS BSP FEMALE 60° CONE (NISSAN) - JIS B 8363 (CRIMPED-BACK NUT)

JIS BSP 英制内螺纹 60° 锥 (尼桑标准) - JIS B 8363 (带扣压-支撑螺母)

DK NISSAN MIT 60° KONUS MIT KONTERSECHSKANT (NACH JIS B 8363, PRESSMUTTER)

FEMMINA GIAPPONESE CONO 60° TIPO NISSAN JIS B 8363 (DADO PRESSATO)




M20712

JIS BSP FEMALE 60° CONE (NISSAN) - JIS B 8363 (THRUST-WIRE NUT)


JIS BSP 英制内螺纹 60° 锥 (尼桑标准) - JIS 8363 (带止推金属丝螺母)

DK NISSAN MIT 60° KONUS MIT KONTERSECHSKANT (NACH JIS B 8363, GESTIFTETE MUTTER)

FEMMINA GIAPPONESE CONO 60° TIPO NISSAN JIS B 8363 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M20711-04-04	6	1/4"	- 04	1/4" - 19	4,0	22,5	4,5		19	19
M20711-06-06	10	3/8"	- 06	3/8" - 19	7,0	24,6	6,4		22	22
M20711-08-08	12	1/2"	- 08	1/2" - 14	9,3	26,4	6,7		27	27
M20712-10-08	16	5/8"	- 10	1/2" - 14	9,3	28,8	6,5		27	27
M20712-10-12	16	5/8"	- 10	3/4" - 14	15,0	30,7	9,0		32	32
M20711-12-12	19	3/4"	- 12	3/4" - 14	15,0	30,0	8,9		32	32
M20712-16-16	25	1"	- 16	1" - 11	19,8	35,5	10,5		38	38



M24111


STRAIGHT KOMATSU FLANGE

小松直式法兰

FLANSCH GERADE KOMATSU

FLANGIA DITTA SERIE KOMATSU

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				
	DN	inch	Size		B	A	D		
M24111-08-10	12	1/2"	- 08	5/8"	14,0	66,0	34,0		
M24111-10-10	16	5/8"	- 10	5/8"	14,0	65,7	34,0		
M24111-12-10	19	3/4"	- 12	5/8"	14,0	66,5	34,0		



M24191


90° KOMATSU FLANGE

90° 度小松法兰

FLANSCH 90° BOGEN KOMATSU

FLANGIA 90° SERIE KOMATSU

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				
	DN	inch	Size		B	A	C	E	
M24191-10-10	16	5/8"	- 10	5/8"	14,0	56,0	34,0	47,5	
M24191-12-10	19	3/4"	- 12	5/8"	14,0	56,0	34,0	47,5	



M24141

45° KOMATSU FLANGE

45° 度小松法兰

FLANSCH 45° BOGEN KOMATSU

FLANGIA 45° SERIE KOMATSU

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				
	DN	inch	Size		B	A	C	E	
M24141-10-10	16	5/8"	- 10	5/8"	14,0	61,0	34,0	22,0	


M23911

STRAIGHT SUPERCAT FLANGE

山猫直式法兰

FLANSCH GERADE SUPERCAT

FLANGIA DITTA SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	S		
M23911-12-12	19	3/4"	- 12	3/4"	15,0	74,5	41,5	14,3		
M23911-16-16	25	1"	- 16	1"	19,8	86,8	47,7	14,3		
M23911-16-20	25	1"	- 16	1.1/4"	26,0	92,3	54,0	14,3		
M23911-20-20	31	1.1/4"	- 20	1.1/4"	26,0	86,0	54,0	14,3		
M23911-24-24	38	1.1/2"	- 24	1.1/2"	32,0	94,0	63,6	14,3		


M23991

90° SUPERCAT FLANGE

90° 度山猫法兰

FLANSCH 90° BOGEN SUPERCAT

FLANGIA 90° SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M23991-12-12	19	3/4"	- 12	3/4"	15,0	64,5	41,5	64,5	14,3	
M23991-16-16	25	1"	- 16	1"	19,8	77,5	47,7	76,5	14,3	
M23991-16-20	25	1"	- 16	1.1/4"	26,0	75,5	54,0	80,5	14,3	
M23991-20-20	31	1.1/4"	- 20	1.1/4"	26,0	85,5	54,0	87,0	14,3	


M23941

45° SUPERCAT FLANGE


45° 度山猫法兰

FLANSCH 45° BOGEN SUPERCAT

FLANGIA 45° SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M23941-12-12	19	3/4"	- 12	3/4"	15,0	77,0	41,5	32,0	14,3	
M23941-16-16	25	1"	- 16	1"	19,8	89,5	47,7	36,5	14,3	
M23941-16-20	25	1"	- 16	1.1/4"	26,0	92,5	54,0	40,5	14,3	
M23941-20-20	31	1.1/4"	- 20	1.1/4"	26,0	99,0	54,0	41,5	14,3	



O20310


BSP BANJO

BSP 绞接式接头

RINGNIPPEL, ZÖLLIG (BSP GEWINDE)

OCCHIELLO GAS

PART. REF.	HOSE BORE			BSP BOLT	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	K	
O20310-04-04	6	1/4"	- 04	1/4" - 19	4,1	22	13,3	14,0	24,0	
O20310-04-06	6	1/4"	- 04	3/8" - 19	4,1	21	16,7	18,0	28,0	
O20310-05-04	8	5/16"	- 05	1/4" - 19	5,1	22	13,3	14,0	24,0	
O20310-05-06	8	5/16"	- 05	3/8" - 19	5,1	23	16,7	18,0	28,0	
O20310-06-06	10	3/8"	- 06	3/8" - 19	7,1	24,1	16,7	18,0	28,0	
O20310-06-08	10	3/8"	- 06	1/2" - 14	7,1	27,1	21,2	22,0	35,0	
O20310-08-08	12	1/2"	- 08	1/2" - 14	9,6	27,5	21,2	22,0	35,0	
O20310-10-10	16	5/8"	- 10	5/8" - 14	12,1	28,2	23,0	23,5	38,0	
O20310-12-12	19	3/4"	- 12	3/4" - 14	15,0	36,5	26,7	29,0	45,0	
O20310-16-16	25	1"	- 16	1" - 11	20,0	44,5	33,4	36,0	54,0	



O20910

METRIC BANJO - DIN 7642

公制绞接式 - DIN 7642

RINGNIPPEL, METRISCH - DIN 7642

OCCHIELLO METRICO - DIN 7642

PART. REF.	HOSE BORE			MATRIC BOLT	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	K	
O20910-04-12	6	1/4"	- 04	M12 x 1,5	4,1	21	12,0	12,0	20,0	
O20910-04-14	6	1/4"	- 04	M14 x 1,5	4,1	21,5	14,0	14,0	24,0	
O20910-05-14	8	5/16"	- 05	M14 x 1,5	5,1	23,1	14,0	14,0	24,0	
O20910-06-14	10	3/8"	- 06	M14 x 1,5	7,1	24,1	14,0	14,0	24,0	
O20910-06-16	10	3/8"	- 06	M16 x 1,5	7,1	24,1	16,0	18,0	28,0	
O20910-06-18	10	3/8"	- 06	M18 x 1,5	7,1	27,1	18,0	20,0	32,0	
O20910-08-18	12	1/2"	- 08	M18 x 1,5	9,6	27,5	18,0	20,0	32,0	
O20910-08-22	12	1/2"	- 08	M22 x 1,5	9,6	27,5	22,0	22,0	35,0	
O20910-10-22	16	5/8"	- 10	M22 x 1,5	12,1	28,2	22,0	23,5	38,0	
O20910-12-26	19	3/4"	- 12	M26 x 1,5	15,0	36,5	26,0	29,0	45,0	

ACCESSORIES


M..IP

BRAZING TAIL


铜焊接头插芯

EINLÖTNIPPEL

INSERTO A SALDARE



PART. REF.	HOSE BORE			DIMENSIONS mm						
	DN	inch	Size		B	A	C	D		
M03IP06	5	3/16"	- 03		6,0	11,5	5,0	10,0		
M04IP08	6	1/4"	- 04		8,0	13,0	5,0	12,0		
M05IP10	8	5/16"	- 05		10,0	13,5	6,0	14,0		
M06IP12	10	3/8"	- 06		12,0	13,5	6,0	16,0		
M06IP14	10	3/8"	- 06		14,0	13,5	6,0	18,0		
M08IP15	12	1/2"	- 08		15,0	14,0	6,0	20,0		
M08IP16	12	1/2"	- 08		16,0	14,0	6,0	20,0		
M10IP18	16	5/8"	- 10		18,0	15,0	7,0	23,0		
M12IP22	19	3/4"	- 12		22,0	16,0	7,0	26,0		
M16IP28	25	1"	- 16		28,0	18,5	8,0	34,0		
M20IP35	31	1.1/4"	- 20		35,0	21,5	9,0	40,0		
M24IP40	38	1.1/2"	- 24		40,0	21,5	9,0	50,0		
M32IP50	51	2"	- 32		50,0	23,0	10,0	60,0		
M40IP60	63	2.1/2"	- 40		60,0	22,0	10,0	73,0		
M48IP70	76	3"	- 48		70,0	38,0	10,0	89,0		



M10050

DOUBLE CONNECTOR

双插芯接头

SCHLAUCHVERBINDER - DOPPELNIPPEL

DOPPIO INSERTO

PART. REF.	HOSE BORE			DIMENSIONS mm						
	DN	inch	Size		B	A	C			
M10050-03-03	5	3/16"	- 03		3,0	15,5	58,5			
M10050-04-04	6	1/4"	- 04		4,0	14,0	69,0			
M10050-05-05	8	5/16"	- 05		5,5	14,0	70,0			
M10050-06-06	10	3/8"	- 06		7,0	14,7	73,5			
M10050-08-08	12	1/2"	- 08		9,3	15,8	78,0			
M10050-10-10	16	5/8"	- 10		12,5	15,4	84,0			
M10050-12-12	19	3/4"	- 12		15,0	18,5	91,5			
M10050-16-16	25	1"	- 16		19,8	22,6	119,0			
M10050-20-20	31	1.1/4"	- 20		26,0	23,0	128,0			
M10050-24-24	38	1.1/2"	- 24		32,0	23,5	147,5			

ACCESSORIES


O80210

BSP BOLT

BSP 螺栓

HOHLSCHRAUBE ZÖLLIG

VITE GAS FORATA



PART. REF.	HOSE BORE			DIMENSIONS mm						
				T	B	A	C		H ₁	
O80210-04				1/4" - 19	7,0	32,0	25,0		17	
O80210-06				3/8" - 19	9,0	38,0	31,0		22	
O80210-08				1/2" - 14	13,0	46,0	38,0		27	
O80210-10				5/8" - 14	13,5	49,0	41,0		30	
O80210-12				3/4" - 14	17,0	56,0	46,0		32	
O80210-16				1" - 11	22,0	69,0	58,0		41	


O80810

METRIC BOLT - DIN 7643

公制螺栓 - DIN 7643

HOHLSCHRAUBE - METRISCH - DIN 7643

VITE METRICA FORATA - DIN 7643



PART. REF.	HOSE BORE			DIMENSIONS mm						
				T	B	A	C		H ₁	
O80810-12				M12 x 1,5	6,0	28,0	23,0		17	
O80810-14				M14 x 1,5	8,0	32,0	25,0		19	
O80810-16				M16 x 1,5	9,0	38,0	31,0		22	
O80810-18				M18 x 1,5	11,0	44,0	36,0		24	
O80810-22				M22 x 1,5	13,0	46,0	38,0		27	
O80810-26				M26 x 1,5	17,0	56,0	46,0		32	


M01500

DOUBLE SKIVE FERRULE FOR HEAVY DUTY SPIRAL HOSES (4 PLY)

重型缠绕软管 (4层) 双面剥胶套筒

PRESSFASSUNG INNEN- UND AUSSENSCHÄLUNG FÜR HÖCHSTDRUCKSCHLÄUCHE (4-LAGIG)

GHIERA PER TUBI SPIRALATI CON DOPPIA PELATURA (4 SPIRALI)



PART. REF.	HOSE BORE			DIMENSIONS mm					
	DN	inch	Size		D	L			
M01500-10	16	5/8"	- 10		35,0	40,9			
M01500-12	19	3/4"	- 12		40,0	51,4			
M01500-16	25	1"	- 16		48,0	64,5			
M01500-20	31	1.1/4"	- 20		57,0	84,0			
M01500-24	38	1.1/2"	- 24		64,3	94,0			
M01500-32	51	2"	- 32		83,5	107,0			


M01600

DOUBLE SKIVE FERRULE FOR HEAVY DUTY SPIRAL HOSES (6 PLY)

重型缠绕软管 (6层) 双面剥胶套筒

PRESSFASSUNG INNEN- UND AUSSENSCHÄLUNG FÜR HÖCHSTDRUCKSCHLÄUCHE (6-LAGIG)

GHIERA PER TUBI SPIRALATI CON DOPPIA PELATURA (6 SPIRALI)



PART. REF.	HOSE BORE			DIMENSIONS mm					
	DN	inch	Size		D	L			
M01600-20	31	1.1/4"	- 20		60,0	85,0			
M01600-24	38	1.1/2"	- 24		68,0	96,0			

M01800


DOUBLE SKIVE FERRULE FOR EXTRA DUTY SPIRAL HOSES (6 PLY)

超重型缠绕软管 (六层) 双面剥胶套筒

PRESSFASSUNG FÜR INNEN- UND AUSSENSCHÄLUNG FÜR SPEZIAL-SPIRALSCHLÄUCHE (6-LAGIG)

GHIERA A PELATURA INTERNA/ESTERNA PER TUBI SPIRALATI

(6 SPIRALI) PER APPLICAZIONI ESTREMAMENTE SEVERE



PART. REF.	HOSE BORE			DIMENSIONS mm					
	DN	inch	Size		D	L			
M01800-20	31	1.1/4"	- 20		64,5	88,2			
M01800-32	51	2"	- 32		86,5	108,0			

INTERLOCK PLUS TYPE



BS STANDARD CONNECTIONS


M30510

BSP MALE PARALLEL 60° CONE SEAT - BS5200 / ISO 8434-6

BSP 平行外螺纹 (60° 锥形底座) - BS5200 / ISO 8434-6

AGR 60° INNENKONUS - BS5200/ISO 8464-6

MASCHIO GAS CILINDRICO CONO 60° - BS5200 / ISO 8434-6



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M30510-12-12	19	3/4"	- 12	3/4" - 14	17,0	36,9	16,0		32	
M30510-12-16	19	3/4"	- 12	1" - 11	22,5	43,0	19,0		41	
M30510-16-16	25	1"	- 16	1" - 11	22,5	42,8	19,0		41	
M30510-16-20	25	1"	- 16	1.1/4" - 11	29,0	47,5	20,0		50	
M30510-20-20	31	1.1/4"	- 20	1.1/4" - 11	28,5	50,5	20,0		50	
M30510-24-24	38	1.1/2"	- 24	1.1/2" - 11	33,5	54,4	22,0		55	
M30510-32-32	51	2"	- 32	2" - 11	42,0	57,8	25,0		70	


M40812

BSP O-RING FEMALE 60° CONE - BS5200 / ISO 12151-6 (THRUST-WIRE NUT)

BSP O-RING 型圈内螺纹 (60° 锥) - BS5200 / ISO 12151-6 (带止推金属丝螺母)


DKOR 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER)

FEMMINA GAS CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M40812-12-12	19	3/4"	- 12	3/4" - 14	14,5	38,8	8,5		32	32
M40812-12-16	19	3/4"	- 12	1" - 11	19,0	40,0	10,6		32	41
M40812-16-12	25	1"	- 16	3/4" - 14	15,0	40,0	8,5		38	32
M40812-16-16	25	1"	- 16	1" - 11	19,5	44,4	10,6		41	41
M40812-16-20	25	1"	- 16	1.1/4" - 11	26,0	43,5	10,1		41	50
M40812-20-16	31	1.1/4"	- 20	1" - 11	19,0	50,0	10,6		50	41
M40812-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	52,4	10,1		50	50
M40812-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	51,5	12,5		50	60
M40812-24-20	38	1.1/2"	- 24	1.1/4" - 11	26,0	52,5	10,1		60	50
M40812-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	51,3	12,5		60	60
M40812-32-32	51	2"	- 32	2" - 11	42,0	51,6	16,1		70	70


M40892



90° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 90° O型圈 BSP 内螺纹巨肘弯头 (60° 锥)
 BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 90° BOGEN 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER)
 FEMMINA GAS 90° CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M40892-12-12	19	3/4"	- 12	3/4" - 14	14,5	72,4	8,5	70,0		32
M40892-12-16	19	3/4"	- 12	1" - 11	19,0	72,0	10,6	71,0		41
M40892-16-16	25	1"	- 16	1" - 11	19,5	82,2	10,6	80,5		41
M40892-16-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	95,0	10,1	78,5		50
M40892-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	98,5	10,1	98,0		50
M40892-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	111,5	12,5	109,0		60
M40892-32-32	51	2"	- 32	2" - 11	42,0	143,2	16,1	140,5		70

M40842



45° BSP O-RING FEMALE SWEPT ELBOW 60° CONE BS5200 / ISO 12151-6 (THRUST-WIRE NUT)
 45° O型圈 BSP 内螺纹巨肘弯头 (60° 锥)
 BS5200 / ISO 12151-6 (带止推金属丝螺母)
 DKOR 45° BOGEN 60° KONUS MIT O-RING - BS5200 / ISO 12151-6 (STIFTMUTTER)
 FEMMINA GAS 45° CONO 60° O-RING - BS5200 / ISO 12151-6 (DADO SPINATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M40842-12-12	19	3/4"	- 12	3/4" - 14	14,5	88,0	8,5	35,0		32
M40842-12-16	19	3/4"	- 12	1" - 11	19,0	89,5	10,6	36,5		41
M40842-16-12	25	1"	- 16	3/4" - 14	15,0	105,5	8,5	36,0		32
M40842-16-16	25	1"	- 16	1" - 11	19,5	97,0	10,6	40,0		41
M40842-16-20	25	1"	- 16	1.1/4" - 11	26,0	108,5	10,1	38,0		50
M40842-20-16	31	1.1/4"	- 20	1"-11	19,0	118,0	10,6	47,5		41
M40842-20-20	31	1.1/4"	- 20	1.1/4" - 11	25,0	120,0	10,1	49,5		50
M40842-20-24	31	1.1/4"	- 20	1.1/2" - 11	32,0	114,5	12,5	40,0		60
M40842-24-24	38	1.1/2"	- 24	1.1/2" - 11	32,0	126,5	12,5	50,0		60
M40842-32-32	51	2"	- 32	2" - 11	42,0	162,6	16,1	66,5		70

INTERLOCK PLUS TYPE



SAE STANDARD CONNECTIONS


M32810

NPTF MALE 60° CONE SEAT - SAE J516/J514

NPTF 外螺纹 60° 锥形底座 - SAE J516/J514

AGN 60° INNENKONUS (NPTF-GEWINDE) - SAE J516/J514

MASCHIO NPTF CONO 60° - SAE J516/J514



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
M32810-12-12	19	3/4"	- 12	3/4" - 14	16,0	42,9	19,2		32	
M32810-16-16	25	1"	- 16	1" - 11,5	19,5	49,3	24,2		41	
M32810-20-20	31	1.1/4"	- 20	1.1/4" - 11,5	26,0	61,0	25,0		46	
M32810-24-24	38	1.1/2"	- 24	1.1/2" - 11,5	32,0	62,6	26,0		50	
M32810-32-32	51	2"	- 32	2" - 11,5	42,0	66,8	26,5		70	


M42512

JIC FEMALE 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)


JIC 内螺纹 37° 锥形底座 - SAE J516 / ISO 12151-5 (带止推金属丝螺母)

JDJ 37° KONUS - SAE J516 / ISO 12151-5 (KONTERSECHSKANT UND STIFTMUTTER)

FEMMINA JIC CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M42512-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	36,2	14,2		32	32
M42512-12-16	19	3/4"	- 16	1.5/16" - 12	21,7	33,0	15,2		41	41
M42512-16-16	25	1"	- 16	1.5/16" - 12	21,7	40,7	15,2		41	41
M42512-16-20	25	1"	- 16	1.5/8" - 12	26,0	50,0	16,2		50	50
M42512-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	51,4	16,2		50	50
M42512-20-24	31	1.1/4"	- 20	1.7/8" - 12	30,5	54,0	18,8		55	60
M42512-24-24	38	1.1/2"	- 24	1.7/8" - 12	31,0	54,5	18,8		55	60
M42512-32-32	51	2"	- 32	2.1/2" - 12	42,0	54,2	24,0		70	75




M42592

90° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 90° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母)
 JDKJ 90° BOGEN, 37° KONUS - SAE J516 / ISO 12151-5 (STIFTMUTTER)
 FEMMINA JIC 90° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
------------	-----------	--	--	--------	------------------	--	--	--	--	--

	DN	inch	Size	T	B	A	C	E		H ₂
M42592-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	72,4	14,2	66,0		32
M42592-12-16	19	3/4"	- 12	1.5/16" - 12	21,7	72,5	15,2	71,5		41
M42592-16-16	25	1"	- 16	1.5/16" - 12	21,7	82,3	15,2	77,5		41
M42592-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	98,5	16,2	92,0		50
M42592-20-24	31	1.1/4"	- 20	1.7/8" - 12	32,0	101,5	18,8	108,0		60
M42592-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	115,5	18,8	106,0		60
M42592-32-32	51	2"	- 32	2.1/2" - 12	42,0	144,7	24,0	137,0		75



M42542

45° JIC FEMALE SWEPT ELBOW 37° CONE SEAT - SAE J516 / ISO 12151-5 (THRUST-WIRE NUT)
 45° JIC 内螺纹巨肘弯头 (37° 锥形底座) - SAE J516 / ISO 12151-5 (带止推金属丝螺母)
 DKJ 45° BOGEN 37° KONUS - SAE J516 / ISO 12151-5 (STIFTMUTTER)
 FEMMINA JIC 45° CONO 37° - SAE J516 / ISO 12151-5 (DADO SPINATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
------------	-----------	--	--	--------	------------------	--	--	--	--	--

	DN	inch	Size	T	B	A	C	E		H ₂
M42542-12-12	19	3/4"	- 12	1.1/16" - 12	15,0	86,0	14,2	33,0		32
M42542-16-16	25	1"	- 16	1.5/16" - 12	21,7	95,0	15,2	37,0		41
M42542-20-20	31	1.1/4"	- 20	1.5/8" - 12	26,0	115,5	16,2	45,0		50
M42542-24-24	38	1.1/2"	- 24	1.7/8" - 12	32,0	126,5	18,8	50,0		60
M42542-32-32	51	2"	- 32	2.1/2" - 12	42,0	161,0	24,0	63,5		75

INTERLOCK PLUS TYPE



SAE STANDARD CONNECTIONS


M42411

ORFS FEMALE - SAE J516 / ISO 12151-1 PULLBACK TYPE (CRIMPED BACK-NUT)

ORFS 内螺纹 - SAE J516 / ISO 12151-1 回拉式 (带扣压-支撑螺母)

ORFS IG - SAE J516 / ISO 12151-1 RÜCKZUGSAUSFÜHRUNG (VERPRESSTE MUTTER)

FEMMINA ORFS - SAE J516 / ISO 12151-1 VERSIONE RETRAIBILE (DADO PRESSATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M42411-10-10	16	5/8"	- 10	1" - 14	11,5	39,5	13,5		24	30
M42411-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	45,9	14,5		32	36
M42411-12-16	19	3/4"	- 12	1.7/16" - 12	19,0	46,5	15,0		36	41
M42411-16-12	25	1"	- 16	1.3/16" - 12	14,5	47,5	14,5		38	36
M42411-16-16	25	1"	- 16	1.7/16" - 12	19,5	48,5	15,0		41	41
M42411-16-20	25	1"	- 16	1.11/16" - 12	24,0	48,5	14,8		41	50
M42411-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	54,8	14,8		50	50
M42411-24-24	38	1.1/2"	- 24	2" - 12	31,0	57,8	15,8		60	60


M42412

ORFS FEMALE - SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE NUT)


ORFS 内螺纹 - SAE J516 / ISO 12151-1 重型 (带止推金属丝螺母)

ORFS MUTTER GESTIFTET - SAE J516 / ISO 12151-1 SCHWERE REIHE (THRUST-WIRE NUT)

FEMMINA ORFS - SAE J516 / ISO 12151-1 SERIE PESANTE (DADO SPINATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	H ₂
M42412-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	37,0	14,0		32	36
M42412-16-16	25	1"	- 16	1.7/16" - 12	19,5	42,0	15,0		41	46
M42412-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	52,0	15,0		50	55
M42412-24-24	38	1.1/2"	- 24	2" - 12	31,0	55,0	15,0		60	60



M42491


90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT)

90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母)

90° ORFS BOGEN (VERPRESSTE MUTTER) - SAE J516 / ISO 12151-1

FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 (DADO PRESSATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M42491-10-12	16	5/8"	- 10	1.3/16" - 12	14,5	51,0	14,5	47,0		36
M42491-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	65,5	14,5	48,0		36
M42491-12-12109	19	3/4"	- 12	1.3/16" - 12	14,5	65,5	14,5	109,0		36
M42491-12-16	19	3/4"	- 12	1.7/16" - 12	19,5	70,5	15,0	53,0		41
M42491-16-16	25	1"	- 16	1.7/16" - 12	19,5	85,0	15,0	54,0		41
M42491-16-16128	25	1"	- 16	1.7/16" - 12	19,5	85,0	15,0	128,0		41
M42491-16-20	25	1"	- 16	1.11/16" - 12	24,0	85,0	14,8	58,0		50
M42491-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	98,5	14,8	65,0		50
M42491-24-24	38	1.1/2"	- 24	2" - 12	31,0	115,7	15,8	79,5		60



M42492

90° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE-NUT)

90° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 重型 (带止推金属丝螺母)

90° ORFS BOGEN - SCHWERE REIHE SAE J516 / ISO 12151-1 (GESHTFETE MUTTER)

FEMMINA ORFS 90° - SAE J516 / ISO 12151-1 SERIE PESANTE (DADO SPINATO)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M42492-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	72,5	14,0	70,5		36
M42492-16-16	25	1"	- 12	1.7/16" - 12	19,5	82,5	15,0	84,5		46
M42492-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	98,5	15,0	98,0		55
M42492-24-24	38	1.1/2"	- 24	2" - 12	31,0	111,5	15,0	109,0		60

INTERLOCK PLUS TYPE



SAE STANDARD CONNECTIONS


M42441

45° ORFS FEMALE SWEPT ELBOW - SAE J516 / ISO 12151-1 (CRIMPED BACK-NUT)

45° ORFS 内螺纹巨肘弯头 - SAE J516 / ISO 12151-1 (带扣压-支撑螺母)

DK ORFS 45° - SAE J516 / ISO 12151-1 (PRESSMUTTER)

FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 (DADO PRESSATO)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
M42441-10-12	16	5/8"	- 10	1.3/16" - 12	14,5	55,5	14,5	21,5		36
M42441-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	69,0	14,5	21,5		36
M42441-12-16	19	3/4"	- 12	1.7/16" - 12	19,0	77,5	15,0	25,0		41
M42441-16-16	25	1"	- 16	1.7/16" - 12	19,5	84,0	15,0	22,0		41
M42441-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	96,5	14,8	26,0		50
M42441-24-24	38	1.1/2"	- 24	2" - 12	31,0	112,0	15,8	31,5		60

M42442

45° ORFS FEMALE SWEPT ELBOW


SAE J516 / ISO 12151-1 HEAVY TYPE (THRUST-WIRE-NUT)

45° ORFS 内螺纹巨肘弯头

SAE J516 / ISO 12151-1 重型 (带止推金属丝螺母)


45° ORFS BOGEN (GESCHFTETE MUTTER) - SAE J516 / ISO 12151-1

FEMMINA ORFS 45° - SAE J516 / ISO 12151-1 SERIE PESANTE (DADO SPINATO)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	C	E		H ₂
M42442-12-12	19	3/4"	- 12	1.3/16" - 12	14,5	89,0	14,0	36,0		36
M42442-16-16	25	1"	- 16	1.7/16" - 12	19,5	100,0	15,0	42,5		46
M42442-20-20	31	1.1/4"	- 20	1.11/16" - 12	25,0	119,5	15,0	49,5		55
M42442-24-24	38	1.1/2"	- 24	2" - 12	31,0	128,5	15,0	52,0		60

M43310




ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

SAE FLANSCH GERADE - SAE J516 / ISO 12151-3

FLANGIA ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D			
M43310-10-16	16	5/8"	- 10	1"	20,0	63,5	44,6			
M43310-12-12	19	3/4"	- 12	3/4"	16,0	59,9	38,0			
M43310-12-16	19	3/4"	- 12	1"	20,0	65,7	44,6			
M43310-16-12	25	1"	- 16	3/4"	16,0	67,0	38,0			
M43310-16-16	25	1"	- 16	1"	20,0	66,7	44,6			
M43310-16-20	25	1"	- 16	1.1/4"	26,0	73,0	51,0			
M43310-20-20	31	1.1/4"	- 20	1.1/4"	26,0	75,0	51,0			
M43310-20-24	31	1.1/4"	- 20	1.1/2"	32,0	80,0	60,5			
M43310-24-24	38	1.1/2"	- 24	1.1/2"	32,0	80,6	60,5			
M43310-24-32	38	1.1/2"	- 24	2"	42,0	88,3	71,6			
M43310-32-32	51	2"	- 32	2"	42,0	82,8	71,6			



M43390

90° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

SAE FLANSCH 90° BOGEN - SAE J516 / ISO 12151-3

FLANGIA 90° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M43390-10-16	16	5/8"	- 10	1"	20,0	70,5	44,6	52,0		
M43390-12-12	19	3/4"	- 12	3/4"	16,0	71,8	38,0	52,0		
M43390-12-16	19	3/4"	- 12	1"	20,0	72,4	44,6	52,0		
M43390-16-16	25	1"	- 16	1"	20,0	83,4	44,6	62,0		
M43390-16-20	25	1"	- 16	1.1/4"	26,0	83,4	51,0	62,0		
M43390-20-16	31	1.1/4"	- 20	1"	19,8	96,5	44,6	66,0		
M43390-20-20	31	1.1/4"	- 20	1.1/4"	26,0	99,0	51,0	70,0		
M43390-20-24	31	1.1/4"	- 20	1.1/2"	32,0	98,7	60,5	72,0		
M43390-24-24	38	1.1/2"	- 24	1.1/2"	32,0	111,6	60,5	84,0		
M43390-24-32	38	1.1/2"	- 24	2"	42,0	111,5	71,6	84,0		
M43390-32-32	51	2"	- 32	2"	42,0	133,7	71,6	99,0		

INTERLOCK PLUS TYPE



SAE STANDARD CONNECTIONS


M43340

45° ISO/SAE CODE 61 FLANGE - SAE J516 / ISO 12151-3

45° ISO/SAE CODE 61 法兰 - SAE J516 / ISO 12151-3

SAE FLANSCH 45° BOGEN - SAE J516 / ISO 12151-3

FLANGIA 45° ISO/SAE CODE 61 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M43340-12-12	19	3/4"	- 12	3/4"	16,0	75,6	38,0	23,0		
M43340-12-16	19	3/4"	- 12	1"	20,0	76,0	44,6	23,0		
M43340-16-16	25	1"	- 16	1"	20,0	87,0	44,6	27,3		
M43340-16-20	25	1"	- 16	1.1/4"	26,0	87,5	51,0	27,3		
M43340-20-20	31	1.1/4"	- 20	1.1/4"	26,0	100,5	51,0	29,5		
M43340-20-24	31	1.1/4"	- 20	1.1/2"	32,0	101,5	60,5	31,0		
M43340-24-24	38	1.1/2"	- 24	1.1/2"	32,0	111,0	60,5	34,5		
M43340-24-32	38	1.1/2"	- 24	2"	42,0	113,0	71,6	34,5		
M43340-32-32	51	2"	- 32	2"	42,0	128,7	71,6	39,0		


M43610

ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3


ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3

ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D			
M43610-10-12	16	5/8"	- 10	3/4"	16,0	64,0	41,4			
M43610-10-16	16	5/8"	- 10	1"	20,0	81,5	47,7			
M43610-12-12	19	3/4"	- 12	3/4"	16,0	71,4	41,4			
M43610-12-16	19	3/4"	- 12	1"	20,0	83,4	47,7			
M43610-16-12	25	1"	- 16	3/4"	16,0	80,3	41,4			
M43610-16-16	25	1"	- 16	1"	20,0	84,7	47,7			
M43610-16-20	25	1"	- 16	1.1/4"	26,0	89,0	54,2			
M43610-20-16	31	1.1/4"	- 20	1"	20,0	87,2	47,7			
M43610-20-20	31	1.1/4"	- 20	1.1/4"	26,0	91,1	54,2			
M43610-20-24	31	1.1/4"	- 20	1.1/2"	32,0	97,2	63,7			
M43610-24-20	38	1.1/2"	- 24	1.1/4"	26,0	101,2	54,2			
M43610-24-24	38	1.1/2"	- 24	1.1/2"	32,0	97,7	63,7			
M43610-24-32	38	1.1/2"	- 24	2"	42,0	112,8	79,6			
M43610-32-24	51	2"	- 32	1.1/2"	32,0	117,0	63,7			
M43610-32-32	51	2"	- 32	2"	42,0	112,8	79,6			



M43690


90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3

90° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M43690-10-12	16	5/8"	- 10	3/4"	16,0	57,5	41,4	60,5		
M43690-12-12	19	3/4"	- 12	3/4"	16,0	72,4	41,4	59,0		
M43690-12-16	19	3/4"	- 12	1"	20,0	72,4	47,7	65,0		
M43690-16-12	25	1"	- 16	3/4"	16,0	81,3	41,4	62,0		
M43690-16-16	25	1"	- 16	1"	20,0	81,1	47,7	68,0		
M43690-16-20	25	1"	- 16	1.1/4"	26,0	78,6	54,2	76,0		
M43690-20-16	31	1.1/4"	- 20	1"	20,0	98,5	47,7	79,0		
M43690-20-20	31	1.1/4"	- 20	1.1/4"	26,0	98,5	54,2	81,0		
M43690-20-24	31	1.1/4"	- 20	1.1/2"	32,0	98,5	63,7	91,5		
M43690-24-20	38	1.1/2"	- 24	1.1/4"	26,0	111,2	54,2	91,0		
M43690-24-24	38	1.1/2"	- 24	1.1/2"	32,0	112,5	63,7	94,5		
M43690-24-32	38	1.1/2"	- 24	2"	42,0	112,5	79,6	110,5		
M43690-32-32	51	2"	- 32	2"	42,0	140,7	79,6	132,0		



M43640

45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

45° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3

45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M43640-10-12	16	5/8"	- 10	3/4"	16,0	71,0	41,4	31,0		
M43640-10-16	16	5/8"	- 10	1"	20,0	83,5	47,7	32,5		
M43640-12-12	19	3/4"	- 12	3/4"	16,0	81,0	41,4	28,0		
M43640-12-16	19	3/4"	- 12	1"	20,0	85,4	47,7	32,3		
M43640-16-12	25	1"	- 16	3/4"	16,0	87,0	41,4	28,0		
M43640-16-16	25	1"	- 16	1"	20,0	91,4	47,7	32,3		
M43640-16-20	25	1"	- 16	1.1/4"	26,0	93,7	54,2	37,5		
M43640-20-16	31	1.1/4"	- 20	1"	20,0	106,5	47,7	36,0		
M43640-20-20	31	1.1/4"	- 20	1.1/4"	26,0	108,0	54,2	37,5		
M43640-20-24	31	1.1/4"	- 20	1.1/2"	32,0	115,0	63,7	45,0		
M43640-24-20	38	1.1/2"	- 24	1.1/4"	26,0	124,5	54,2	43,0		
M43640-24-24	38	1.1/2"	- 24	1.1/2"	32,0	124,3	63,7	44,0		
M43640-24-32	38	1.1/2"	- 24	2"	42,0	135,6	79,6	55,4		
M43640-32-32	51	2"	- 32	2"	42,0	154,0	79,6	60,5		

INTERLOCK PLUS TYPE



SAE STANDARD CONNECTIONS


M43630

30° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

30° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3

30° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 30° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M43630-12-12	19	3/4"	- 12	3/4"	16,0	87,0	41,4	17,5		
M43630-16-16	25	1"	- 16	1"	20,0	98,5	47,7	20,0		
M43630-20-20	31	1.1/4"	- 20	1.1/4"	26,0	115,5	54,2	23,0		
M43630-24-24	38	1.1/2"	- 24	1.1/2"	32,0	133,5	63,7	27,0		
M43630-32-32	51	2"	- 32	2"	42,0	166,5	79,6	60,5		


M43660

60° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

60° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3


60° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA 60° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E		
M43660-12-12	19	3/4"	- 12	3/4"	16,0	98,5	41,4	39,0		
M43660-12-16	19	3/4"	- 12	1"	20,0	101,5	47,7	44,0		
M43660-16-16	25	1"	- 16	1"	20,0	107,5	47,7	52,0		
M43660-20-20	31	1.1/4"	- 20	1.1/4"	26,0	130,0	54,2	59,0		
M43660-20-24	31	1.1/4"	- 20	1.1/2"	32,0	136,0	63,7	67,5		
M43660-24-24	38	1.1/2"	- 24	1.1/2"	32,0	154,0	63,7	61,5		
M43660-32-32	51	2"	- 32	2"	42,0	197,5	79,5	85,0		

M43710



FLANGE PLUS (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)


法兰增强式 (SAE J518 CODE 62 / ISO 6162-2 端口兼容)

GERADER FLANSCH SCHWERE REIHE (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS)

FLANGIA PLUS (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	S		
M43710-10-12	16	5/8"	- 10	3/4"	16,0	51,5	41,4	9,0		
M43710-12-12	19	3/4"	- 12	3/4"	14,5	71,5	41,4	10,0		
M43710-16-16	25	1"	- 16	1"	19,5	64,0	47,7	11,0		
M43710-20-20	31	1.1/4"	- 20	1.1/4"	25,0	81,0	54,2	12,0		

M43740



45° FLANGE PLUS (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)


45° 法兰增强式 (SAE J518 CODE 62 - ISO 6162-2 端口兼容)

45°-BOGEN FLANSCH SCHWERE REIHE

(SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS)

FLANGIA PLUS 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43740-10-12	16	5/8"	- 10	3/4"	16,0	72,5	41,4	32,0	9,0	
M43740-12-12	19	3/4"	- 12	3/4"	14,5	113,0	41,4	40,0	10,0	
M43740-16-16	25	1"	- 16	1"	19,5	113,5	47,7	43,0	11,0	
M43740-20-20	31	1.1/4"	- 20	1.1/4"	25,0	133,5	54,2	50,0	12,0	



M43790

90° FLANGE PLUS (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)

90° 法兰增强式 (SAE J518 CODE 62 - ISO 6162-2 端口兼容)

90°-BOGEN FLANSCH SCHWERE REIHE

(SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS)

FLANGIA PLUS 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43790-10-12	16	5/8"	- 10	3/4"	16,0	61,5	41,4	60,5	9,0	
M43790-12-12	19	3/4"	- 12	3/4"	14,5	93,0	41,4	75,0	10,0	
M43790-16-16	25	1"	- 16	1"	19,5	90,0	47,7	90,0	11,0	
M43790-20-20	31	1.1/4"	- 20	1.1/4"	25,0	115,0	54,0	110,0	12,0	

INTERLOCK PLUS TYPE



ORIGINAL EQUIPEMENT CONNECTIONS


M43910

STRAIGHT SUPERCAT SERIES FLANGE

山猫系列直式法兰

FLANSCH GERADE SUPERCAT

FLANGIA DITTA SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	S		
M43910-12-12	19	3/4"	- 12	3/4"	16,0	77,0	41,5	14,3		
M43910-12-16	19	3/4"	- 12	1"	20,0	88,5	47,7	14,3		
M43910-16-16	25	1"	- 16	1"	20,0	89,5	47,7	14,3		
M43910-16-20	25	1"	- 16	1.1/4"	26,0	93,5	54,0	14,3		
M43910-20-20	31	1.1/4"	- 20	1.1/4"	26,0	95,2	54,0	14,3		
M43910-20-24	31	1.1/4"	- 20	1.1/2"	32,0	98,5	63,6	14,3		
M43910-24-24	38	1.1/2"	- 24	1.1/2"	32,0	99,2	63,6	14,3		
M43910-24-32	38	1.1/2"	- 24	2"	42,0	115,0	79,3	14,3		
M43910-32-24	51	2"	- 32	1.1/2"	32,0	119,0	63,6	14,3		
M43910-32-32	51	2"	- 32	2"	42,0	114,0	79,3	14,3		


M43920

22,5° SUPERCAT SERIES FLANGE


22,5° 山猫系列法兰

22,5° FLANSCH SERIE SUPERCAT

FLANGIA 22,5° SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43920-12-12	19	3/4"	- 12	3/4"	16,0	94,5	41,5	14,5	14,3	
M43920-12-16	19	3/4"	- 12	1"	20,0	102,0	47,7	16,5	14,3	
M43920-16-16	25	1"	- 16	1"	20,0	111,0	47,7	16,5	14,3	
M43920-16-20	25	1"	- 16	1.1/4"	26,0	115,5	54,0	19,0	14,3	
M43920-20-20	31	1.1/4"	- 20	1.1/4"	26,0	122,0	54,0	18,0	14,3	
M43920-20-24	31	1.1/4"	- 20	1.1/2"	32,0	139,0	63,6	23,0	14,3	
M43920-24-24	38	1.1/2"	- 24	1.1/2"	32,0	138,0	63,6	20,0	14,3	



M43930


30° SUPERCAT SERIES FLANGE

30° 山猫系列法兰

30° FLANSCH SERIE SUPERCAT

FLANGIA 30° SERIE SUPERCAT

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43930-12-12	19	3/4"	- 12	3/4"	16,0	92,0	41,5	20,0	14,3	
M43930-12-16	19	3/4"	- 12	1"	20,0	99,5	47,7	22,5	14,3	
M43930-16-16	25	1"	- 16	1"	20,0	108,5	47,7	23,0	14,3	
M43930-16-20	25	1"	- 16	1.1/4"	26,0	112,5	54,0	26,0	14,3	
M43930-20-20	31	1.1/4"	- 20	1.1/4"	26,0	119,0	54,0	25,0	14,3	
M43930-20-24	31	1.1/4"	- 20	1.1/2"	32,0	135,5	63,6	32,0	14,3	
M43930-24-24	38	1.1/2"	- 24	1.1/2"	32,0	135,0	63,6	28,0	14,3	
M43930-24-32	38	1.1/2"	- 24	2"	42,0	151,5	79,3	36,0	14,3	
M43930-32-32	51	2"	- 32	2"	42,0	171,5	79,3	37,5	14,3	



M43940

45° SUPERCAT SERIES FLANGE

45° 山猫系列法兰

FLANSCH 45° BOGEN SUPERCAT

FLANGIA 45° SERIE SUPERCAT

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43940-12-12	19	3/4"	- 12	3/4"	16,0	85,0	41,5	32,0	14,3	
M43940-12-16	19	3/4"	- 12	1"	20,0	92,0	47,7	35,5	14,3	
M43940-16-16	25	1"	- 16	1"	20,0	100,4	47,7	36,7	14,3	
M43940-16-20	25	1"	- 16	1.1/4"	26,0	104,0	54,0	40,5	14,3	
M43940-20-20	31	1.1/4"	- 20	1.1/4"	26,0	110,5	54,0	40,5	14,3	
M43940-20-24	31	1.1/4"	- 20	1.1/2"	32,0	125,5	63,6	50,5	14,3	
M43940-24-24	38	1.1/2"	- 24	1.1/2"	32,0	125,5	63,6	45,3	14,3	
M43940-24-32	38	1.1/2"	- 24	2"	42,0	139,5	79,3	56,5	14,3	
M43940-32-32	51	2"	- 32	2"	42,0	158,5	79,3	61,5	14,3	

INTERLOCK PLUS TYPE



ORIGINAL EQUIPEMENT CONNECTIONS


M43960

60° SUPERCAT SERIES FLANGE

60° 山猫系列法兰

60° FLANSCH SERIE SUPERCAT

FLANGIA 60° SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43960-12-12	19	3/4"	- 12	3/4"	16,0	101,5	41,5	44,0	14,3	
M43960-12-16	19	3/4"	- 12	1"	20,0	106,5	47,7	48,0	14,3	
M43960-16-16	25	1"	- 16	1"	20,0	122,0	47,7	51,0	14,3	
M43960-16-16055	25	1"	- 16	1"	20,0	117,5	47,7	55,0	14,3	
M43960-16-20	25	1"	- 16	1.1/4"	26,0	122,5	54,0	55,0	14,3	
M43960-20-20	31	1.1/4"	- 20	1.1/4"	26,0	135,5	54,0	56,0	14,3	
M43960-20-24	31	1.1/4"	- 20	1.1/2"	32,0	149,0	63,6	69,0	14,3	
M43960-24-24	38	1.1/2"	- 24	1.1/2"	32,0	154,5	63,6	63,0	14,3	
M43960-32-32	51	2"	- 32	2"	42,0	202,0	79,3	86,5	14,3	
M43960-32-32150	51	2"	- 32	2"	42,0	196,5	79,3	150,0	14,3	


M43970

67,5° SUPERCAT SERIES FLANGE


67,5° 山猫系列法兰

67,5° FLANSCH SERIE SUPERCAT

FLANGIA 67,5° SERIE SUPERCAT



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43970-12-12	19	3/4"	- 12	3/4"	16,0	95,5	41,5	49,5	14,3	
M43970-12-16	19	3/4"	- 12	1"	20,0	100,0	47,7	54,0	14,3	
M43970-16-16	25	1"	- 16	1"	20,0	115,0	47,7	58,0	14,3	
M43970-16-20	25	1"	- 16	1.1/4"	26,0	115,0	54,0	62,0	14,3	
M43970-20-20	31	1.1/4"	- 20	1.1/4"	26,0	128,0	54,0	64,0	14,3	
M43970-20-24	31	1.1/4"	- 20	1.1/2"	32,0	139,5	63,6	78,0	14,3	
M43970-24-24	38	1.1/2"	- 24	1.1/2"	32,0	146,0	63,6	72,0	14,3	
M43970-32-32	51	2"	- 32	2"	42,0	189,5	79,3	99,0	14,3	



M43990


90° SUPERCAT SERIES FLANGE

90° 山猫系列法兰

FLANSCH 90° BOGEN SUPERCAT

FLANGIA 90° SERIE SUPERCAT

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43990-12-12	19	3/4"	- 12	3/4"	16,0	72,5	41,5	64,5	14,3	
M43990-12-16	19	3/4"	- 12	1"	20,0	75,5	47,7	69,5	14,3	
M43990-16-16	25	1"	- 16	1"	20,0	88,5	47,7	76,5	14,3	
M43990-16-20	25	1"	- 16	1.1/4"	26,0	86,5	54,0	80,5	14,3	
M43990-20-20	31	1.1/4"	- 20	1.1/4"	26,0	98,5	54,0	85,0	14,3	
M43990-20-24	31	1.1/4"	- 20	1.1/2"	32,0	104,5	63,6	101,0	14,3	
M43990-24-24	38	1.1/2"	- 24	1.1/2"	32,0	112,5	63,6	96,5	14,3	
M43990-24-32	38	1.1/2"	- 24	2"	42,0	115,0	79,3	112,0	14,3	
M43990-32-32	51	2"	- 32	2"	42,0	144,0	79,3	133,5	14,3	



M43990 LONG DROP

90° LONG DROP SUPERCAT SERIES FLANGE

90° 加长山猫系列法兰

90° LANGER SCHENKEL FLANSCH SERIE SUPERCAT

FLANGIA 90° SERIE SUPERCAT CURVA LUNGA

PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					
	DN	inch	Size		B	A	D	E	S	
M43990-16-16132	25	1"	- 16	1"	20,0	88,5	47,7	132,0	14,3	
M43990-16-16150	25	1"	- 16	1"	20,0	88,5	47,7	150,0	14,3	
M43990-16-20150	25	1"	- 16	1.1/4"	26,0	88,5	54,0	150,0	14,3	
M43990-20-20092	31	1.1/4"	- 20	1.1/4"	26,0	98,5	54,0	92,0	14,3	
M43990-20-20150	31	1.1/4"	- 20	1.1/4"	26,0	98,5	54,0	150,0	14,3	
M43990-20-24135	31	1.1/4"	- 20	1.1/2"	32,0	98,5	63,6	135,0	14,3	
M43990-24-24106	38	1.1/2"	- 24	1.1/2"	32,0	112,5	63,6	106,0	14,3	

INTERLOCK PLUS TYPE



XTRAFLANGE


M48510

XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)

XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容)

XTRAFLANSCH GERADE (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					WEIGHT
	DN	inch	Size		B	A	D			kg
M48510-12-12	19	3/4"	- 12	3/4"	14,5	64,0	41,4			0,4
M48510-16-16	25	1"	- 16	1"	19,5	68,3	47,7			0,6
M48510-20-20	31	1.1/4"	- 20	1.1/4"	25,0	88,0	54,4			1,0
M48510-24-24	38	1.1/2"	- 24	1.1/2"	31,0	102,0	63,7			1,4
M48510-32-32	51	2"	- 32	2"	41,0	129,0	79,6			2,7


M48540

45° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)

45° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容)

45°-BOGEN XTRAFLANSCH (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					WEIGHT
	DN	inch	Size		B	A	D	E		kg
M48540-12-12	19	3/4"	- 12	3/4"	14,5	92,5	41,4	38,0		0,5
M48540-16-16	25	1"	- 16	1"	19,5	101,5	47,7	45,0		0,7
M48540-20-20	31	1.1/4"	- 20	1.1/4"	25,0	138,0	54,4	62,5		1,3
M48540-24-24	38	1.1/2"	- 24	1.1/2"	31,0	155,0	63,7	71,5		1,9
M48540-32-32	51	2"	- 32	2"	41,0	193,5	79,6	92,5		3,9


M48590

90° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)

90° XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容)


XTRAFLANSCH 90° BOGEN (SAE J518 CODE 62 - ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm					WEIGHT
	DN	inch	Size		B	A	D	E		kg
M48590-12-12	19	3/4"	- 12	3/4"	14,5	75,5	41,4	75,0		0,5
M48590-16-16	25	1"	- 16	1"	19,5	83,5	47,7	90,0		0,8
M48590-20-20	31	1.1/4"	- 20	1.1/4"	25,0	107,0	54,4	120,0		1,5
M48590-24-24	38	1.1/2"	- 24	1.1/2"	31,0	122,0	63,7	140,0		2,2
M48590-32-32	51	2"	- 32	2"	41,0	147,5	79,6	180,0		4,3

M31210



METRIC MALE 24° CONE SEAT HEAVY DUTY - DIN 20066 / ISO 12151-2

公制外螺纹 24° - 锥形底座重型系列 DIN 20066 / ISO 12151-2


CES - DIN 20066 / ISO 12151-2

MASCHIO METRICO 24° - SERIE PESANTE DIN 20066 / ISO 12151-2

PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm					
------------	-----------	--	--------	------	---------------	--	--	--	--	--

	DN	inch	Size	T	mm	B	A	C		H1
M31210-10-30	16	5/8"	- 10	M 30x2	20	12,0	36,8	16,0		30
M31210-12-30	19	3/4"	- 12	M 30x2	20	14,5	38,5	16,0		32
M31210-12-36	19	3/4"	- 12	M 36x2	25	14,5	43,4	18,0		36
M31210-16-36	25	1"	- 16	M 36x2	25	19,5	45,0	18,0		36
M31210-16-42	35	1"	- 16	M 42x2	30	19,5	46,8	20,0		46
M31210-20-52	31	1.1/4"	- 20	M 52x2	38	25,0	55,0	22,0		55
M31210-24-52	38	1.1/2"	- 24	M 52x2	38	30,5	55,6	22,0		55

M41612



METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


公制内螺纹 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOS - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)

M41613



METRIC O-RING FEMALE 24° CONE HEAVY DUTY - DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

公制内螺纹 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOS - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)

PART. REF.	HOSE BORE		THREAD	PIPE	DIMENSIONS mm					
------------	-----------	--	--------	------	---------------	--	--	--	--	--

	DN	inch	Size	T	mm	B	A	C		H2
M41613-10-30	16	5/8"	- 10	M 30x2	20	12,0	37,1	3,5		36
M41612-10-24	16	5/8"	- 10	M 24x1,5	16	9,3	31,0	4,0		30
M41612-12-30	19	3/4"	- 12	M 30x2	20	12,5	43,9	3,2		36
M41613-12-36	19	3/4"	- 12	M 36x2	25	14,5	42,1	3,4		41
M41613-12-42	19	3/4"	- 12	M 42x2	30	19,0	35,8	5,3		50
M41612-16-36	25	1"	- 16	M 36x2	25	16,0	46,8	4,1		41
M41613-16-42	25	1"	- 16	M 42x2	30	19,5	46,3	5,3		50
M41613-16-52	25	1"	- 16	M 52x2	38	26,0	50,5	8,0		60
M41612-20-42	31	1.1/4"	- 20	M 42x2	30	19,0	47,5	6,1		50
M41613-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	41,7	8,0		60
M41612-24-52	38	1.1/2"	- 24	M 52x2	38	29,0	52,5	8,8		60

INTERLOCK PLUS TYPE



DIN STANDARD CONNECTIONS

M41692

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY


DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)

90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列 SERIE PESADA

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)



M41693

90° METRIC O-RING FEMALE SWEPT ELBOW 24° CONE HEAVY DUTY


DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

90° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)


DKOS 90° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA 90° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M41693-10-30	16	5/8"	- 10	M 30x2	20	12,0	52,5	3,5	57,5		36
M41692-12-30	19	3/4"	- 12	M 30x2	25	12,5	63,8	3,2	68,5		36
M41693-12-36	19	3/4"	- 12	M 36x2	25	14,5	67,0	3,4	67,5		41
M41692-16-36	25	1"	- 16	M 36x2	25	16,0	81,7	4,1	89,0		41
M41693-16-42	25	1"	- 16	M 42x2	30	19,5	81,6	5,3	75,5		50
M41692-20-42	31	1.1/4"	- 20	M 42x2	30	19,0	103,5	6,1	90,0		50
M41693-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	100,0	8,0	86,5		60

M41642



45° METRIC O-RING FEMALE SWEEP ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (THRUST-WIRE NUT)


45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带止推金属丝螺母)

DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (GESTIFTETE MUTTER)

FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO SPINATO)

M41643



45° METRIC O-RING FEMALE SWEEP ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

45° 公制内螺纹巨肘弯头 24° 锥带O型圈重型系列

DIN 20066 / ISO 12151-2 (带滑套螺母)

DKOS 45° BOGEN - DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA 45° CONO 24° O-RING SERIE PESANTE DIN 20066 / ISO 12151-2 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M41643-10-30	16	5/8"	- 10	M 30x2	20	12,0	66,5	3,5	29,5		36
M41642-12-30	19	3/4"	- 12	M 30x2	20	12,5	79,2	3,2	34,8		36
M41643-12-36	19	3/4"	- 12	M 36x2	25	14,5	81,0	3,4	33,5		41
M41642-16-36	25	1"	- 16	M 36x2	25	16,0	103,0	4,1	45,5		41
M41643-16-42	25	1"	- 16	M 42x2	30	19,5	93,1	5,3	36,0		50
M41642-20-42	31	1.1/4"	- 20	M 42x2	30	19,0	116,5	6,1	44,5		50
M41643-20-52	31	1.1/4"	- 20	M 52x2	38	26,0	110,0	8,0	40,0		60

M41293

90° METRIC O-RING FEMALE MEDIUM/LONG DROP ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

90° 公制内螺纹中型/加长弯头 24° 锥带O型圈重型系列


DIN 20066 / ISO 12151-2 (带滑套螺母)

90° BOGEN O-RING METRISCH 24° KONUS H.T.

DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA O-RING SERIE PESANTE CONO 24° CURVA 90° MEDIO/LUNGA

DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M41293-10-30	16	5/8"	- 10	M 30x2	20	12,0	53,0	3,5	60,0		36
M41293-12-36	19	3/4"	- 12	M 36x2	25	14,5	67,0	3,4	67,5		41
M41293-16-42	25	1"	- 16	M 42x2	30	19,5	81,5	5,3	86,0		50
M41293-20-52	31	1.1/4"	- 20	M 52x2	38	26,1	100,0	8,0	92,0		60

M41243

45° METRIC O-RING FEMALE MEDIUM/LONG DROP ELBOW 24° CONE HEAVY DUTY

DIN 20066 / ISO 12151-2 (SLIP-ON NUT)

45° 公制内螺纹中型/加长弯头 24° 锥带O型圈重型系列


DIN 20066 / ISO 12151-2 (带滑套螺母)

45° BOGEN O-RING METRISCH 24° KONUS H.T.


DIN 20066 / ISO 12151-2 (HINTERLEGTE MUTTER)

FEMMINA METRICA O-RING SERIE PESANTE CONO 24° CURVA 45° MEDIO/LUNGA

DIN 20066 / ISO 12151-2 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	PIPE	DIMENSIONS mm					
	DN	inch	Size	T	mm	B	A	C	E		H ₂
M41243-10-30	16	5/8"	- 10	M 30x2	20	12,0	77,5	3,5	35,0		36
M41243-12-36	19	3/4"	- 12	M 36x2	25	14,5	101,0	3,4	45,0		41
M41243-16-42	25	1"	- 16	M 42x2	30	19,5	112,0	5,3	55,0		50
M41243-20-52	31	1.1/4"	- 20	M 52x2	38	26,1	133,0	8,0	63,0		60



M30050


DOUBLE CONNECTOR

双插芯接头

DOPPELVERBINDER

DOPPIO INSERTO

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		B	A	C			
M30050-20-20	31	1.1/4"	- 20		25,0	42,0	206,0			
M30050-24-24	38	1.1/2"	- 24		31,0	42,5	228,5			
M30050-32-32	51	2"	- 32		41,0	42,5	244,5			



M49510WL


WELDING TAIL

焊接插芯

VERSCHWEISSNIPPEL

INSERTO A SALDARE

PART. REF.	HOSE BORE				DIMENSIONS mm					
	DN	inch	Size		B	A	C	D		
M49510-10-18WL	16	5/8"	- 10		18,1	20,5	10,0	26,0		
M49510-12-22WL	19	3/4"	- 12		22,1	27,5	12,0	34,0		
M49510-16-28WL	25	1"	- 16		28,1	31,5	14,0	40,0		
M49510-20-35WL	31	1.1/4"	- 20		35,1	33,0	14,0	49,0		



JO29

OPTIONAL INTERLOCK PLUS O-RING

可选内锁增强式O型圈

OPTIONAL INTERLOCK PLUS O-RING

O-RING INTERLOCK PLUS OPZIONALE

PART. REF.	HOSE BORE			O-RING SIZE (dxs mm)	MATERIAL
	DN	inch	Size		
JO29171318	16	5/8"	- 10	13,20x1,80	NBR 90 Shore A
JO29191618	19	3/4"	- 12	15,60x1,78	NBR 90 Shore A
JO29262218	25	1"	- 16	21,95x1,78	NBR 90 Shore A
JO29322818	31	1.1/4"	- 20	28,30x1,78	NBR 90 Shore A
JO29383518	38	1.1/2"	- 24	34,65x1,78	NBR 90 Shore A
JO29514718	51	2"	- 32	47,35x1,78	NBR 90 Shore A

DIAMONDSPIR HOSE RANGE

M01750


DOUBLE SKIVE FERRULE FOR EXTRA DUTY SPIRAL HOSES (4 PLY)

超重型缠绕软管 (四层) 双面剥胶套筒

PRESSFASSUNG FÜR INNEN- UND AUSSENSCHÄLUNG FÜR SPEZIAL-SPIRALSCHLÄUCHE (4-LAGIG)

GHIERA A PELATURA INTERNA/ESTERNA PER TUBI SPIRALATI

(4 SPIRALI) PER APPLICAZIONI ESTREMAMENTE SEVERE



PART. REF.	HOSE BORE				DIMENSIONS mm			
	DN	inch	Size		D	L	C	H _i
M01750-12	19	3/4"	- 12		45,1	69,0		

M01800


DOUBLE SKIVE FERRULE FOR EXTRA DUTY SPIRAL HOSES (6 PLY)

超重型缠绕软管 (六层) 双面剥胶套筒


PRESSFASSUNG FÜR INNEN- UND AUSSENSCHÄLUNG FÜR SPEZIAL-SPIRALSCHLÄUCHE (6-LAGIG)

GHIERA A PELATURA INTERNA/ESTERNA PER TUBI SPIRALATI

(6 SPIRALI) PER APPLICAZIONI ESTREMAMENTE SEVERE



PART. REF.	HOSE BORE				DIMENSIONS mm			
	DN	inch	Size		D	L		
M01800-16	25	1"	- 16		53,5	69,0		
M01800-20	31	1.1/4"	- 20		64,5	88,2		
M01800-24	38	1.1/2"	- 24		73,0	97,8		
M01800-32	51	2"	- 32		86,5	108,0		
M01800-40	63	2.1/2"	- 40		103,0	135,0		
M01800-48	76	3"	- 48		113,5	125,0		



M52810/M57810

NPTF MALE 60° CONE SEAT - SAE J516/J514

NPTF 外螺纹 60° 锥形底座 - SAE J516/J514

AG NPTF KONUS 60° - SAE J516/J514

MASCHIO NPTF CONO 60° - SAE J516/J514

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm			
------------	-----------	--	--	--------	------------------	--	--	--

	DN	inch	Size	T	B	A	C	H ₁
M52810-12-12	19	3/4"	12	3/4" - 14	15,0	49,4	21,0	32
M57810-16-16	25	1"	- 16	1" - 11.5	19,0	60,4	24,2	41
M57810-20-20	31	1.1/4"	- 20	1.1/4" - 11.5	26,1	63,9	28,0	46
M57810-24-24	38	1.1/2"	- 24	1.1/2" - 11.5	32,1	70,4	30,0	55
M57810-32-32	51	2"	- 32	2" - 11.5	42,0	75,5	35,0	70
M57810-40-40	63	2.1/2"	- 40	2.1/2" - 8	55,4	94,5	43,0	80
M57810-48-48	76	3"	- 48	3" - 8	62,5	123,5	51,5	100


M68610

ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3

ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3

ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3

FLANGIA DITTA SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			
------------	-----------	--	--	--------	------------------	--	--	--

	DN	inch	Size		B	A	D	
M68610-12-12	19	3/4"	-12	3/4"	16,0	74,0	41,4	
M68610-16-16	25	1"	- 16	1"	20,0	86,0	47,7	
M68610-20-20	31	1.1/4"	- 20	1.1/4"	26,0	91,0	54,2	
M68610-24-24	38	1.1/2"	- 24	1.1/2"	32,0	97,5	63,7	
M68610-32-32	51	2"	- 32	2"	42,0	112,5	79,6	
M68610-32-40 *	51	2"	- 32	2.1/2"	51,5	124,0	107,8	
M68610-40-32	63	2.1/2"	- 40	2"	41,0	115,0	79,6	
M68610-40-40 *	63	2.1/2"	- 40	2.1/2"	51,5	127,0	107,8	
M68610-48-48 *	76	3"	- 48	3"	63,0	167,0	131,9	

* Manuli specification / 玛努利规格 / Especificación Manuli / Specifica Manuli


XTRALOCK TYPE



DIAMONDSPIR HOSE RANGE

M68690


90° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3
90° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3
90° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3
FLANGIA 90° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3




PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			
	DN	inch	Size		B	A	D	E
M68690-12-12	19	3/4"	- 12	3/4"	16,0	75,0	41,4	59,0
M68690-16-16	25	1"	- 16	1"	20,0	89,0	47,7	80,0
M68690-20-20	31	1.1/4"	- 20	1.1/4"	24,0	110,0	54,2	93,0
M68690-24-24	38	1.1/2"	- 24	1.1/2"	38,5	125,0	63,7	110,0
M68690-32-32	51	2"	- 32	2"	42,0	148,0	79,6	136,0

M68640

45° ISO/SAE CODE 62 FLANGE - SAE J516 / ISO 12151-3
45° ISO/SAE CODE 62 法兰 - SAE J516 / ISO 12151-3
45° ISO/SAE CODE 62 FLANSCH - SAE J516 / ISO 12151-3
FLANGIA 45° ISO/SAE CODE 62 - SAE J516 / ISO 12151-3



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			
	DN	inch	Size		B	A	D	E
M68640-16-16	25	1"	- 16	1"	20,0	98,5	47,7	38,0
M68640-20-20	31	1.1/4"	- 20	1.1/4"	24,0	121,5	54,2	43,5
M68640-24-24	38	1.1/2"	- 24	1.1/2"	38,5	136,0	63,7	50,0
M68640-32-32	51	2"	- 32	2"	42,0	160,0	79,6	61,0




M53410

API MALE WITH HEXAGONAL BODY (API 5B THREAD)

六角形 API 外螺纹接头 (API 5B 螺纹)

VERBINDER API SECHSKANT (API 5B GEWINDE)

MASCHIO API CON CORPO ESAGONALE (FILETTATURA API 5B)



M53410...H00


API MALE WITH CYLINDRICAL BODY (API 5B THREAD)

圆柱形 API 外螺纹接头 (API 5B 螺纹)

VERBINDER API ZYLINDRISCH (API 5B GEWINDE)

MASCHIO API CON CORPO CILINDRICO (FILETTATURA API 5B)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C		H ₁
M53410-32-32	51	2"	- 32	2" - 11,5	41	119,5	55,0			70
M53410-32-32H00	51	2"	- 32	2" - 11,5	41	76,5	60			-
M53410-40-40	63	2.1/2"	- 40	2.1/2" - 8	51,5	135,0	63,0			80
M53410-40-40H00	63	2.1/2"	- 40	2.1/2" - 8	51,5	99,5	81			-
M53410-48-48	76	3"	- 48	3" - 8	62,5	143,5	71,5			100
M53410-48-48H00	76	3"	- 48	3" - 8	62,5	115	100			-
M53410-48-64	76	3"	-48	4" - 8	62,5	171,5	76,0			120
M53410-48-64H00	76	3"	- 48	4" - 8	62,5	151,5	118			-



M53510

NPT MALE

NPT 外螺纹

NPT-SCHRAUBVERBINDUNG

NPT MASCHIO

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size		T	B	A	C		H ₁
M53510-32-32	51	2"	- 32	2" - 11,5	41,0	119,5	55,0	70		
M53510-40-40	63	2.1/2"	- 40	2.1/2" - 8	51,5	135,0	63,0	80		
M53510-48-48	76	3"	- 48	3" - 8	62,5	143,5	71,5	100		

XTRAFLANGE


M68510

XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 PORT COMPATIBLE)

XTRAFLANGE (SAE J518 CODE 62 - ISO 6162-2 端口兼容)

XTRAFLANSCH GERADE (SAE J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm			W.P.	WEIGHT
	DN	inch	Size		B	A	D	bar	kg
M68510-16-16	25	1"	- 16	1"	20,0	69,5	47,7	560	0,6
M68510-20-20	31	1.1/4"	- 20	1.1/4"	24,0	88,0	54,4	560	1,0
M68510-20-24	31	1.1/4"	- 20	1.1/2"	30,5	100,0	63,7	560	1,3
M68510-24-24	38	1.1/2"	- 24	1.1/2"	30,5	102,0	63,7	560	1,4
M68510-32-32	51	2"	- 32	2"	41,0	129,0	79,6	450	2,7
M68510-40-40	63	2.1/2"	- 40	2.1/2"	51,5	149,0	99,2	350	4,4


M68590

90° XTRAFLANGE (SAE J518 CODE 62 AND ISO 6162-2 PORT COMPATIBLE)

90° XTRAFLANGE (SAE J518 CODE 62 和 ISO 6162-2 端口兼容)

XTRAFLANSCH 90° BOGEN (J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA 90° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)



PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				W.P.	WEIGHT
	DN	inch	Size		B	A	D	E	bar	kg
M68590-16-16	25	1"	- 16	1"	20,0	84,2	47,7	90,0	560	0,8
M68590-20-20	31	1.1/4"	- 20	1.1/4"	24,0	107,0	54,4	120,0	560	1,5
M68590-24-24	38	1.1/2"	- 24	1.1/2"	30,5	122,2	63,7	140,0	560	2,2
M68590-32-32	51	2"	- 32	2"	41,0	147,5	79,6	180,0	450	4,3


M68540

45° XTRAFLANGE (SAE J518 CODE 62 AND ISO 6162-2 PORT COMPATIBLE)


45° XTRAFLANGE (SAE J518 CODE 62 和 ISO 6162-2 端口兼容)

XTRAFLANSCH 45° BOGEN (SAE J518 CODE 62 / ISO 6162-2 KOMPATIBLER ANSCHLUSS)

XTRAFLANGIA 45° (COMPATIBILE CON PORTA SAE J518 CODE 62 / ISO 6162-2)




PART. REF.	HOSE BORE			FLANGE	DIMENSIONS mm				W.P.	WEIGHT
	DN	inch	Size		B	A	D	E	bar	kg
M68540-16-16	25	1"	- 16	1"	20,0	103,0	47,7	45,0	560	0,7
M68540-20-20	31	1.1/4"	- 20	1.1/4"	24,0	138,0	54,4	62,5	560	1,4
M68540-24-24	38	1.1/2"	- 24	1.1/2"	30,5	155,0	63,7	71,5	560	1,9
M68540-32-32	51	2"	- 32	2"	41,0	193,5	79,6	92,5	450	4,0



O83308

ISO/SAE CODE 61 SPLIT FLANGE CLAMPS - SAE J518 / ISO 6162-1
 ISO/SAE CODE 61 分片法兰管夹 - SAE J518 / ISO 6162-1
 ISO/SAE CODE 61 ZWEIFELIGER GEGENFLANSCH - SAE J518 / ISO 6162-1
 SEMIFLANGIA ISO/SAE CODE 61 - SAE J518 / ISO 6162-1

PART. REF.	HOSE BORE			DIMENSIONS mm						
	DN	inch	Size		B	A	C	D	E	
O83308-08	12	1/2"	- 08		23,0	54,0	38,1	9,0	8,7	
O83308-12	19	3/4"	- 12		26,1	65,1	47,6	11,0	11,1	
O83308-16	25	1"	- 16		29,4	69,8	52,4	11,0	13,1	
O83308-20	31	1.1/4"	- 20		36,5	79,4	58,7	12,0	15,1	
O83308-24	38	1.1/2"	- 24		41,3	93,7	69,8	13,5	17,8	
O83308-32	51	2"	- 32		48,4	101,6	77,8	13,5	21,4	
O83308-40	63	2.1/2"	- 40		54,4	114,3	88,9	13,5	25,4	
O83308-48	76	3"	- 48		65,3	135,0	106,4	16,5	30,9	



O83609

ISO/SAE CODE 62 SPLIT FLANGE CLAMPS - SAE J518 / ISO 6162-2
 ISO/SAE CODE 62 分片法兰管夹 - SAE J518 / ISO 6162-2
 ISO/SAE CODE 62 ZWEIFELIGER GEGENFLANSCH - SAE J518 / ISO 6162-2
 SEMIFLANGIA ISO/SAE CODE 62 - SAE J518 / ISO 6162-2

PART. REF.	HOSE BORE			DIMENSIONS mm						
	DN	inch	Size		B	A	C	D	E	
O83609-08	12	1/2"	- 08		23,8	56,3	40,5	9,0	9,1	
O83609-12	19	3/4"	- 12		30,2	71,4	50,8	11,0	11,9	
O83609-16	25	1"	- 16		34,9	80,9	57,1	13,0	13,9	
O83609-20	31	1.1/4"	- 20		38,9	95,2	66,7	15,0	15,8	
O83609-24	38	1.1/2"	- 24		47,6	112,7	79,4	17,0	18,2	
O83609-32	51	2"	- 32		57,1	133,3	96,8	21,0	22,2	

ACCESSORIES


O83607

ONE-PIECE FLANGE CLAMP ISO 6162-2 / SAE J518 CODE 62

整片法兰管夹 ISO 6162-2 / SAE J518 CODE 62

VOLLFLANSCH - ISO 6162-2 / SAE J518 CODE 62

SEMIFLANGIA INTERA - ISO 6162-2 / SAE J518 CODICE 62



PART. REF.	HOSE BORE			DIMENSIONS mm				
	DN	inch	Size	B	A	C	D	E
O83607-12	19	3/4"	- 12	60,0	72,0	50,8	10,5	23,8
O83607-16	25	1"	- 16	70,0	81,0	57,2	13,0	27,8
O83607-20	31	1.1/4"	- 20	78,0	96,0	66,7	15,0	31,8
O83607-24	38	1.1/2"	- 24	96,0	113,0	79,4	17,0	36,5
O83607-32	51	2"	- 32	114,0	134,0	96,8	21,0	44,4
O83607-40	63	2.1/2"	- 40	150,0	175,0	123,8	25,0	58,7
O83607-48	76	3"	- 48	178,0	210,0	152,4	32,0	71,4


O88507

ONE-PIECE XTRAFRANGE CLAMP ISO 6162-2 / SAE J518 CODE 62 PORT COMPATIBLE


整片 XTRAFRANGE 管夹 ISO 6162-2 / SAE J518 CODE 62 端口兼容

VOLLFLANSCH FÜR XTRAFRANSCH ISO 6162-2 / SAE J518 CODE 62 KOMPATIBLER ANSCHLUSS

SEMIFLANGIA INTERA XTRAFRANGIA ISO 6162-2 / SAE J518 COMPATIBILE CON PORTA CODE 62



PART. REF.	FLANGE SIZE			DIMENSIONS mm						BOLT	WEIGHT
	DN	inch	Size	B	A	C	D	E	H	length mm	kg
O88507-12	19	3/4"	- 12	60,0	71,5	50,8	11,0	23,8	21,5	50,0	0,4
O88507-16	25	1"	- 16	66,7	80,0	57,2	13,0	27,8	24,0	65,0	0,5
O88507-20	31	1.1/4"	- 20	78,0	95,0	66,7	15,0	31,7	30,0	75,0	0,9
O88507-24	38	1.1/2"	- 24	94,0	112,0	79,4	17,0	36,5	36,0	100,0	1,6
O88507-32	51	2"	- 32	114,0	133,0	96,8	21,0	44,5	47,0	110,0	2,7
O88507-40	63	2.1/2"	- 40	150,0	180,0	123,8	26,0	58,8	55,0	110,0	6,4



O820..

ANTI-KINK SLEEVE
抗扭曲套筒
KNICKSCHUTZHÜLSE
GHIERA ANTI-KINK

PART. REF.	HOSE BORE			DIMENSIONS mm			
	DN	inch	Size		D	L	
O82040-12	19	3/4"	- 12		45,0	67,0	
O82040-16	25	1"	- 16		52,0	81,0	
O82068-16	25	1"	- 16		55,0	75,0	
O82060-20	31	1.1/4"	- 20		64,0	84,0	
O82062-20	31	1.1/4 "	- 20		64,0	83,0	
O82068-20	31	1.1/4 "	- 20		65,5	83,0	
O82060-24	38	1.1/2"	- 24		72,0	102,0	
O82068-24	38	1.1/2"	- 24		73,0	99,0	
O82068-32	51	2"	- 32		86,5	116,0	
O82068-40	63	2.1/2"	- 40		103,0	148,5	
O82068-48	76	3"	- 48		112,0	156,5	



The following assembling instructions are strongly recommended on heavy duty applications.

强烈建议下列总成说明用于重型应用场合。

Bei schweren Anwendungen empfehlen wir unbedingt die folgenden Verarbeitungshinweise einzuhalten.

Si raccomanda di seguire attentamente le seguenti istruzioni d'assemblaggio in particolare in caso di applicazioni estremamente severe.

M437x0 - M686x0

PART. REF.	FLANGE SIZE	SPLIT FLANGE TYPE	ONE-PIECE FLANGE TYPE	OR (NBR 90 ShA) SAE J515	METRIC BOLT DIMENSIONS (Class. 10.9)	UNC BOLT DIMENSIONS (Grade 8)	BOLT THREAD LENGHT (mm)	BOLT TORQUE (Nm)
M437x0-12-12	3/4"		O83607-12	24,99x3,53	M 10	3/8-16	35	70
M686x0-12-12	3/4"		O83607-12	24,99x3,53	M 10	3/8-16	35	70
M437x0-16-16	1"		O83607-16	32,92x3,53	M 12	7/16-14	45	130
M686x0-16-16	1"		O83607-16	32,92x3,53	M 12	7/16-14	45	130
M437x0-20-20	1.1/4"		O83607-20	37,69x3,53	M 14	1/2-13	45	180
M686x0-20-20	1.1/4"		O83607-20	37,69x3,53	M 14	1/2-13	45	180
M686x0-24-24	1.1/2"		O83607-24	47,22x3,53	M 16	5/8-11	55	290
M686x0-32-32	2"		O83607-32	56,74x3,53	M 20	3/4-10	70	450
M686x0-40-32	2"		O83609-32	56,74x3,53	M 20	3/4-10	70	450
M686x0-40-40	2.1/2"		O83607-40	69,44x3,53	M 24	1-8	80	550
M686x0-48-48	3"		O83607-48	85,32x3,53	M 30	1.1/4-7	90	650

M485x0 - M685x0

PART. REF.	FLANGE SIZE	ONE-PIECE FLANGE TYPE	OR (NBR 90 ShA) SAE J515	METRIC BOLT DIMENSIONS (Class. 10.9)	UNC BOLT DIMENSIONS (Grade 8)	BOLT THREAD LENGHT (mm)	BOLT TORQUE (Nm)
M485x0-12-12	3/4"	O88507-12	24,99x3,53	M 10	3/8-16	45	70
M485x0-16-16	1"	O88507-16	32,92x3,53	M 12	7/16-14	50	130
M685x0-16-16	1"	O88507-16	32,92x3,53	M 12	7/16-14	50	130
M485x0-20-20	1.1/4"	O88507-20	37,69x3,53	M 14	1/2-13	65	180
M685x0-20-20	1.1/4"	O88507-20	37,69x3,53	M 14	1/2-13	65	180
M485x0-24-24	1.1/2"	O88507-24	47,22x3,53	M 16	5/8-11	75	290
M685x0-24-24	1.1/2"	O88507-24	47,22x3,53	M 16	5/8-11	75	290
M485x0-32-32	2"	O88507-32	56,74x3,53	M 20	3/4-10	95	450
M685x0-32-32	2"	O88507-32	56,74x3,53	M 20	3/4-10	95	450
M685x0-40-40	2.1/2"	O88507-40	69,44x3,53	M 24	1-8	110	550

SCREWS HAVE TO BE TORQUED WITH THE FOLLOWING SCHEME:


必须按下列图示顺序拧紧螺栓:

SCHRAUBEN SOLLTEN GEMÄSS FOLGENDER SKIZZE

ÜBER KREUZ ANGEZOGEN WERDEN:

I BULLONI DEVONO ESSERE LEGGERMENTE SERRATI SE-

GUENDO LO SCHEMA SEGUENTE:



During the installation it is recommended to apply a light torque to each screw before the final one to avoid:

- misalignments between flanges and clamps

- clamp halves damages during installation

安装时推荐先轻轻预紧每一个螺栓以避免:

- 法兰与管夹错位


- 安装时管夹部分损坏

XTRAFANGE ASSEMBLING SCHEME:

ESQUEMA PARA ENSAMBLAR UN XTRAFANGE:

XTRAFANSCH ANBAUSKIZZE:

SCHEMA D'ASSEMBLAGGIO DELLE XTRAFANGE:



Um Beschädigungen und Spannungen an Vollflanschen, Flanschhälften und Flanschen selbst zu vermeiden, ist es wichtig, alle Schrauben zuerst nur handfest, gleichmässig anzuziehen, bevor sie mit dem empfohlenen Drehmoment festgezogen werden.

È importante che tutti i bulloni siano leggermente avvitati prima di applicare i valori di serraggio finali raccomandati al fine di evitare: • disallineamenti tra flange e controflange (clamps) • danneggiare le mezze controflange durante l'installazione.

XTRALOCK FITTINGS CRIMPING OPERATION



The crimping operation to apply XTRALOCK fittings must be carried out with proper high performance crimping/assembly machines (crimping force higher than 2800-3000 kN) and approved by Manuli Hydraulics, in order to guarantee the optimum couplings assembly deformations and hose gripping; ■ Special crimping machines with long die sets are requested for the large size XTRALOCK fittings (double crimping operation is not recommended); ■ The use of uncut split flanges (one piece flanges) is recommended for the best performance of the assemblies in heavy duty applications; ■ It is recommended to follow the detailed assembly instructions supplied by Manuli Hydraulics to customers, assemblers and operators using the integrated package DIAMONDSPIR hose & XTRALOCK fittings.

为了保证适宜的扣压形变和胶管联接，扣压超级内锁式接头必须选用玛努利液压器材集团认可的高性能扣压/总成机器（扣压力高于2800-3000 kN）；并经由玛努利液压器材集团认可，以保证最佳连接总成变形及胶管咬合。

■ 大尺寸XTRALOCK接头需采用带加长模具的专用扣压机器（不推荐两次扣压操作）；

■ 重型应用场合为了获得最好的总成性能，推荐使用不切割整片法兰（整片式法兰）；■ 建议客户、

总成商和操作工选用DIAMONDSPIR胶管/超级内锁式接头时，遵守玛努利液压器材集团提供的详细总成说明。

Die Einbindung von XTRALOCK Armaturen muß mit entsprechenden Hochleistungspressen (Presskraft größer 2800-3000 kN) durchgeführt werden die von Manuli Hydraulics zugelassen sind; ■ Für große Nennweiten sind Spezialpressen mit langen Pressbacken erforderlich. Doppelpressungen sind nicht zu empfehlen; ■ Für beste Haltbarkeit und Performance der Schlauchleitung unter härtesten Bedingungen empfehlen wir den Einsatz von Vollflanschen; ■ Wir empfehlen sich strikt an die Anweisungen zur Einbindung zu halten, wie sie von Manuli Hydraulics zur Verfügung gestellt werden und ausschl. die integrierte Lösung DIAMONDSPIR™ Schlauch & XTRALOCK Armatur zu verwenden.

Il crimpaggio per applicare i raccordi XTRALOCK deve avvenire su presse che possano garantire performance di un certo livello (forza di crimpaggio superiore a 2800-3000 kN) e che siano approvate da Manuli Hydraulics al fine di garantire un'ottima deformazione dei raccordi nonché una perfetta presa degli stessi sul tubo; ■ Si richiedono presse speciali dotate di morsetti lunghi per raccordi XTRALOCK di grandi dimensioni (non è consigliata la doppia pressatura); ■ Si raccomanda l'utilizzo di flange a pezzo unico per ottenere una migliore riuscita degli assemblati in applicazioni molto severe; ■ Si consiglia di seguire le istruzioni dettagliate che Manuli Hydraulics fornisce ai clienti, agli assemblatori e a tutti gli operatori che utilizzano il pacchetto integrato formato da tubo DIAMONDSPIR™ e raccordi XTRALOCK.

PUSH-LOCK TYPE



BS STANDARD CONNECTIONS


L10510

BSP MALE PARALLEL 60° CONE SEAT - BS5200/ISO 8434-6

BSP 平行外螺纹 (60° 锥形底座) - BS5200/ISO 8434-6

AGR 60° INNENKONUS (BSP-GEWINDE) - BS5200/ISO 8434-6

MASCHIO GAS CILINDRICO - BS5200/ISO 8434-6



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C		H ₁	
L10510-04-04	6	1/4"	- 04	1/4" - 19	5,0	18,9	11,0		19	
L10510-04-06	6	1/4"	- 04	3/8" - 19	8,0	21,0	12,0		22	
L10510-06-06	10	3/8"	- 06	3/8" - 19	8,0	21,0	12,0		22	
L10510-08-08	12	1/2"	- 08	1/2" - 14	11,0	25,0	14,0		27	
L10510-10-10	16	5/8"	- 10	5/8" - 14	14,5	26,5	16,0		30	
L10510-12-12	19	3/4"	- 12	3/4" - 14	17,0	28,0	16,0		32	
L10510-16-16	25	1"	- 16	1" - 11	22,5	32,0	19,0		41	


L20513

BSP FEMALE 60° CONE - BS5200/ISO 12151-6 (SLIP-ON NUT)


BSP 内螺纹 (60° 锥) - BS5200/ISO 12151-6 (带滑套螺母)

DKR 90° KONUS (BSP-GEWINDE) - HINTERLEGTE MUTTER BS5200/ISO 12151-6

FEMMINA GAS CONO 90° - BS5200/ISO 12151-6 (DADO PASSANTE)



PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C			H ₂
L20513-04-04	6	1/4"	- 04	1/4" - 19	4,0	10,9	5,8			19
L20513-04-06	6	1/4"	- 04	3/8" - 19	7,0	13,0	6,0			22
L20513-06-06	10	3/8"	- 06	3/8" - 19	7,0	13,0	6,0			22
L20513-08-08	12	1/2"	- 08	1/2" - 14	9,5	14,5	6,5			27
L20513-10-10	16	5/8"	- 10	5/8" - 14	12,0	14,0	9,0			28
L20513-12-12	19	3/4"	- 12	3/4" - 14	16,0	15,5	9,0			32
L20513-12-16	19	3/4"	- 12	1" - 11	19,0	17,0	11,0			38
L20513-16-16	25	1"	- 16	1" - 11	19,0	17,0	11,0			38




L20593*

90° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200/ISO 12151-6 (SLIP-ON NUT)
 90° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200/ISO 12151-6 (带滑套螺母)
 DKR 90° BOGEN 60° KONUS (BSP-GEWINDE) - BS5200/ISO 12151-6 (HINTERLEGTE MUTTER)
 FEMMINA GAS 90° CONO 60° - BS5200/ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
L20593-04-04	6	1/4"	- 04	1/4" - 19	4,0	24,0	5,8	24,0		19
L20593-06-06	10	3/8"	- 06	3/8" - 19	7,0	32,0	6,0	32,0		22
L20593-08-08	12	1/2"	- 08	1/2" - 14	9,5	36,0	6,5	38,5		27
L20593-10-10	16	5/8"	- 10	5/8" - 14	12,0	43,5	9,0	41,0		28
L20593-12-12	19	3/4"	- 12	3/4" - 14	16,0	46,0	9,0	46,5		32
L20593-12-16	19	3/4"	- 12	1" - 11	19,0	46,0	11,0	48,5		38
L20593-16-16	25	1"	- 16	1" - 11	19,0	51,0	11,0	54,0		38

* No ferrule needed / No necesita casquillo / Keine Fassung notwendig / Ghiera non necessaria



L20543*

45° BSP FEMALE SWEPT ELBOW 60° CONE - BS5200/ISO 12151-6 (SLIP-ON NUT)
 45° BSP 内螺纹巨肘弯头 (60° 锥) - BS5200/ISO 12151-6 (带滑套螺母)
 DKR 45° BOGEN 60° KONUS (BSP-GEWINDE) - BS5200/ISO 12151-6 (HINTERLEGTE MUTTER)
 FEMMINA GAS 45° CONO 60° - BS5200/ISO 12151-6 (DADO PASSANTE)

PART. REF.	HOSE BORE			THREAD	DIMENSIONS mm					
	DN	inch	Size	T	B	A	C	E		H ₂
L20543-04-04	6	1/4"	- 04	1/4" - 19	4,0	29,0	5,8	12,0		19
L20543-06-06	10	3/8"	- 06	3/8" - 19	7,0	36,5	6,0	15,0		22
L20543-08-08	12	1/2"	- 08	1/2" - 14	9,5	42,0	6,5	18,5		27
L20543-10-10	16	5/8"	- 10	5/8" - 14	12,0	48,5	9,0	19,0		28
L20543-12-12	19	3/4"	- 12	3/4" - 14	16,0	50,5	9,0	21,0		32
L20543-16-16	25	1"	- 16	1" - 11	19,0	54,0	11,0	24,0		38

* No ferrule needed / 无需套筒 / Keine Fassung notwendig / Ghiera non necessaria

